



Safety Data Sheet

Copyright,2019, 3M Company.

All rights reserved. Copying and/or downloading of this information for the purpose of properly utilizing 3M products is allowed provided that: (1) the information is copied in full with no changes unless prior written agreement is obtained from 3M, and (2) neither the copy nor the original is resold or otherwise distributed with the intention of earning a profit thereon.

Document Group: 31-9640-9 **Version Number:** 4.01
Issue Date: 12/30/19 **Supersedes Date:** 09/11/19

SECTION 1: Identification

1.1. Product identifier

3M™ Finesse-It™ Polish - Purple, 25143, 28795, 51056, 61104

1.2. Recommended use and restrictions on use

Recommended use

Industrial use

1.3. Supplier's details

MANUFACTURER: 3M
DIVISION: Abrasive Systems Division
ADDRESS: 3M Center, St. Paul, MN 55144-1000, USA
Telephone: 1-888-3M HELPS (1-888-364-3577)

1.4. Emergency telephone number

1-800-364-3577 or (651) 737-6501 (24 hours)

SECTION 2: Hazard identification

2.1. Hazard classification

Not classified as hazardous according to OSHA Hazard Communication Standard, 29 CFR 1910.1200.

2.2. Label elements

Signal word

Not applicable.

Symbols

Not applicable.

Pictograms

Not applicable.

SECTION 3: Composition/information on ingredients

Ingredient	C.A.S. No.	% by Wt
Water	7732-18-5	60 - 80

Aluminum Oxide Mineral (nonfibrous)	1344-28-1	5 - 10
HYDROTREATED HEAVY NAPHTHA (PETROLEUM)	64742-48-9	< 10
DISTILLATES (PETROLEUM), ACID TREATED, LIGHT	64742-14-9	4 - 6
HYDROTREATED LIGHT PETROLEUM DISTILLATES	64742-47-8	4 - 6
Mineral Oil	8042-47-5	1 - 2
Light aromatic solvent naphtha (petroleum)	64742-95-6	< 0.5
1,2,4-Trimethylbenzene	95-63-6	< 0.2

SECTION 4: First aid measures

4.1. Description of first aid measures

Inhalation:

No need for first aid is anticipated.

Skin Contact:

No need for first aid is anticipated.

Eye Contact:

No need for first aid is anticipated.

If Swallowed:

Rinse mouth. If you feel unwell, get medical attention.

4.2. Most important symptoms and effects, both acute and delayed

See Section 11.1. Information on toxicological effects.

4.3. Indication of any immediate medical attention and special treatment required

Not applicable.

SECTION 5: Fire-fighting measures

5.1. Suitable extinguishing media

In case of fire: Use a fire fighting agent suitable for ordinary combustible material such as water or foam to extinguish.

5.2. Special hazards arising from the substance or mixture

Closed containers exposed to heat from fire may build pressure and explode.

Hazardous Decomposition or By-Products

Substance

Hydrocarbons
Carbon monoxide
Carbon dioxide
Oxides of Nitrogen

Condition

During Combustion
During Combustion
During Combustion
During Combustion

5.3. Special protective actions for fire-fighters

Water may not effectively extinguish fire; however, it should be used to keep fire-exposed containers and surfaces cool and prevent explosive rupture. Wear full protective clothing, including helmet, self-contained, positive pressure or pressure demand breathing apparatus, bunker coat and pants, bands around arms, waist and legs, face mask, and protective covering for exposed areas of the head.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Ventilate the area with fresh air. For large spill, or spills in confined spaces, provide mechanical ventilation to disperse or exhaust vapors, in accordance with good industrial hygiene practice. Refer to other sections of this SDS for information regarding physical and health hazards, respiratory protection, ventilation, and personal protective equipment.

6.2. Environmental precautions

Avoid release to the environment. For larger spills, cover drains and build dikes to prevent entry into sewer systems or bodies of water.

6.3. Methods and material for containment and cleaning up

Contain spill. Working from around the edges of the spill inward, cover with bentonite, vermiculite, or commercially available inorganic absorbent material. Mix in sufficient absorbent until it appears dry. Remember, adding an absorbent material does not remove a physical, health, or environmental hazard. Collect as much of the spilled material as possible. Place in a closed container approved for transportation by appropriate authorities. Clean up residue with an appropriate solvent selected by a qualified and authorized person. Ventilate the area with fresh air. Read and follow safety precautions on the solvent label and SDS. Seal the container. Dispose of collected material as soon as possible in accordance with applicable local/regional/national/international regulations.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Do not eat, drink or smoke when using this product. Wash thoroughly after handling. Avoid release to the environment.

7.2. Conditions for safe storage including any incompatibilities

No special storage requirements.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Occupational exposure limits

If a component is disclosed in section 3 but does not appear in the table below, an occupational exposure limit is not available for the component.

Ingredient	C.A.S. No.	Agency	Limit type	Additional Comments
Aluminum Oxide Mineral (nonfibrous)	1344-28-1	OSHA	TWA(as total dust):15 mg/m ³ ;TWA(respirable fraction):5 mg/m ³	
Aluminum, insoluble compounds	1344-28-1	ACGIH	TWA(respirable fraction):1 mg/m ³	A4: Not class. as human carcin
MINERAL OILS, HIGHLY-REFINED OILS	8042-47-5	ACGIH	TWA(inhalable fraction):5 mg/m ³	A4: Not class. as human carcin
Paraffin oil	8042-47-5	OSHA	TWA(as mist):5 mg/m ³	
Benzene, trimethyl-	95-63-6	ACGIH	TWA:25 ppm	

ACGIH : American Conference of Governmental Industrial Hygienists

AIHA : American Industrial Hygiene Association

CMRG : Chemical Manufacturer's Recommended Guidelines

OSHA : United States Department of Labor - Occupational Safety and Health Administration

TWA: Time-Weighted-Average

STEL: Short Term Exposure Limit

CEIL: Ceiling

8.2. Exposure controls

8.2.1. Engineering controls

No engineering controls required.

8.2.2. Personal protective equipment (PPE)**Eye/face protection**

None required.

Skin/hand protection

No chemical protective gloves are required.

Respiratory protection

None required.

SECTION 9: Physical and chemical properties**9.1. Information on basic physical and chemical properties****Appearance**

Physical state

Liquid

Color

Purple

Odor

Solvent

Odor threshold

No Data Available

pH

7.5 - 8

Melting point

No Data Available

Boiling Point

212 °F

Flash Point

>=200 °F [*Test Method*:Closed Cup]

Evaporation rate

No Data Available

Flammability (solid, gas)

Not Applicable

Flammable Limits(LEL)

No Data Available

Flammable Limits(UEL)

No Data Available

Vapor Pressure

18 mmHg [*@ 20 °C*]

Vapor Density

No Data Available

Density

0.96 - 0.98 g/ml

Specific Gravity

0.96 - 0.98 [*Ref.Std*:WATER=1]

Solubility In Water

No Data Available

Solubility- non-water

No Data Available

Partition coefficient: n-octanol/ water

No Data Available

Autoignition temperature

No Data Available

Decomposition temperature

No Data Available

Viscosity

14,000 - 19,000 centipoise [*Test Method*:Brookfield]

Molecular weight

No Data Available

VOC Less H2O & Exempt Solvents

633.2 g/l [*Test Method*:tested per EPA method 24]

SECTION 10: Stability and reactivity**10.1. Reactivity**

This material is considered to be non reactive under normal use conditions.

10.2. Chemical stability

Stable.

10.3. Possibility of hazardous reactions

Hazardous polymerization will not occur.

10.4. Conditions to avoid

None known.

10.5. Incompatible materials

None known.

10.6. Hazardous decomposition products**Substance****Condition**

None known.

Refer to section 5.2 for hazardous decomposition products during combustion.

SECTION 11: Toxicological information

The information below may not be consistent with the material classification in Section 2 if specific ingredient classifications are mandated by a competent authority. In addition, toxicological data on ingredients may not be reflected in the material classification and/or the signs and symptoms of exposure, because an ingredient may be present below the threshold for labeling, an ingredient may not be available for exposure, or the data may not be relevant to the material as a whole.

11.1. Information on Toxicological effects**Signs and Symptoms of Exposure**

Based on test data and/or information on the components, this material may produce the following health effects:

Inhalation:

No known health effects.

Skin Contact:

Contact with the skin during product use is not expected to result in significant irritation.

Eye Contact:

Contact with the eyes during product use is not expected to result in significant irritation.

Ingestion:

Gastrointestinal Irritation: Signs/symptoms may include abdominal pain, stomach upset, nausea, vomiting and diarrhea.

Toxicological Data

If a component is disclosed in section 3 but does not appear in a table below, either no data are available for that endpoint or the data are not sufficient for classification.

Acute Toxicity

Name	Route	Species	Value
Overall product	Inhalation-Vapor(4 hr)		No data available; calculated ATE >50 mg/l
Overall product	Ingestion		No data available; calculated ATE >5,000 mg/kg
HYDROTREATED HEAVY NAPHTHA (PETROLEUM)	Inhalation-Vapor	Professional judgement	LC50 estimated to be 20 - 50 mg/l
HYDROTREATED HEAVY NAPHTHA (PETROLEUM)	Dermal	Rabbit	LD50 > 5,000 mg/kg

HYDROTREATED HEAVY NAPHTHA (PETROLEUM)	Ingestion	Rat	LD50 > 5,000 mg/kg
Aluminum Oxide Mineral (nonfibrous)	Dermal		LD50 estimated to be > 5,000 mg/kg
Aluminum Oxide Mineral (nonfibrous)	Inhalation-Dust/Mist (4 hours)	Rat	LC50 > 2.3 mg/l
Aluminum Oxide Mineral (nonfibrous)	Ingestion	Rat	LD50 > 5,000 mg/kg
HYDROTREATED LIGHT PETROLEUM DISTILLATES	Inhalation-Vapor	Professional judgement	LC50 estimated to be 20 - 50 mg/l
HYDROTREATED LIGHT PETROLEUM DISTILLATES	Dermal	Rabbit	LD50 > 5,000 mg/kg
HYDROTREATED LIGHT PETROLEUM DISTILLATES	Ingestion	Rat	LD50 > 5,000 mg/kg
DISTILLATES (PETROLEUM), ACID TREATED, LIGHT	Inhalation-Vapor	Professional judgement	LC50 estimated to be 20 - 50 mg/l
DISTILLATES (PETROLEUM), ACID TREATED, LIGHT	Dermal	Rabbit	LD50 > 5,000 mg/kg
DISTILLATES (PETROLEUM), ACID TREATED, LIGHT	Ingestion	Rat	LD50 > 5,000 mg/kg
Mineral Oil	Dermal	Rabbit	LD50 > 2,000 mg/kg
Mineral Oil	Ingestion	Rat	LD50 > 5,000 mg/kg
Light aromatic solvent naphtha (petroleum)	Dermal	Rabbit	LD50 > 2,000 mg/kg
Light aromatic solvent naphtha (petroleum)	Inhalation-Vapor (4 hours)	Rat	LC50 > 5.2 mg/l
Light aromatic solvent naphtha (petroleum)	Ingestion	Rat	LD50 > 5,000 mg/kg
1,2,4-Trimethylbenzene	Dermal	Rabbit	LD50 > 3,160 mg/kg
1,2,4-Trimethylbenzene	Inhalation-Vapor (4 hours)	Rat	LC50 18 mg/l
1,2,4-Trimethylbenzene	Ingestion	Rat	LD50 3,400 mg/kg

ATE = acute toxicity estimate

Skin Corrosion/Irritation

Name	Species	Value
HYDROTREATED HEAVY NAPHTHA (PETROLEUM)	Rabbit	Mild irritant
Aluminum Oxide Mineral (nonfibrous)	Rabbit	No significant irritation
HYDROTREATED LIGHT PETROLEUM DISTILLATES	Rabbit	Minimal irritation
DISTILLATES (PETROLEUM), ACID TREATED, LIGHT	Rabbit	Minimal irritation
Mineral Oil	Rabbit	No significant irritation
Light aromatic solvent naphtha (petroleum)	Rabbit	Irritant
1,2,4-Trimethylbenzene	Rabbit	Irritant

Serious Eye Damage/Irritation

Name	Species	Value
HYDROTREATED HEAVY NAPHTHA (PETROLEUM)	Rabbit	Mild irritant
Aluminum Oxide Mineral (nonfibrous)	Rabbit	No significant irritation
HYDROTREATED LIGHT PETROLEUM DISTILLATES	Rabbit	Mild irritant
DISTILLATES (PETROLEUM), ACID TREATED, LIGHT	Rabbit	Mild irritant
Mineral Oil	Rabbit	Mild irritant
Light aromatic solvent naphtha (petroleum)	Rabbit	Mild irritant
1,2,4-Trimethylbenzene	Rabbit	Mild irritant

Skin Sensitization

Name	Species	Value
HYDROTREATED HEAVY NAPHTHA (PETROLEUM)	Guinea pig	Not classified
HYDROTREATED LIGHT PETROLEUM DISTILLATES	Guinea pig	Not classified
DISTILLATES (PETROLEUM), ACID TREATED, LIGHT	Guinea pig	Not classified
Mineral Oil	Guinea	Not classified

Light aromatic solvent naphtha (petroleum)	pig Guinea	Not classified
1,2,4-Trimethylbenzene	pig Guinea	Not classified

Respiratory Sensitization

For the component/components, either no data are currently available or the data are not sufficient for classification.

Germ Cell Mutagenicity

Name	Route	Value
HYDROTREATED HEAVY NAPHTHA (PETROLEUM)	In Vitro	Not mutagenic
HYDROTREATED HEAVY NAPHTHA (PETROLEUM)	In vivo	Not mutagenic
Aluminum Oxide Mineral (nonfibrous)	In Vitro	Not mutagenic
HYDROTREATED LIGHT PETROLEUM DISTILLATES	In Vitro	Not mutagenic
HYDROTREATED LIGHT PETROLEUM DISTILLATES	In vivo	Not mutagenic
DISTILLATES (PETROLEUM), ACID TREATED, LIGHT	In Vitro	Not mutagenic
DISTILLATES (PETROLEUM), ACID TREATED, LIGHT	In vivo	Not mutagenic
Mineral Oil	In Vitro	Not mutagenic
1,2,4-Trimethylbenzene	In Vitro	Not mutagenic

Carcinogenicity

Name	Route	Species	Value
HYDROTREATED HEAVY NAPHTHA (PETROLEUM)	Not Specified	Not available	Not carcinogenic
Aluminum Oxide Mineral (nonfibrous)	Inhalation	Rat	Not carcinogenic
HYDROTREATED LIGHT PETROLEUM DISTILLATES	Not Specified	Not available	Not carcinogenic
DISTILLATES (PETROLEUM), ACID TREATED, LIGHT	Not Specified	Not available	Not carcinogenic
Mineral Oil	Dermal	Mouse	Not carcinogenic
Mineral Oil	Inhalation	Multiple animal species	Not carcinogenic
Light aromatic solvent naphtha (petroleum)	Inhalation	Mouse	Some positive data exist, but the data are not sufficient for classification

Reproductive Toxicity

Reproductive and/or Developmental Effects

Name	Route	Value	Species	Test Result	Exposure Duration
HYDROTREATED HEAVY NAPHTHA (PETROLEUM)	Not Specified	Not classified for female reproduction	Rat	NOAEL Not available	1 generation
HYDROTREATED HEAVY NAPHTHA (PETROLEUM)	Not Specified	Not classified for male reproduction	Rat	NOAEL Not available	28 days
HYDROTREATED HEAVY NAPHTHA (PETROLEUM)	Not Specified	Not classified for development	Rat	NOAEL Not available	during gestation
HYDROTREATED LIGHT PETROLEUM DISTILLATES	Not Specified	Not classified for female reproduction	Rat	NOAEL Not available	1 generation
HYDROTREATED LIGHT PETROLEUM DISTILLATES	Not Specified	Not classified for male reproduction	Rat	NOAEL Not available	28 days
HYDROTREATED LIGHT PETROLEUM DISTILLATES	Not Specified	Not classified for development	Rat	NOAEL Not available	during gestation
DISTILLATES (PETROLEUM), ACID TREATED, LIGHT	Not Specified	Not classified for female reproduction	Rat	NOAEL Not available	1 generation
DISTILLATES (PETROLEUM), ACID TREATED, LIGHT	Not Specified	Not classified for male reproduction	Rat	NOAEL Not available	1 generation
DISTILLATES (PETROLEUM), ACID TREATED, LIGHT	Not Specified	Not classified for development	Rat	NOAEL Not available	1 generation
Mineral Oil	Ingestion	Not classified for female reproduction	Rat	NOAEL 4,350 mg/kg/day	13 weeks

Mineral Oil	Ingestion	Not classified for male reproduction	Rat	NOAEL 4,350 mg/kg/day	13 weeks
Mineral Oil	Ingestion	Not classified for development	Rat	NOAEL 4,350 mg/kg/day	during gestation
Light aromatic solvent naphtha (petroleum)	Inhalation	Not classified for female reproduction	Rat	NOAEL 1,500 ppm	2 generation
Light aromatic solvent naphtha (petroleum)	Inhalation	Not classified for male reproduction	Rat	NOAEL 1,500 ppm	2 generation
Light aromatic solvent naphtha (petroleum)	Inhalation	Not classified for development	Rat	NOAEL 500 ppm	2 generation
1,2,4-Trimethylbenzene	Inhalation	Not classified for female reproduction	Rat	NOAEL 1.2 mg/l	3 months
1,2,4-Trimethylbenzene	Inhalation	Not classified for male reproduction	Rat	NOAEL 1.2 mg/l	3 months
1,2,4-Trimethylbenzene	Inhalation	Not classified for development	Rat	NOAEL 1.5 mg/l	during gestation

Target Organ(s)

Specific Target Organ Toxicity - single exposure

Name	Route	Target Organ(s)	Value	Species	Test Result	Exposure Duration
HYDROTREATED HEAVY NAPHTHA (PETROLEUM)	Inhalation	central nervous system depression	May cause drowsiness or dizziness	Human and animal	NOAEL Not available	
Light aromatic solvent naphtha (petroleum)	Inhalation	central nervous system depression	May cause drowsiness or dizziness	Professional judgement	NOAEL Not available	
Light aromatic solvent naphtha (petroleum)	Inhalation	respiratory irritation	Some positive data exist, but the data are not sufficient for classification	Professional judgement	NOAEL Not available	
Light aromatic solvent naphtha (petroleum)	Ingestion	central nervous system depression	May cause drowsiness or dizziness	Professional judgement	NOAEL Not available	
1,2,4-Trimethylbenzene	Inhalation	central nervous system depression	May cause drowsiness or dizziness	Human and animal	NOAEL Not available	
1,2,4-Trimethylbenzene	Inhalation	respiratory irritation	May cause respiratory irritation	official classification	NOAEL Not available	
1,2,4-Trimethylbenzene	Ingestion	central nervous system depression	May cause drowsiness or dizziness	Professional judgement	NOAEL Not available	

Specific Target Organ Toxicity - repeated exposure

Name	Route	Target Organ(s)	Value	Species	Test Result	Exposure Duration
Aluminum Oxide Mineral (nonfibrous)	Inhalation	pneumoconiosis	Some positive data exist, but the data are not sufficient for classification	Human	NOAEL Not available	occupational exposure
Aluminum Oxide Mineral (nonfibrous)	Inhalation	pulmonary fibrosis	Not classified	Human	NOAEL Not available	occupational exposure
Mineral Oil	Ingestion	hematopoietic system	Not classified	Rat	NOAEL 1,381 mg/kg/day	90 days
Mineral Oil	Ingestion	liver immune system	Not classified	Rat	NOAEL 1,336 mg/kg/day	90 days
1,2,4-Trimethylbenzene	Inhalation	hematopoietic system	Some positive data exist, but the data are not sufficient for classification	Rat	NOAEL 0.5 mg/l	3 months
1,2,4-Trimethylbenzene	Inhalation	nervous system	Some positive data exist, but the	Rat	LOAEL 0.1	3 months

			data are not sufficient for classification		mg/l	
1,2,4-Trimethylbenzene	Inhalation	respiratory system	Some positive data exist, but the data are not sufficient for classification	Human	NOAEL Not available	occupational exposure
1,2,4-Trimethylbenzene	Inhalation	liver kidney and/or bladder heart endocrine system gastrointestinal tract immune system	Not classified	Rat	NOAEL 1.2 mg/l	3 months
1,2,4-Trimethylbenzene	Ingestion	hematopoietic system	Not classified	Rat	NOAEL 600 mg/kg/day	14 days
1,2,4-Trimethylbenzene	Ingestion	liver immune system kidney and/or bladder	Not classified	Rat	NOAEL 1,000 mg/kg/day	28 days

Aspiration Hazard

Name	Value
HYDROTREATED HEAVY NAPHTHA (PETROLEUM)	Aspiration hazard
HYDROTREATED LIGHT PETROLEUM DISTILLATES	Aspiration hazard
DISTILLATES (PETROLEUM), ACID TREATED, LIGHT	Aspiration hazard
Mineral Oil	Aspiration hazard
Light aromatic solvent naphtha (petroleum)	Aspiration hazard
1,2,4-Trimethylbenzene	Aspiration hazard

Please contact the address or phone number listed on the first page of the SDS for additional toxicological information on this material and/or its components.

SECTION 12: Ecological information

Ecotoxicological information

Please contact the address or phone number listed on the first page of the SDS for additional ecotoxicological information on this material and/or its components.

Chemical fate information

Please contact the address or phone number listed on the first page of the SDS for additional chemical fate information on this material and/or its components.

SECTION 13: Disposal considerations

13.1. Disposal methods

Dispose of contents/ container in accordance with the local/regional/national/international regulations.

Dispose of waste product in a permitted industrial waste facility. As a disposal alternative, incinerate in a permitted waste incineration facility. Proper destruction may require the use of additional fuel during incineration processes. Empty drums/barrels/containers used for transporting and handling hazardous chemicals (chemical substances/mixtures/preparations classified as Hazardous as per applicable regulations) shall be considered, stored, treated & disposed of as hazardous wastes unless otherwise defined by applicable waste regulations. Consult with the respective regulating authorities to determine the available treatment and disposal facilities.

EPA Hazardous Waste Number (RCRA): Not regulated

SECTION 14: Transport Information

For Transport Information, please visit <http://3M.com/Transportinfo> or call 1-800-364-3577 or 651-737-6501.

SECTION 15: Regulatory information**15.1. US Federal Regulations**

Contact 3M for more information.

EPCRA 311/312 Hazard Classifications:**Physical Hazards**

Not applicable

Health Hazards

Not applicable

15.2. State Regulations

Contact 3M for more information.

15.3. Chemical Inventories

The components of this product are in compliance with the chemical notification requirements of TSCA. All required components of this product are listed on the active portion of the TSCA Inventory.

Contact 3M for more information.

15.4. International Regulations

Contact 3M for more information.

This SDS has been prepared to meet the U.S. OSHA Hazard Communication Standard, 29 CFR 1910.1200.

SECTION 16: Other information**NFPA Hazard Classification**

Health: 0 **Flammability:** 1 **Instability:** 0 **Special Hazards:** None

National Fire Protection Association (NFPA) hazard ratings are designed for use by emergency response personnel to address the hazards that are presented by short-term, acute exposure to a material under conditions of fire, spill, or similar emergencies. Hazard ratings are primarily based on the inherent physical and toxic properties of the material but also include the toxic properties of combustion or decomposition products that are known to be generated in significant quantities.

HMIS Hazard Classification

Health: 0 **Flammability:** 1 **Physical Hazard:** 0 **Personal Protection:** X - See PPE section.

Hazardous Material Identification System (HMIS® IV) hazard ratings are designed to inform employees of chemical hazards in the workplace. These ratings are based on the inherent properties of the material under expected conditions of normal use and are not intended for use in emergency situations. HMIS® IV ratings are to be used with a fully implemented HMIS® IV program. HMIS® is a registered mark of the American Coatings Association (ACA).

Document Group: 31-9640-9

Version Number: 4.01

Issue Date: 12/30/19

Supersedes Date: 09/11/19

DISCLAIMER: The information in this Safety Data Sheet (SDS) is believed to be correct as of the date issued. 3M MAKES NO WARRANTIES, EXPRESSED OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE OR COURSE OF PERFORMANCE OR USAGE OF TRADE. User is responsible for determining whether the 3M product is fit for a particular purpose and suitable for user's method of use or application. Given the variety of factors that can affect the use and application of a 3M product,

some of which are uniquely within the user's knowledge and control, it is essential that the user evaluate the 3M product to determine whether it is fit for a particular purpose and suitable for user's method of use or application.

3M provides information in electronic form as a service to its customers. Due to the remote possibility that electronic transfer may have resulted in errors, omissions or alterations in this information, 3M makes no representations as to its completeness or accuracy. In addition, information obtained from a database may not be as current as the information in the SDS available directly from 3M.

3M USA SDSs are available at www.3M.com