

# Safety Data Sheet

Product Name: Cut-In-Clear

Product identifier: 100718

Revision Date: 06-09-2015

Replaces:

# EVERCOAT®

## 1. Identification

**Product Name:** Cut-In-Clear

**Product identifier:** 100718

**Relevant identified uses of the substance or mixture and uses advised against:** Clearcoat

**Chemical Manufacturer / Importer / Distributor:** ITW Evercoat  
a division of Illinois Tool Works Inc.  
6600 Cornell Road  
Cincinnati, OH 45242  
513-489-7600

**Emergency telephone number:** CHEMTREC: 1-800-424-9300  
CANUTEC: 1-613-996-6666

## 2. Hazard(s) identification

**Classification of the chemical in accordance with paragraph (d) of §1910.1200;**

**GHS Hazard Symbols:**



**GHS Classification:** Germ Cell Mutagenicity Category 1B  
Carcinogenicity Category 1A  
Serious Eye Damage/Eye Irritation Category 2A  
Reproductive Toxicity Category 2  
Specific Target Organ Systemic Toxicity (STOT) - Repeated Exposure Category 2  
Specific Target Organ Systemic Toxicity (STOT) - Single Exposure Category 3  
Hazardous to the aquatic environment - Acute Category 3

**GHS Signal Word:** Danger

**GHS Hazard Statements:** Causes serious eye irritation.  
May cause drowsiness or dizziness.  
May cause genetic defects..  
May cause cancer.  
Suspected of damaging fertility or the unborn child.  
May cause damage to organs through prolonged or repeated exposure.  
Harmful to aquatic life.

# Safety Data Sheet

Product Name: Cut-In-Clear

Product identifier: 100718

Revision Date: 06-09-2015

Replaces:

## GHS Precautionary Statements:

### Safety Precautions:

Obtain special instructions before use.  
Do not handle until all safety precautions have been read and understood.  
Do not breathe dust/fume/gas/mist/vapours/spray.  
Avoid breathing dust/fume/gas/mist/vapours/spray.  
Wash thoroughly after handling.  
Use only outdoors or in a well-ventilated area.  
Avoid release to the environment.  
Wear protective gloves/protective clothing/eye protection/face protection.  
Use personal protective equipment as required.

### First Aid Measures:

IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.  
IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.  
IF exposed or concerned: Get medical advice/attention.  
Call a POISON CENTER or doctor/physician if you feel unwell.  
Get medical advice/attention if you feel unwell.  
If eye irritation persists: Get medical advice/attention.

### Storage:

Store in a well-ventilated place. Keep container tightly closed.  
Store locked up.

### Disposal:

Dispose of contents/container in accordance with local/regional/national/international regulation for hazardous wastes.

### Hazards not otherwise classified:

Reports have associated repeated and prolonged occupational overexposure to solvents with permanent brain and nervous system damage.

## 3. Composition/information on ingredients

Chemical Component:	CAS number and other unique identifiers	% (or range) of ingredient
Acetone	67-64-1	10 - 30
Propane	74-98-6	10 - 30
Isobutane	75-28-5	5 - 10
Toluene	108-88-3	1 - 5
n-Butyl acetate	123-86-4	1 - 5
4-Hydroxy-4-methyl-2-pentanone	123-42-2	1 - 5

the specific chemical identity and/or exact percentage (concentration) of composition has been withheld as a trade secret is required.

# Safety Data Sheet

Product Name: Cut-In-Clear

Product identifier: 100718

Revision Date: 06-09-2015

Replaces:

## 4. First-aid measures

<b>Eye Contact:</b>	Immediately flush eyes with plenty of water for at least 20 minutes retracting eyelids often. Tilt the head to prevent chemical from transferring to the uncontaminated eye. Get immediate medical attention and monitor the eye daily as advised by your physician. Flush eyes gently with water for at least 15 minutes, lifting upper & lower eye lids. Seek immediate medical attention.
<b>Skin Contact:</b>	Wash with soap and water. Remove contaminated clothing and launder. Get medical attention if irritation develops or persists. Remove contaminated clothing and continue flushing with water. Wash affected area thoroughly with soap and water. Seek medical advice if symptoms persist Wash clothing before reuse.
<b>Inhalation:</b>	Remove to fresh air. If breathing is difficult, have a trained individual administer oxygen. If not breathing, give artificial respiration and have a trained individual administer oxygen. Get medical attention immediately. If symptoms develop, immediately move individual away from exposure and into fresh air. Get medical attention immediately. Keep the victim warm and quiet. If the victim has stopped breathing open airway, loosen collar and belt, and administer artificial respiration. If breathing is difficult, oxygen may be beneficial if administered by trained personnel, preferably on a doctor's advice.
<b>Ingestion:</b>	Do not induce vomiting and seek medical attention immediately. Drink two glasses of water or milk to dilute. Provide medical care provider with this MSDS. Call a physician or poison control center immediately. Do not induce vomiting unless directed to do so by medical personnel. If individual is drowsy or unconscious, do not give anything by mouth; place individual on left side with head down. If possible, do not leave individual unattended. If vomiting occurs spontaneously, keep head below hips to prevent aspiration of liquid into lungs.
<b>Most important symptoms/effects (Delayed:</b>	Solvents may cause defatting dermatitis. Toluene may be harmful to the human fetus based on positive results with laboratory animals. Overexposure to Toluene has been suggested as a cause of the following effects in humans: cardiac sensitization, kidney damage. The substance may have effects on the central nervous system, resulting in decreased learning ability and psychological disorders.
<b>Immediate medical attention and special treatment needed,:</b>	No additional first aid information available

# Safety Data Sheet

Product Name: Cut-In-Clear

Product identifier: 100718

Revision Date: 06-09-2015

Replaces:

## 5. Fire-fighting measures

**Suitable extinguishing media:** Use alcohol resistant foam, carbon dioxide, or dry chemical extinguishing agents. Water spray or fog may also be effective for extinguishing if swept across the base of the fire. Water can also be used to absorb heat and keep exposed material from being damaged by fire. Regular foam Carbon dioxide Dry chemical

**Unsuitable extinguishing media:** No data available

**Fire and/or Explosion Hazards:** Vapors may be ignited by heat, sparks, flames or other sources of ignition at or above the low flash point giving rise to a Class B fire. Vapors are heavier than air and may travel to a source of ignition and flash back. Aerosol containers may explode when exposed to extreme heat.

Contents under pressure.

**Hazardous Combustion**

Toxic and corrosive gases,, Carbon monoxide, Hydrocarbons

**Products:**

**Special protective equipment and precautions for fire-fighters:**

Do not enter fire area without proper protection including self-contained toxic breathing apparatus and full protective equipment. Fight fire from a safe distance and a protected location due to the potential of hazardous vapors and decomposition products. Flammable component(s) of this material may be lighter than water and burn while floating on the surface. Use water spray/fog for cooling. Water may be used to cool closed containers to prevent pressure build-up and possible auto ignition or explosion when exposed to extreme heat.

Wear a self contained breathing apparatus (NIOSH approved) with a full face piece operated in the positive pressure demand mode with appropriate turn-out gear and chemical resistant personal protective equipment.

## 6. Accidental release measures

**Personal precautions, protective equipment and emergency procedures:**

Exposure to the spilled material may be irritating or harmful. Follow personal protective equipment recommendations found in Section VIII of this MSDS. Additional precautions may be necessary based on special circumstances created by the spill including; the material spilled, the quantity of the spill, the area in which the spill occurred. Also consider the expertise of employees in the area responding to the spill.

**Methods and material for containment and cleaning up:**

Prevent the spread of any spill to minimize harm to human health and the environment if safe to do so. Wear complete and proper personal protective equipment following the recommendation of Section VIII at a minimum. Dike with suitable absorbent material like granulated clay. Gather and store in a sealed container pending

# Safety Data Sheet

**Product Name:** Cut-In-Clear

**Product identifier:** 100718

**Revision Date:** 06-09-2015

**Replaces:**

a waste disposal evaluation. Shut off ignition sources; including electrical equipment and flames. Do not allow smoking in the area. Activate available exhaust ventilation equipment in the immediate spill area. All personnel in the area should be protected as in Section 8. Avoid breathing vapors. Use an inert absorbent such as sand or vermiculite. Place in properly labeled closed container.

## 7. Handling and storage

**Precautions for safe handling:** Harmful or irritating material. Avoid contacting and avoid breathing the material. Use only in a well ventilated area. All hazard precautions given in the data sheet must be observed. Do not get in eyes, on skin and clothing Wash hands before eating Use with adequate ventilation Avoid contact with material, avoid breathing dusts or fumes, use only in a well ventilated area. Do not take internally. Keep out of the reach of children.

**Conditions for safe storage:** Store in a cool dry ventilated location. Isolate from incompatible materials and conditions. Keep container(s) closed. Store in a cool dry place Contents under pressure. Do not puncture or incinerate. Do not store above 120° F (49° C). For maximum product quality, avoid prolonged storage at temperatures above 75 °F (25 °C). Keep away from heat, sparks, and flame Store in a tightly closed container Avoid contact with incompatible materials.

**Materials to Avoid/Chemical Incompatibility::** Strong oxidizing agents

## 8. Exposure controls/personal protection

### Limits:

Chemical Component	OSHA PEL	ACGIH TLV-TWA	ACGIH STEL
Acetone	1000 ppm	500 ppm	750 ppm
Propane	1000 ppm	2500 ppm	
Isobutane	No PEL established	1000 ppm	
Toluene	100 ppm	100 ppm	
4-Hydroxy-4-methyl-2-pentanone	50 ppm	50 ppm	
n-Butyl acetate	150 ppm	150 ppm	200 ppm STEL; 950 mg/m3 STEL

**Appropriate engineering controls.:** No exposure limits exist for the constituents of this product. Use local exhaust ventilation or other engineering controls to minimize

# Safety Data Sheet

**Product Name:** Cut-In-Clear

**Product identifier:** 100718

**Revision Date:** 06-09-2015

**Replaces:**

---

exposures and maintain operator comfort. General or local ventilation or isolation may prove adequate to keep airborne exposures below exposure limits. Explosion proof exhaust ventilation should be used.

**Eye Protection:**

Wear chemically resistant safety glasses with side shields when handling this product. Wear additional eye protection such as chemical splash goggles and/or face shield when the possibility exists for eye contact with splashing or spraying liquid, or airborne material. Do not wear contact lenses. Have an eye wash station available. Splash proof chemical goggles are recommended to protect against the splash of product.

**Skin Protection:**

Wear protective gloves. Inspect gloves for chemical break-through and replace at regular intervals. Clean protective equipment regularly. Wash hands and other exposed areas with mild soap and water before eating, drinking, and when leaving work. Protective gloves and proper clothing should be worn to prevent skin contact. Gloves should be made of neoprene or natural rubber. To prevent repeated or prolonged skin contact, wear impervious clothing and boots.

**Respiratory Protection:**

Respiratory protection may be required to avoid overexposure when handling this product. General or local exhaust ventilation is the preferred means of protection. Use a respirator if general room ventilation is not available or sufficient to eliminate symptoms. Use a NIOSH approved respirator designed to remove particulate matter and organic solvent vapors. NIOSH approved air purifying respirator with organic vapor cartridge and HEPA filter. Air purifying respirators should not be used in oxygen deficient or IDLH atmospheres.

**Other Protective Equipment:**

Splash proof chemical goggles are recommended to protect against the splash of product. Protective gloves and proper clothing should be worn to prevent skin contact. Gloves should be made of neoprene or natural rubber. To prevent repeated or prolonged skin contact, wear impervious clothing and boots.

**General Hygiene Conditions:**

All hazard precautions given in the data sheet must be observed. Do not get in eyes, on skin and clothing. Wash hands before eating. Use with adequate ventilation. Avoid contact with material, avoid breathing dusts or fumes, use only in a well ventilated area. Do not take internally. Keep out of the reach of children.

<b>9. Physical and chemical properties</b>
--

**Appearance (physical state):**

Aerosol

**Color:**

Clear

**Odor:**

Ketone

# Safety Data Sheet

Product Name: Cut-In-Clear

Product identifier: 100718

Revision Date: 06-09-2015

Replaces:

Odor threshold:	No data available
pH:	No data available
Melting Point/Freezing Point (°C):	No data available
Initial Boiling Point and Boiling Range (°C):	-42
Flash Point (°C):	-18
Evaporation Rate:	No data available
Flammability (solid, gas):	No data available
Upper Flammable/Explosive Limit:	15.1
Lower Flammable/Explosive Limit:	1
Vapor Pressure:	6384 MMHG@20C/68F 21 MMHG@20C/68F
Vapor Density:	Heavier than air. Vapors that evolve from this product will tend to settle and accumulate near the floor.
Relative Density:	Not determined
Solubility(ies):	Complete; 100%
Partition coefficient: n-octanol/water:	2.36 2.76
Auto-ignition Temperature (°C):	420 °C
Decomposition Temperature::	No data available
Viscosity:	No data available
VOC (as packaged-less exempts and water)	0.6 or

## 10. Stability and reactivity

Reactivity:	No data available
Chemical stability:	Stable under normal conditions.
Conditions to avoid:	None known. Contamination.
Incompatible materials:	Strong oxidizing agents
Hazardous decomposition products:	Carbon dioxide Carbon monoxide Hydrocarbons

## 11. Toxicological information

Likely routes of exposure (inhalation, ingestion, skin and eye contact): Skin contact, Eye contact, Ingestion

### Immediate (Acute) Health Effects by Route of Exposure:

Inhalation Irritation:	Can cause moderate respiratory irritation, dizziness, weakness, fatigue, nausea and headache. Excessive inhalation of vapors may cause nasal and respiratory irritation, acute nervous system depression, fatigue, weakness, nausea, headache and dizziness. Airborne overexposure well above the PEL may result additionally in eye irritation, headache, chemical bronchitis, asthma-like findings or pulmonary edema.
Inhalation Toxicity:	Harmful! Can cause systemic damage (see "Target Organs)
Skin Contact:	Can cause moderate skin irritation, defatting, and dermatitis. Not likely to cause permanent damage.

# Safety Data Sheet

Product Name: Cut-In-Clear

Product identifier: 100718

Revision Date: 06-09-2015

Replaces:

- Skin Absorption:** Harmful if absorbed through the skin. May cause severe irritation and systemic damage. Can cause irritation.
- Eye Contact:** Contact with the eyes may cause moderate to severe eye injury. Eye contact may result in tearing and reddening, but not likely to permanently injure eye tissue. Temporary vision impairment (cloudy or blurred vision) is possible. Can cause irritation.
- Ingestion Irritation:** Irritating to mouth, throat, and stomach. Can cause abdominal discomfort, nausea, vomiting and diarrhea. May cause headache, nausea, vomiting and weakness. Aspiration of material into the lungs can cause chemical pneumonitis which can be fatal. Not expected to be a relevant route of exposure for an aerosol container.
- Ingestion Toxicity:** Harmful if swallowed. May cause systemic poisoning.

**Long-Term (Chronic) Health Effects:**

- Carcinogenicity:** None of the substances have been shown to cause cancer in long term animal studies. Not a carcinogen according to NTP, IARC, or OSHA. Not listed by ACGIH, IARC, NIOSH, NTP OR OSHA.
- Reproductive and Developmental Toxicity:** No data available to indicate product or any components present at greater than 0.1% may cause birth defects.
- Mutagenicity:** No data available to indicate product or any components present at greater than 0.1% is mutagenic or genotoxic.
- Inhalation:** Upon prolonged and/or repeated exposure, can cause moderate respiratory irritation, dizziness, weakness, fatigue, nausea and headache. Upon prolonged and/or repeated exposure, can cause moderate respiratory irritation, dizziness, weakness, fatigue, nausea and headache. Harmful! Can cause systemic damage upon prolonged and/or repeated exposure (see "Target Organs")
- Skin Contact:** Upon prolonged or repeated contact, can cause moderate skin irritation, defatting, and dermatitis. Not likely to cause permanent damage.
- Skin Absorption:** Upon prolonged or repeated exposure, harmful if absorbed through the skin. May cause severe irritation and systemic damage.

**Component Toxicology Data**

Chemical Component	Oral LD50	Dermal LD50	Inhalation LC50
No data available			

**Has the chemical been classified as a Carcinogen by NTP, IARC or OSHA.**

Chemical Name	OSHA Carcinogen	IARC Carcinogen	NTP Carcinogen
No data available			

# Safety Data Sheet

Product Name: Cut-In-Clear

Product identifier: 100718

Revision Date: 06-09-2015

Replaces:

## 12. Ecological information

**Ecotoxicity (aquatic and terrestrial, where available):** This material is not expected to be harmful to the ecology. This material is toxic to aquatic organisms and should not be released to sewage, draining systems or any body of water exceeding concentrations of approved limits under applicable regulations and permits.

**Persistence and degradability:** No data available

**Mobility in soil:** No data available

**Other adverse effects (such as hazardous to the ozone layer):** No data available

### Ecological Toxicity Data

Chemical Component	Aquatic EC50 Crustacea	Aquatic ERC50 Algae	Aquatic LC50 Fish
No data available			

## 13. Disposal considerations

**Description of waste residues:** Spent or discarded material is a hazardous waste.

**Safe Handling of Waste:** This material as supplied, if discarded, would be regulated as a hazardous waste under RCRA (40 CFR 261).

**Waste treatment methods (including packaging):** Dispose of by incineration following Federal, State, Local, or Provincial regulations.

**Waste Disposal Code(s):** D001

## 14. Transport information

**UN proper shipping name:** The DOT Classification for shipping is dependent on quantity, type of packaging (a kit may include other components), or method of shipment.

## 15. Regulatory information

**TSCA Status:** The intentional ingredients of this product are listed.

### Regulated Components:

Chemical Component	CAS number and other unique identifiers	CERCLA	SARA EHS	SARA 313	California Prop 65
Acetone	67-64-1	N	N	Y	N
Toluene	108-88-3	N	N	Y	Y

# Safety Data Sheet

Product Name: Cut-In-Clear

Product identifier: 100718

Revision Date: 06-09-2015

Replaces:

---

<b>16. Other information, including date of preparation or last revision.</b>
---

Revision Date: 06-09-2015

Revision Number: 3

**Disclaimer:** NOTICE: The information accumulated herein is believed to be correct as of the date issued from sources, which are believed to be accurate and reliable. Since it is not possible to anticipate all circumstances of use, recipients are advised to confirm, in advance of need, that the information is current, applicable and suitable to their circumstances