



**Safety Data Sheet**  
acc. to OSHA HCS

Printing date 07/16/2025

Reviewed on 07/16/2025

**1 Identification**

- **Product identifier**
- **Trade name:** HIT\_2415-1 NR SCHOOL BUS YELLOW 2K SS FPC
- **Article number:** 2415
- **Details of the supplier of the safety data sheet**
- **Manufacturer/Supplier:**  
HIGH TECK PRODUCTS  
PO BOX 24631  
WEST PALM BEACH, FLORIDA 33416  
USA  
877-900-8325  
info@highteckproducts.com
- **Information department:** Product safety department
- **Emergency telephone number:** 800 424-9300 (Chemtrec)

**2 Hazard(s) identification**

- **Classification of the substance or mixture**



GHS02 Flame

Flammable Liquids 3

H226 Flammable liquid and vapor.



GHS08 Health hazard

Carcinogenicity 2

H351 Suspected of causing cancer. Route of exposure: Inhalation.



GHS07

Sensitization - Skin 1

H317 May cause an allergic skin reaction.

Specific Target Organ Toxicity - Single Exposure 3 H336 May cause drowsiness or dizziness.

- **Label elements**

- **GHS label elements**

The product is classified and labeled according to the Globally Harmonized System (GHS).

(Contd. on page 2)

# Safety Data Sheet

acc. to OSHA HCS

Printing date 07/16/2025

Reviewed on 07/16/2025

Trade name: HIT\_2415-1 NR SCHOOL BUS YELLOW 2K SS FPC

(Contd. of page 1)

· **Hazard pictograms**



GHS02 GHS07 GHS08

· **Signal word** Warning

· **Hazard-determining components of labeling:**

*n*-butyl acetate  
 titanium dioxide  
 ethylbenzene  
 bis(1,2,2,6,6-pentamethyl-4-piperidyl)sebacate

· **Hazard statements**

Flammable liquid and vapor.  
 May cause an allergic skin reaction.  
 Suspected of causing cancer. Route of exposure: Inhalation.  
 May cause drowsiness or dizziness.

· **Precautionary statements**

Obtain special instructions before use.  
 Do not handle until all safety precautions have been read and understood.  
 Keep away from heat/sparks/open flames/hot surfaces. - No smoking.  
 Ground/bond container and receiving equipment.  
 Use explosion-proof electrical/ventilating/lighting/equipment.  
 Use only non-sparking tools.  
 Take precautionary measures against static discharge.  
 Avoid breathing dust/fume/gas/mist/vapors/spray  
 Use only outdoors or in a well-ventilated area.  
 Contaminated work clothing must not be allowed out of the workplace.  
 Wear protective gloves/protective clothing/eye protection/face protection.  
 If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.  
 IF INHALED: Remove person to fresh air and keep comfortable for breathing.  
 IF exposed or concerned: Get medical advice/attention.  
 Call a poison center/doctor if you feel unwell.  
 Specific treatment (see on this label).  
 If skin irritation or rash occurs: Get medical advice/attention.  
 Wash contaminated clothing before reuse.  
 In case of fire: Use CO<sub>2</sub>, powder or water spray to extinguish.  
 Store in a well-ventilated place. Keep container tightly closed.  
 Store in a well-ventilated place. Keep cool.  
 Store locked up.  
 Dispose of contents/container in accordance with local/regional/national/international regulations.

· **Classification system:**

· **NFPA ratings (scale 0 - 4)**



Health = 0  
 Fire = 3  
 Reactivity = 0

· **HMIS-ratings (scale 0 - 4)**



HEALTH 0 Health = 0  
 FIRE 3 Fire = 3  
 REACTIVITY 0 Reactivity = 0

(Contd. on page 3)

# Safety Data Sheet

acc. to OSHA HCS

Printing date 07/16/2025

Reviewed on 07/16/2025

Trade name: HIT\_2415-1 NR SCHOOL BUS YELLOW 2K SS FPC

(Contd. of page 2)

- **Other hazards**
- **Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.

## 3 Composition/information on ingredients

- **Chemical characterization: Mixtures**
- **Description:** Mixture of the substances listed below with nonhazardous additions.

- **Dangerous components:**

123-86-4	n-butyl acetate	25-50%
110-43-0	heptan-2-one	2.5-10%
2530-83-8	[3-(2,3-epoxypropoxy)propyl]trimethoxysilane	0-≤2.5%
13463-67-7	titanium dioxide	≤2.5%
41556-26-7	bis(1,2,2,6,6-pentamethyl-4-piperidyl)sebacate	≤2.5%
100-41-4	ethylbenzene	≤2.5%

## 4 First-aid measures

- **Description of first aid measures**
- **General information:** Immediately remove any clothing soiled by the product.
- **After inhalation:**  
Supply fresh air and to be sure call for a doctor.  
In case of unconsciousness place patient stably in side position for transportation.
- **After skin contact:** Immediately wash with water and soap and rinse thoroughly.
- **After eye contact:** Rinse opened eye for several minutes under running water.
- **After swallowing:** If symptoms persist consult doctor.
- **Information for doctor:**
- **Most important symptoms and effects, both acute and delayed**  
No further relevant information available.
- **Indication of any immediate medical attention and special treatment needed**  
No further relevant information available.

## 5 Fire-fighting measures

- **Extinguishing media**
- **Suitable extinguishing agents:**  
CO<sub>2</sub>, extinguishing powder or water spray. Fight larger fires with water spray or alcohol resistant foam.
- **Special hazards arising from the substance or mixture** No further relevant information available.
- **Advice for firefighters**
- **Protective equipment:** No special measures required.

## 6 Accidental release measures

- **Personal precautions, protective equipment and emergency procedures**  
Wear protective equipment. Keep unprotected persons away.
- **Environmental precautions:**  
Prevent seepage into sewage system, workpits and cellars.  
Dilute with plenty of water.

(Contd. on page 4)

USA

# Safety Data Sheet

acc. to OSHA HCS

Printing date 07/16/2025

Reviewed on 07/16/2025

Trade name: HIT\_2415-1 NR SCHOOL BUS YELLOW 2K SS FPC

(Contd. of page 3)

- **Methods and material for containment and cleaning up:**  
Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).  
Dispose contaminated material as waste according to section 13.  
Ensure adequate ventilation.
- **Reference to other sections**  
See Section 7 for information on safe handling.  
See Section 8 for information on personal protection equipment.  
See Section 13 for disposal information.
- **Protective Action Criteria for Chemicals**

· **PAC-1:**

123-86-4	<i>n</i> -butyl acetate	5 ppm
110-43-0	heptan-2-one	150 ppm
2530-83-8	[3-(2,3-epoxypropoxy)propyl]trimethoxysilane	9.3 mg/m <sup>3</sup>
13463-67-7	titanium dioxide	30 mg/m <sup>3</sup>
1330-20-7	xylene	130 ppm
67-64-1	acetone	200 ppm
79-20-9	methyl acetate	250 ppm
100-41-4	ethylbenzene	33 ppm
108-38-3	<i>m</i> -xylene	130 ppm
122-99-6	2-phenoxyethanol	1.5 ppm
77-58-7	dibutyltin dilaurate	1.1 mg/m <sup>3</sup>
108-65-6	2-methoxy-1-methylethyl acetate	50 ppm
1333-86-4	Carbon black	9 mg/m <sup>3</sup>
34590-94-8	Dipropylene glycol monomethyl ether	150 ppm
14808-60-7	Quartz (SiO <sub>2</sub> )	0.075 mg/m <sup>3</sup>
108-83-8	2,6-dimethylheptan-4-one	75 ppm
57-55-6	Propylene glycol	30 mg/m <sup>3</sup>
78-83-1	butanol	150 ppm
70657-70-4	2-methoxypropyl acetate	50 ppm

· **PAC-2:**

123-86-4	<i>n</i> -butyl acetate	200 ppm
110-43-0	heptan-2-one	670 ppm
2530-83-8	[3-(2,3-epoxypropoxy)propyl]trimethoxysilane	100 mg/m <sup>3</sup>
13463-67-7	titanium dioxide	330 mg/m <sup>3</sup>
1330-20-7	xylene	920* ppm
67-64-1	acetone	3200* ppm
79-20-9	methyl acetate	1,700 ppm
100-41-4	ethylbenzene	1100 ppm
108-38-3	<i>m</i> -xylene	920 ppm
122-99-6	2-phenoxyethanol	16 ppm
77-58-7	dibutyltin dilaurate	3.8 mg/m <sup>3</sup>
108-65-6	2-methoxy-1-methylethyl acetate	1,000 ppm
1333-86-4	Carbon black	290 mg/m <sup>3</sup>
34590-94-8	Dipropylene glycol monomethyl ether	1700* ppm
14808-60-7	Quartz (SiO <sub>2</sub> )	8.3 mg/m <sup>3</sup>

(Contd. on page 5)

# Safety Data Sheet

acc. to OSHA HCS

Printing date 07/16/2025

Reviewed on 07/16/2025

Trade name: HIT\_2415-1 NR SCHOOL BUS YELLOW 2K SS FPC

(Contd. of page 4)

108-83-8	2,6-dimethylheptan-4-one	330 ppm
57-55-6	Propylene glycol	1,300 mg/m <sup>3</sup>
78-83-1	butanol	1,300 ppm
70657-70-4	2-methoxypropyl acetate	1,000 ppm
<b>· PAC-3:</b>		
123-86-4	n-butyl acetate	3000* ppm
110-43-0	heptan-2-one	4000* ppm
2530-83-8	[3-(2,3-epoxypropoxy)propyl]trimethoxysilane	230 mg/m <sup>3</sup>
13463-67-7	titanium dioxide	2,000 mg/m <sup>3</sup>
1330-20-7	xylene	2500* ppm
67-64-1	acetone	5700* ppm
79-20-9	methyl acetate	10000* ppm
100-41-4	ethylbenzene	1800 ppm
108-38-3	m-xylene	2500* ppm
122-99-6	2-phenoxyethanol	97 ppm
77-58-7	dibutyltin dilaurate	23 mg/m <sup>3</sup>
108-65-6	2-methoxy-1-methylethyl acetate	5000* ppm
1333-86-4	Carbon black	1750 mg/m <sup>3</sup>
34590-94-8	Dipropylene glycol monomethyl ether	9900** ppm
14808-60-7	Quartz (SiO <sub>2</sub> )	50 mg/m <sup>3</sup>
108-83-8	2,6-dimethylheptan-4-one	2000* ppm
57-55-6	Propylene glycol	7,900 mg/m <sup>3</sup>
78-83-1	butanol	8000* ppm
70657-70-4	2-methoxypropyl acetate	5,000 ppm

## 7 Handling and storage

- **Handling:**

- **Precautions for safe handling**

Ensure good ventilation/exhaustion at the workplace.

Open and handle receptacle with care.

Prevent formation of aerosols.

- **Information about protection against explosions and fires:**

Keep ignition sources away - Do not smoke.

Protect against electrostatic charges.

Keep respiratory protective device available.

- **Conditions for safe storage, including any incompatibilities**

- **Storage:**

- **Requirements to be met by storerooms and receptacles:** No special requirements.

- **Information about storage in one common storage facility:** Not required.

- **Further information about storage conditions:** Keep receptacle tightly sealed.

- **Specific end use(s)** No further relevant information available.

## 8 Exposure controls/personal protection

- **Additional information about design of technical systems:** No further data; see section 7.

(Contd. on page 6)

# Safety Data Sheet

acc. to OSHA HCS

Printing date 07/16/2025

Reviewed on 07/16/2025

Trade name: HIT\_2415-1 NR SCHOOL BUS YELLOW 2K SS FPC

(Contd. of page 5)

- **Control parameters**

- **Components with limit values that require monitoring at the workplace:**

The following constituents are the only constituents of the product which have a PEL, TLV or other recommended exposure limit.

At this time, the other constituents have no known exposure limits.

**123-86-4 n-butyl acetate**

PEL Long-term value: 710 mg/m<sup>3</sup>, 150 ppm

REL Short-term value: 950 mg/m<sup>3</sup>, 200 ppm  
Long-term value: 710 mg/m<sup>3</sup>, 150 ppm

TLV Short-term value: 712 mg/m<sup>3</sup>, 150 ppm  
Long-term value: 238 mg/m<sup>3</sup>, 50 ppm

**110-43-0 heptan-2-one**

PEL Long-term value: 465 mg/m<sup>3</sup>, 100 ppm

REL Long-term value: 465 mg/m<sup>3</sup>, 100 ppm

TLV Long-term value: 50 ppm

**100-41-4 ethylbenzene**

PEL Long-term value: 435 mg/m<sup>3</sup>, 100 ppm

REL Short-term value: 545 mg/m<sup>3</sup>, 125 ppm  
Long-term value: 435 mg/m<sup>3</sup>, 100 ppm

TLV Long-term value: 20 ppm  
OTO, BEI, A3

- **Ingredients with biological limit values:**

**100-41-4 ethylbenzene**

BEI 0.15 g/g creatinine

Medium: urine

Time: end of shift

Parameter: Sum of mandelic acid and phenylglyoxylic acid (nonspecific)

- **Additional information:** The lists that were valid during the creation were used as basis.

- **Exposure controls**

- **Personal protective equipment:**

- **General protective and hygienic measures:**

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing.

Wash hands before breaks and at the end of work.

Store protective clothing separately.

- **Breathing equipment:**

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use respiratory protective device that is independent of circulating air.

- **Protection of hands:**



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation. Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

(Contd. on page 7)

USA

# Safety Data Sheet

acc. to OSHA HCS

Printing date 07/16/2025

Reviewed on 07/16/2025

Trade name: HIT\_2415-1 NR SCHOOL BUS YELLOW 2K SS FPC

(Contd. of page 6)

- **Material of gloves**

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

- **Penetration time of glove material**

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

- **Eye protection:**



Tightly sealed goggles

## 9 Physical and chemical properties

- **Information on basic physical and chemical properties**

- **General Information**

- **Appearance:**

· <b>Form:</b>	Liquid
· <b>Color:</b>	Yellow
· <b>Odor:</b>	Characteristic
· <b>Odor threshold:</b>	Not determined.

- **pH-value:** Not determined (pH N/A in solvent coatings)

- **Change in condition**

· <b>Melting point/Melting range:</b>	Undetermined.
· <b>Boiling point/Boiling range:</b>	124-128 °C (255.2-262.4 °F)

- **Flash point:** 27 °C (80.6 °F)

- **Flammability:** Flammable.

- **Auto igniting:** 370 °C (698 °F)

- **Decomposition temperature:** Not determined.

- **Ignition temperature:** Product is not selfigniting.

- **Danger of explosion:** Product is not explosive. However, formation of explosive air/vapor mixtures are possible.

- **Explosion limits:**

· <b>Lower:</b>	1.2 Vol %
· <b>Upper:</b>	7.5 Vol %

- **Vapor pressure at 20 °C (68 °F):** 10.7 hPa (8 mm Hg)

- **Vapor pressure at 50 °C (122 °F):** 55 hPa (41.3 mm Hg)

- **Density at 20 °C (68 °F):** 1.041 g/cm<sup>3</sup> (8.6871 lbs/gal)

- **Relative density** Not determined.

- **Vapor density** Not determined.

- **Evaporation rate** Not determined.

- **Solubility in / Miscibility with**

- **Water:** Fully miscible.

(Contd. on page 8)

# Safety Data Sheet

acc. to OSHA HCS

Printing date 07/16/2025

Reviewed on 07/16/2025

Trade name: HIT\_2415-1 NR SCHOOL BUS YELLOW 2K SS FPC

(Contd. of page 7)

· **Partition coefficient (n-octanol/water):** Not determined.

· **Viscosity:**

**Dynamic:** Not determined.

**Kinematic:** Not determined.

· **Solvent content:**

**Organic solvents:** 40.9 %

**Water:** 0.0 %

**VOC content:** 40.07 %  
371.0 g/l / 3.10 lb/gal

**Solids content:** 59.8 %

· **Other information** No further relevant information available.

## 10 Stability and reactivity

· **Reactivity** No further relevant information available.

· **Chemical stability**

· **Thermal decomposition / conditions to be avoided:**

No decomposition if used according to specifications.

· **Possibility of hazardous reactions** No dangerous reactions known.

· **Conditions to avoid** No further relevant information available.

· **Incompatible materials:** No further relevant information available.

· **Hazardous decomposition products:** No dangerous decomposition products known.

## 11 Toxicological information

· **Information on toxicological effects**

· **Acute toxicity:**

· **LD/LC50 values that are relevant for classification:**

### 123-86-4 n-butyl acetate

Oral	LD50	13,100 mg/kg (rat)
Dermal	LD50	>5,000 mg/kg (rabbit)
Inhalative	LC50/4 h	>21 mg/l (rat)

· **Primary irritant effect:**

· **on the skin:** No irritant effect.

· **on the eye:** No irritating effect.

· **Sensitization:** Sensitization possible through skin contact.

· **Additional toxicological information:**

The product shows the following dangers according to internally approved calculation methods for preparations:

Irritant

· **Carcinogenic categories**

· **IARC (International Agency for Research on Cancer)**

13463-67-7	titanium dioxide	2B
1330-20-7	xylene	3
100-41-4	ethylbenzene	2B

(Contd. on page 9)

USA

# Safety Data Sheet

acc. to OSHA HCS

Printing date 07/16/2025

Reviewed on 07/16/2025

Trade name: HIT\_2415-1 NR SCHOOL BUS YELLOW 2K SS FPC

(Contd. of page 8)

95-47-6	<i>o</i> -xylene	3
106-42-3	<i>p</i> -xylene	3
108-38-3	<i>m</i> -xylene	3
1333-86-4	Carbon black	2B
14808-60-7	Quartz (SiO <sub>2</sub> )	1

· **NTP (National Toxicology Program)**

14808-60-7	Quartz (SiO <sub>2</sub> )	K
------------	----------------------------	---

· **OSHA-Ca (Occupational Safety & Health Administration)**

None of the ingredients is listed.

## 12 Ecological information

- **Toxicity**
- **Aquatic toxicity:** No further relevant information available.
- **Persistence and degradability** No further relevant information available.
- **Behavior in environmental systems:**
- **Bioaccumulative potential** No further relevant information available.
- **Mobility in soil** No further relevant information available.
- **Additional ecological information:**
- **General notes:** Not hazardous for water.
- **Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.
- **Other adverse effects** No further relevant information available.

## 13 Disposal considerations

- **Waste treatment methods**
- **Recommendation:**  
Must not be disposed of together with household garbage. Do not allow product to reach sewage system.
- **Uncleaned packagings:**
- **Recommendation:** Disposal must be made according to official regulations.
- **Recommended cleansing agent:** Water, if necessary with cleansing agents.

## 14 Transport information

- |   |                        |
|---|------------------------|
| <ul style="list-style-type: none"> <li>· <b>UN-Number</b></li> <li>· <b>DOT, IMDG, IATA</b></li> </ul>                                | <p>UN1263</p>          |
| <ul style="list-style-type: none"> <li>· <b>UN proper shipping name</b></li> <li>· <b>DOT</b></li> <li>· <b>IMDG, IATA</b></li> </ul> | <p>Paint<br/>PAINT</p> |

(Contd. on page 10)

USA

# Safety Data Sheet

acc. to OSHA HCS

Printing date 07/16/2025

Reviewed on 07/16/2025

Trade name: HIT\_2415-1 NR SCHOOL BUS YELLOW 2K SS FPC

(Contd. of page 9)

- **Transport hazard class(es)**

- **DOT**



- **Class** 3 Flammable liquids
- **Label** 3

- **IMDG, IATA**



- **Class** 3 Flammable liquids
- **Label** 3

- **Packing group**
- **DOT, IMDG, IATA** III

- **Environmental hazards:** Not applicable.

- **Special precautions for user** Warning: Flammable liquids

- **Hazard identification number (Kemler code):** 30

- **EMS Number:** F-E, S-E

- **Stowage Category** A

- **Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code** Not applicable.

- **Transport/Additional information:**

- **DOT**

- **Quantity limitations** On passenger aircraft/rail: 60 L  
On cargo aircraft only: 220 L

- **IMDG**

- **Limited quantities (LQ)** 5L

- **Excepted quantities (EQ)** Code: E1  
Maximum net quantity per inner packaging: 30 ml  
Maximum net quantity per outer packaging: 1000 ml

- **UN "Model Regulation":** UN 1263 PAINT, 3, III

## 15 Regulatory information

- **Safety, health and environmental regulations/legislation specific for the substance or mixture**  
No further relevant information available.

- **Sara**

- **Section 355 (extremely hazardous substances):**

None of the ingredients is listed.

- **Section 313 (Specific toxic chemical listings):**

1330-20-7 xylene

(Contd. on page 11)

USA

# Safety Data Sheet

acc. to OSHA HCS

Printing date 07/16/2025

Reviewed on 07/16/2025

Trade name: HIT\_2415-1 NR SCHOOL BUS YELLOW 2K SS FPC

(Contd. of page 10)

100-41-4	ethylbenzene
95-47-6	<i>o</i> -xylene
106-42-3	<i>p</i> -xylene
108-38-3	<i>m</i> -xylene
122-99-6	2-phenoxyethanol

· **TSCA (Toxic Substances Control Act):**

123-86-4	<i>n</i> -butyl acetate	ACTIVE
110-43-0	heptan-2-one	ACTIVE
61790-51-0	Resin acids and Rosin acids, sodium salts	ACTIVE
2530-83-8	[3-(2,3-epoxypropoxy)propyl]trimethoxysilane	ACTIVE
13463-67-7	titanium dioxide	ACTIVE
1330-20-7	xylene	ACTIVE
41556-26-7	bis(1,2,2,6,6-pentamethyl-4-piperidyl)sebacate	ACTIVE
67-64-1	acetone	ACTIVE
79-20-9	methyl acetate	ACTIVE
100-41-4	ethylbenzene	ACTIVE
95-47-6	<i>o</i> -xylene	ACTIVE
106-42-3	<i>p</i> -xylene	ACTIVE
108-38-3	<i>m</i> -xylene	ACTIVE
64742-47-8	Distillates (petroleum), hydrotreated light	ACTIVE
82919-37-7	methyl 1,2,2,6,6-pentamethyl-4-piperidylsebacate	ACTIVE
122-99-6	2-phenoxyethanol	ACTIVE
77-58-7	dibutyltin dilaurate	ACTIVE
108-65-6	2-methoxy-1-methylethyl acetate	ACTIVE
1333-86-4	Carbon black	ACTIVE
7732-18-5	water, distilled, conductivity or of similar purity	ACTIVE
64742-95-6	Solvent naphtha (petroleum), light arom.	ACTIVE
34590-94-8	Dipropylene glycol monomethyl ether	ACTIVE
14808-60-7	Quartz (SiO <sub>2</sub> )	ACTIVE
108-83-8	2,6-dimethylheptan-4-one	ACTIVE
57-55-6	Propylene glycol	ACTIVE
78-83-1	butanol	ACTIVE

· **Hazardous Air Pollutants**

1330-20-7	xylene
100-41-4	ethylbenzene
95-47-6	<i>o</i> -xylene
106-42-3	<i>p</i> -xylene
108-38-3	<i>m</i> -xylene

· **Proposition 65**

· **Chemicals known to cause cancer:**

13463-67-7	titanium dioxide
100-41-4	ethylbenzene
1333-86-4	Carbon black

(Contd. on page 12)

# Safety Data Sheet

acc. to OSHA HCS

Printing date 07/16/2025

Reviewed on 07/16/2025

Trade name: HIT\_2415-1 NR SCHOOL BUS YELLOW 2K SS FPC

(Contd. of page 11)

14808-60-7 Quartz (SiO<sub>2</sub>)

· **Chemicals known to cause reproductive toxicity for females:**

None of the ingredients is listed.

· **Chemicals known to cause reproductive toxicity for males:**

None of the ingredients is listed.

· **Chemicals known to cause developmental toxicity:**

None of the ingredients is listed.

· **Carcinogenic categories**

· **EPA (Environmental Protection Agency)**

1330-20-7	xylene	I
67-64-1	acetone	I
100-41-4	ethylbenzene	D
95-47-6	o-xylene	I
106-42-3	p-xylene	I
108-38-3	m-xylene	I

· **TLV (Threshold Limit Value)**

13463-67-7	titanium dioxide	A4
1330-20-7	xylene	A4
67-64-1	acetone	A4
100-41-4	ethylbenzene	A3
95-47-6	o-xylene	A4
106-42-3	p-xylene	A4
108-38-3	m-xylene	A4
77-58-7	dibutyltin dilaurate	A4
1333-86-4	Carbon black	A4
14808-60-7	Quartz (SiO <sub>2</sub> )	A2

· **NIOSH-Ca (National Institute for Occupational Safety and Health)**

13463-67-7	titanium dioxide
1333-86-4	Carbon black
14808-60-7	Quartz (SiO <sub>2</sub> )

· **GHS label elements**

The product is classified and labeled according to the Globally Harmonized System (GHS).

· **Hazard pictograms**



GHS02 GHS07 GHS08

· **Signal word** Warning

· **Hazard-determining components of labeling:**

n-butyl acetate  
titanium dioxide  
ethylbenzene  
bis(1,2,2,6,6-pentamethyl-4-piperidyl)sebacate

(Contd. on page 13)

# Safety Data Sheet

acc. to OSHA HCS

Printing date 07/16/2025

Reviewed on 07/16/2025

Trade name: HIT\_2415-1 NR SCHOOL BUS YELLOW 2K SS FPC

(Contd. of page 12)

- **Hazard statements**

*Flammable liquid and vapor.*  
*May cause an allergic skin reaction.*  
*Suspected of causing cancer. Route of exposure: Inhalation.*  
*May cause drowsiness or dizziness.*

- **Precautionary statements**

*Obtain special instructions before use.*  
*Do not handle until all safety precautions have been read and understood.*  
*Keep away from heat/sparks/open flames/hot surfaces. - No smoking.*  
*Ground/bond container and receiving equipment.*  
*Use explosion-proof electrical/ventilating/lighting/equipment.*  
*Use only non-sparking tools.*  
*Take precautionary measures against static discharge.*  
*Avoid breathing dust/fume/gas/mist/vapors/spray*  
*Use only outdoors or in a well-ventilated area.*  
*Contaminated work clothing must not be allowed out of the workplace.*  
*Wear protective gloves/protective clothing/eye protection/face protection.*  
*If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.*  
*IF INHALED: Remove person to fresh air and keep comfortable for breathing.*  
*IF exposed or concerned: Get medical advice/attention.*  
*Call a poison center/doctor if you feel unwell.*  
*Specific treatment (see on this label).*  
*If skin irritation or rash occurs: Get medical advice/attention.*  
*Wash contaminated clothing before reuse.*  
*In case of fire: Use CO2, powder or water spray to extinguish.*  
*Store in a well-ventilated place. Keep container tightly closed.*  
*Store in a well-ventilated place. Keep cool.*  
*Store locked up.*  
*Dispose of contents/container in accordance with local/regional/national/international regulations.*

- **Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

## 16 Other information

*This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.*

- **Contact:**

- **Date of preparation / last revision** 07/16/2025 / -

- **Abbreviations and acronyms:**

*IMDG: International Maritime Code for Dangerous Goods*  
*DOT: US Department of Transportation*  
*IATA: International Air Transport Association*  
*EINECS: European Inventory of Existing Commercial Chemical Substances*  
*ELINCS: European List of Notified Chemical Substances*  
*CAS: Chemical Abstracts Service (division of the American Chemical Society)*  
*NFPA: National Fire Protection Association (USA)*  
*HMIS: Hazardous Materials Identification System (USA)*  
*VOC: Volatile Organic Compounds (USA, EU)*  
*LC50: Lethal concentration, 50 percent*  
*LD50: Lethal dose, 50 percent*  
*PBT: Persistent, Bioaccumulative and Toxic*  
*vPvB: very Persistent and very Bioaccumulative*  
*NIOSH: National Institute for Occupational Safety*  
*OSHA: Occupational Safety & Health*  
*TLV: Threshold Limit Value*  
*PEL: Permissible Exposure Limit*  
*REL: Recommended Exposure Limit*  
*BEI: Biological Exposure Limit*  
*Flammable Liquids 3: Flammable liquids – Category 3*

(Contd. on page 14)

USA

**Safety Data Sheet**  
acc. to OSHA HCS

Printing date 07/16/2025

Reviewed on 07/16/2025

**Trade name: HIT\_2415-1 NR SCHOOL BUS YELLOW 2K SS FPC**

(Contd. of page 13)

*Sensitization - Skin 1: Skin sensitisation – Category 1*

*Carcinogenicity 2: Carcinogenicity – Category 2*

*Specific Target Organ Toxicity - Single Exposure 3: Specific target organ toxicity (single exposure) – Category 3*

USA