

**PRODUCT NAME:** NORMAL, HS CLEAR ACTIVATOR  
**PRODUCT CODE:** HT-7152-4

**HMIS CODES:** H F R P  
2\*3 0 G

===== **SECTION I - MANUFACTURER IDENTIFICATION** =====

**MANUFACTURED FOR :** High Teck Quality Products  
**ADDRESS :** West Palm Beach, FL 33413

**EMERGENCY PHONE :** (800)424-9300      **DATE PRINTED :** 7/31/2013  
**INFORMATION PHONE :** (877)900-8325      **PREPARER NAME:** MSDS Coordinator

===== **SECTION II - HAZARDOUS INGREDIENTS/SARA III INFORMATION** =====

REPORTABLE COMPONENTS	CAS NUMBER	VAPOR PRESSURE mm Hg @ TEMP	WEIGHT PERCENT
hexamethylene diisocyanate polymer	28182-81-2	N/A	N/A
isocyanate polymer	53880-05-0		35%-45%
n-BUTYL ACETATE	123-86-4	8.4	68 F
ACGIH TLV TWA: 150 ppm			15.4032
ACGIH TLV STEL: 200 ppm			
OSHA VPEL TWA: 150 ppm			
OSHA VPEL STEL: 200 ppm			
light aromatic petroleum solvent	64742-95-6	4	68 F
* pseudocumene	95-63-6	1.58	68 F
ACGIH TLV: 25 ppm TWA			0%-10%
OSHA PEL: 25 ppm TWA			3.98
NIOSH: 25 ppm TWA			
NIOSH: 125 mg/m3 TWA			
1,3,5-trimethylbenzene	108-67-8	2.5	68 F
NIOSH: 25 ppm TWA AND 125 mg/m3 TWA			0%-10%
XYLENES	1330-20-7	5.10	68 F
ACGIH TWA 100 ppm			.48
ACGIH STEL 150 ppm			
OSHA TWA 100 ppm			
OSHA STEL 150 ppm			
{N120} hexamethylene diisocyanate	822-06-0	0.0003	77 F
ACGIH TLV: 0.005 ppm TWA			<1%
ACGIH TLV: 0.34 mg/m3 TWA			
NIOSH: 0.005 ppm TWA			
NIOSH: 35 ug/m3 TWA			

\* Indicates toxic chemical(s) subject to the reporting requirements of section 313 of Title III and of 40 CFR 372.  
N/A

===== **SECTION III - PHYSICAL/CHEMICAL CHARACTERISTICS** =====

<b>BOILING RANGE:</b> 201.2 F - 334.4 F	<b>SPECIFIC GRAVITY (H2O=1):</b> 1.07
<b>VAPOR DENSITY:</b> Heavier than air	<b>EVAPORATION RATE:</b> Slower than ether
<b>V.O.C. grams/liter:</b> 283.03	<b>V.O.C. lbs/gl:</b> 2.36
<b>SOLUBILITY IN WATER:</b> Insoluble	<b>SOLIDS BY VOLUME:</b> 67.559
<b>APPEARANCE AND ODOR:</b> Clear liquid with organic solvent odor	

===== **SECTION IV - FIRE AND EXPLOSION HAZARD DATA** =====



**CARCINOGENICITY: NTP CARCINOGEN: No IARC MONOGRAPHS: No**  
To the best of our knowledge this material contains no known carcinogens

**OSHA REGULATED: Yes**

**MEDICAL CONDITIONS GENERALLY AGGRAVATED BY EXPOSURE**

Do not use this product if you have chronic lung or breathing problems, or if you have ever had a reaction to isocyanates.

**EMERGENCY AND FIRST AID PROCEDURES**

If ingestion, or any type of overexposure or symptoms of overexposure occur during the use of this product, contact a poison control center, emergency room or physician immediately; have material safety data sheet available.

===== **SECTION VII - PRECAUTIONS FOR SAFE HANDLING AND USE** =====

**STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED**

Remove all sources of ignition (sparks, flames, and hot surfaces). Avoid breathing vapors. Ventilate area. Remove with an inert absorbent and non-sparking tools.

**WASTE DISPOSAL METHOD**

Dispose in accordance with state ,federal and local regulations. Do not incinerate closed containers.

**PRECAUTIONS TO BE TAKEN IN HANDLING AND STORING**

Keep containers tightly closed in a cool, dry, well ventilated area away from all possible ignition sources. Store large quantities of material in buildings designed for the storage of flammable liquids.

**OTHER PRECAUTIONS**

Employees should be trained in safety measures that should be taken when using this product.

===== **SECTION VIII - CONTROL MEASURES** =====

**RESPIRATORY PROTECTION**

Avoid breathing vapors or spray mist. Wear a properly fitted respirator approved by NIOSH/MSHA (TC-23c) for use with paints during application and until all vapors are exhausted. In confined areas, or where continuous spray operations are typical, or proper respirator fit is not possible, wear a positive-pressure supplied air respirator (TC-19c). In all cases follow respirator manufactures directions for respirator use. Do not allow anyone without protection into the painting area.

**VENTILATION**

Provide sufficient ventilation to keep contaminates below applicable OSHA requirements.

**PROTECTIVE GLOVES**

Neoprene gloves impervious to organic solvents are recommended.

**EYE PROTECTION**

Use safety eyewear designed to protect against liquid splash.

**OTHER PROTECTIVE CLOTHING OR EQUIPMENT**

Impervious coveralls are recommended.

**WORK/HYGIENIC PRACTICES**

Eye wash and safety showers in the work place are recommended. Wash hands before eating and smoking.

===== **SECTION IX - DISCLAIMER** =====

The information contained in this material safety data sheet is information from our suppliers and other sources. It is believed to be reliable. This data is not to be taken as a warranty or representation for which this company assumes legal responsibility.