

SECTION 1: Identification

1.1. Product identifier

Product form : Mixture
 Trade name : REVvive by RSG Acid Etch Primer - Gray
 Product group : Aerosol
 Other means of identification : UPC - 66623391010

1.2. Recommended use and restrictions on use

Recommended use : For professional use only

1.3. Supplier

Canada

Saint-Gobain Canada, Inc.
 28 Albert Street, W.
 N0J 1S0 Plattsville, ON
 T 519-684-7441
www.Nortonabrasives.com

United States

Saint-Gobain Abrasives Inc
 1 New Bond Street
 01615 Worcester, MA
 T 800-551-4413
www.Nortonabrasives.com

1.4. Emergency telephone number

Emergency number : 508-795-5000. For emergencies in Canada, call CHEMTREC: 800-424-9300

SECTION 2: Hazard identification

2.1. Classification of the substance or mixture

Classification (GHS-CA)

Flammable aerosol Category 1	H222
Skin corrosion/irritation Category 2	H315
Serious eye damage/eye irritation Category 1	H318
Carcinogenicity Category 2	H351
Specific target organ toxicity (single exposure) Category 3	H336
Hazardous to the aquatic environment - Chronic Hazard Category 2	H411

Full text of H statements : see section 16

2.2. GHS Label elements, including precautionary statements

GHS-CA labeling

Hazard pictograms (GHS-CA) :



Signal word (GHS-CA) : Danger

Hazard statements (GHS-CA) : H222 - Extremely flammable aerosol
 H315 - Causes skin irritation
 H318 - Causes serious eye damage
 H336 - May cause drowsiness or dizziness
 H351 - Suspected of causing cancer
 H411 - Toxic to aquatic life with long lasting effects

Precautionary statements (GHS-CA) : P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
 P251 - Do not pierce or burn, even after use.
 P261 - Avoid breathing fume, spray, vapors.
 P280 - Wear eye protection, Protective gloves, protective clothing.
 P302+P352 - IF ON SKIN: Wash with plenty of water.
 P305 - IF IN EYES: Rinse first with plenty of water and if necessary take medical advice
 P410+P412 - Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.

2.3. Other hazards

No additional information available

2.4. Unknown acute toxicity (GHS-CA)

No data available

SECTION 3: Composition/Information on ingredients

3.1. Substances

Not applicable

08-21-2018

EN (English US)

REVvive by RSG Acid Etch Primer - Gray

Safety Data Sheet

according to the Hazardous Products Regulation (February 11, 2015)

3.2. Mixtures

Name	Chemical name / Synonyms	Product identifier	%	Classification (GHS-CA)
ethyl acetate	methyl acetate acetate of methyl / acetic acid methyl ester / acetic acid, methyl ester / devoton / ethyl ester of monoacetyl acid / methyl acetate / methyl acetate, anhydrous / methyl acetic ester / methyl ester acetic acid / methyl ethanoate / tereton	(CAS-No.) 79-20-9	15 - 30	Flam. Liq. 2, H225 Eye Irrit. 2A, H319 STOT SE 3, H336
1-butanol	1-butanol / 1-butyl alcohol / 1-hydroxy butane / alcohol C4 / butan-1-ol / butanol / butyl alcohol / butyl hydroxide / butyric alcohol / butyric alcohol, n- / butyric alcohol, normal- / CCS203 / FEMA No 2178 / hemostyp / methyl ethyl carbinol / methylol propane / n-butan-1-ol / n-butanol / n-butyl alcohol / n-butyric alcohol / normal primary butyl alcohol / normal-butan-1-ol / normal-butanol / normal-butyl alcohol / normal-butyric alcohol / normal-propyl carbinol / n-prim butyl alcohol / n-propyl carbinol / primary-normal-butyl alcohol / prim-n-butyl alcohol / propyl carbinol / propyl methanol	(CAS-No.) 71-36-3	7 - 10	Flam. Liq. 3, H226 Acute Tox. 4 (Oral), H302 Skin Irrit. 2, H315 Eye Dam. 1, H318 STOT SE 3, H335 STOT SE 3, H336

REVvive by RSG Acid Etch Primer - Gray

Safety Data Sheet

according to the Hazardous Products Regulation (February 11, 2015)

Name	Chemical name / Synonyms	Product identifier	%	Classification (GHS-CA)
titanium(IV) oxide	1700 WHITE / A051 / A072 / A351 / AC 1 / AC 11 / AC 5 / A-FIL CREAM / AJANTOX / AJANTOX AGP / AJANTOX GR / AJANTOX RUTILE / AN10 / ASD / ASTM D476 / ASTM D76 / atlas white titanium dioxide / AUSTIOX / AUSTIOX ADM / AUSTIOX AE / AUSTIOX AFN3 / AUSTIOX AHR / AUSTIOX ALF / AUSTIOX ALF2 / AUSTIOX APP / AUSTIOX APP2 / AUSTIOX GRANULAR / AUSTIOX RCR / AUSTIOX RCR10 / AUSTIOX RCR2 / AUSTIOX RCR3 / AUSTIOX RCR6 / AUSTIOX RCR60 / AUSTIOX RFC / AUSTIOX RFC2 / AUSTIOX RFC5 / AUSTIOX RHD / AUSTIOX RHD2 / AUSTIOX RHD3 / AUSTIOX RHD4 / AUSTIOX RHD6 / AUSTIOX RMC / AUSTIOX RSM / AUSTIOX RSM2 / AUSTIOX RSM3 / AUSTIOX RTC2 / AUSTIOX RTC30 / AUSTIOX RTC4 / AUSTIOX RTC4U / AUSTIOX RTC50 / AUSTIOX RTC90 / AUSTIOX RXL / AUSTIOX RXW / BAYER titan / BAYER titan A / BAYER titan A2 / BAYER titan AC5522 / BAYER titan AC5581 / BAYER titan AE / BAYER titan AN2 / BAYER titan AN3 / BAYER titan RCK20 / BAYER titan RCL10 / BAYER titan RCL20 / BAYER titan RD / BAYER titan RFD1 / BAYER titan RFD2 / BAYER titan RFDI / BAYER titan R-FK 21 / BAYER titan RFKD / BAYER titan RKB2 / BAYER titan RKB3 / BAYER titan RKB4 / BAYER titan RKBD / BAYER titan RPL1 / BAYER titan RU2 / BAYER titan RUF / BAYER titan T / BAYERITIAN / BAYTITAN / BETA-RUTILE / BROOKITE / C.I. 77891 / C.I. pigment white 6 / CABOT / CALCOTONE WHITE T / COSMETIC WHITE C47-5175 / COSMETIC WHITE C47-9623 / DETI-ANA / DETI-RU / E171 / ET 10 / FA50 / FA55W / FA65 / FA80 / FE150 / FE160 / FINN titan / FINN titan AG / FINN titan AN / FINN titan AP / FINN titan RD / FINN titan RD2 / FINN titan RDD / FINN titan RDDX / FINN titan RDE2 / FINN titan RDI / FINN titan RF / FINN titan RF2 / FINN titan RF2new / FINN titan RF4 / FINN titan RR / FINN titan RR2 / FINN titan RR2S / FINN titan RR3 / FINN titan RRL / FINN titan RU / FLAMENCO / FR22 / FR30 / FR31 / FR41 / FRUF84 / FUJI titan / FUJI titan TA100 / FUJI titan TA200 / FUJI titan TA210 / FUJI titan TA300 / FUJI titan TA400 / FUJI titan TA500 / FUJI titan TE / FUJI titan TP13 / FUJI titan TP2 / FUJI titan TP3 / FUJI titan TR700 / FUJI titan TR780 / FUJI titan TR840 / FURUKAWA / HOMBITAN / HOMBITAN KA / HOMBITAN LOCR / HOMBITAN LOCRK / HOMBITAN LOCRS / HOMBITAN LW / HOMBITAN LWS / HOMBITAN LWSU / HOMBITAN R101 / HOMBITAN R10106 / HOMBITAN R101D / HOMBITAN R110 / HOMBITAN R210 / HOMBITAN R301 / HOMBITAN R301D / HOMBITAN R320 / HOMBITAN R505 / HOMBITAN R506 / HOMBITAN R510 / HOMBITAN R511 / HOMBITAN R610 / HOMBITAN R610D / HOMBITAN R610K / HOMBITAN R610L / HOMBITAN R611 / HOMBITAN R611D / HOMBITAN R710 / HOMBITAN RCL22 / HOMBITAN RCL66 / HOMBITAN SA10 / HOMBITAN SR12 / HOMBITAN SR16 / HORSE HEAD / HORSE HEAD A-410 / HORSE HEAD A-420 / HORSE HEAD A430 / HORSE HEAD A430C / HORSE HEAD A430FG / HORSE HEAD	(CAS-No.) 13463-67-7	5 - 7	Carc. 2, H351
08-21-2018				3/17

REVvive by RSG Acid Etch Primer - Gray

Safety Data Sheet

according to the Hazardous Products Regulation (February 11, 2015)

Name	Chemical name / Synonyms	Product identifier	%	Classification (GHS-CA)
1-methoxy-2-propanol, monopropylene glycol methyl ether	(+/-)-1-methoxy-2-propanol / 1-methoxy-2-hydroxypropane / 1-methoxy-2-propanol / 1-methoxy-2-propanol, (+/-)- / 1-methoxypropan-2-ol / 1-methoxypropanol-2 / 2-methoxy-1-methylethanol / 2-propanol, 1-methoxy- / alpha-propylene glycol 1-methyl ether / alpha-propylene glycol monomethyl ether / dowanol 33B / dowanol PM / dowanol PM glycol ether / dowanol PM-E glycol ether / dowtherm 209 / glycol ether PM / methoxy ether of propyleneglycol / methoxyisopropanol / methyl ether of propylene glycol / monoethyl ether of propylene glycol / monopropylene glycol methyl ether / MP-S / PGME (= propylene glycol monomethyl ether) / poly-solve MPM / propasol solvent M / propylene glycol methyl ether / propylene glycol monomethyl ether / UCAR PM solvent / UCAR solvent LM / UCAR triol HG-170	(CAS-No.) 107-98-2	1.5 - 5	Flam. Liq. 3, H226 STOT SE 3, H336
cyclohexanone	cyclohexanone anon / anone / caswell No 270 / cyclohexanone / cyclohexanone, selectophore / cyclohexyl ketone / epa pesticide chemical code 025902 / hexanon(=cyclohexanone) / hexanone(=cyclohexanone) / htyiol / htyrol O / keto hexamethylene / ketoexamethylene / MATTHEWS 10 thinner/cleaner / nadone / pimelic ketone / pimelin ketone / sextone	(CAS-No.) 108-94-1	1.5 - 3	Flam. Liq. 3, H226 Acute Tox. 4 (Oral), H302 Acute Tox. 4 (Dermal), H312 Acute Tox. 4 (Inhalation), H332 Skin Irrit. 2, H315 Eye Dam. 1, H318
2-methylpropan-1-ol, iso-butanol	2-methylpropan-1-ol, iso-butanol 1-hydroxymethylpropane / 1-propanol, 2-methyl- / 2-methyl-1-propanol / 2-methylpropan-1-ol / 2-methylpropanol / 2-methylpropyl alcohol / FEMA No 2179 / fermentation butyl alcohol / IBUOH / iso-butanol / isobutyl alcohol / isobutyric alcohol / isopropyl carbinol	(CAS-No.) 78-83-1	1 - 1.5	Flam. Liq. 3, H226 Skin Irrit. 2, H315 Eye Dam. 1, H318 STOT SE 3, H335 STOT SE 3, H336
ethylbenzene	ethylbenzene benzene, ethyl- / ethylbenzene / ethylbenzene, anhydrous / phenylethane	(CAS-No.) 100-41-4	0.1 - 0.5	Flam. Liq. 2, H225 Acute Tox. 4 (Inhalation), H332 Carc. 2, H351 STOT RE 2, H373 Asp. Tox. 1, H304

Full text of hazard classes and H-statements : see section 16

SECTION 4: First-aid measures

4.1. Description of first aid measures

- First-aid measures after inhalation : Remove person to fresh air and keep comfortable for breathing.
- First-aid measures after skin contact : Wash skin with plenty of water. Take off contaminated clothing. If skin irritation occurs: Get medical advice/attention.
- First-aid measures after eye contact : Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Call a physician immediately.
- First-aid measures after ingestion : Call a poison center/doctor/physician if you feel unwell.
- First-aid measures general : IF exposed or concerned: Get medical advice/attention.

4.2. Most important symptoms and effects (acute and delayed)

- Symptoms/effects : May cause drowsiness or dizziness.
- Symptoms/effects after skin contact : Irritation.
- Symptoms/effects after eye contact : Serious damage to eyes.

4.3. Immediate medical attention and special treatment, if necessary

- Other medical advice or treatment : Treat symptomatically.

SECTION 5: Fire-fighting measures

5.1. Suitable extinguishing media

- Suitable extinguishing media : Water spray. Dry powder. Foam. Carbon dioxide.

REVvive by RSG Acid Etch Primer - Gray

Safety Data Sheet

according to the Hazardous Products Regulation (February 11, 2015)

5.2. Unsuitable extinguishing media

No additional information available

5.3. Specific hazards arising from the hazardous product

Fire hazard : Extremely flammable aerosol.
Explosion hazard : Pressurized container: may burst if heated.

5.4. Special protective equipment and precautions for fire-fighters

Protection during firefighting : Do not attempt to take action without suitable protective equipment. Self-contained breathing apparatus. Complete protective clothing.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

No additional information available

6.2. Methods and materials for containment and cleaning up

For containment : Contain released product, pump into suitable containers. Collect spillage.
Methods for cleaning up : Notify authorities if product enters sewers or public waters. Mechanically recover the product.
Other information : Dispose of materials or solid residues at an authorized site.

6.3. Reference to other sections

For further information refer to section 8: "Exposure controls/personal protection"

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Precautions for safe handling : Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Wear personal protective equipment. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Do not spray on an open flame or other ignition source. Pressurized container: Do not pierce or burn, even after use. Use only outdoors or in a well-ventilated area. Avoid breathing dust/fume/gas/mist/vapors/spray. Avoid contact with skin and eyes.
Hygiene measures : Do not eat, drink or smoke when using this product. Always wash hands after handling the product. Wash contaminated clothing before reuse.

7.2. Conditions for safe storage, including any incompatibilities

Storage conditions : Store locked up. Protect from sunlight. Do not expose to temperatures exceeding 50 °C/ 122 °F. Store in a well-ventilated place. Keep container tightly closed. Keep cool.
Storage temperature : < 25 °C
Special rules on packaging : Keep only in original container.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

ethylbenzene (100-41-4)		
USA - ACGIH	ACGIH TWA (ppm)	20 ppm
USA - ACGIH	Remark (ACGIH)	URT irr; kidney dam (nephropathy)
USA - ACGIH	Regulatory reference	ACGIH 2018
USA - OSHA	OSHA PEL (TWA) (mg/m³)	435 mg/m³
USA - OSHA	OSHA PEL (TWA) (ppm)	100 ppm
USA - OSHA	Regulatory reference (US-OSHA)	OSHA
Saskatchewan	OEL STEL (ppm)	125 ppm
Saskatchewan	OEL TWA (ppm)	100 ppm
Saskatchewan	Notations and remarks	T20
2-methylpropan-1-ol, iso-butanol (78-83-1)		
USA - ACGIH	ACGIH TWA (ppm)	50 ppm
USA - ACGIH	Remark (ACGIH)	Skin & eye irr
USA - ACGIH	Regulatory reference	ACGIH 2018
USA - OSHA	OSHA PEL (TWA) (mg/m³)	300 mg/m³
USA - OSHA	OSHA PEL (TWA) (ppm)	100 ppm
USA - OSHA	Regulatory reference (US-OSHA)	OSHA
Alberta	OEL TWA (ppm)	50 ppm

REVvive by RSG Acid Etch Primer - Gray

Safety Data Sheet

according to the Hazardous Products Regulation (February 11, 2015)

2-methylpropan-1-ol, iso-butanol (78-83-1)		
Alberta	Notations and remarks	Skin & eye irr
British Columbia	OEL TWA (ppm)	50 ppm
British Columbia	Notations and remarks	Skin & eye irr
Manitoba	OEL TWA (ppm)	50 ppm
Manitoba	Notations and remarks	Skin & eye irr
New Brunswick	OEL TWA (ppm)	50 ppm
New Brunswick	Notations and remarks	Skin & eye irr
New Foundland & Labrador	OEL TWA (ppm)	50 ppm
New Foundland & Labrador	Notations and remarks	Skin & eye irr
Nova Scotia	OEL TWA (ppm)	50 ppm
Nova Scotia	Notations and remarks	Skin & eye irr
Nunavut	OEL TWA (ppm)	50 ppm
Nunavut	Notations and remarks	Skin & eye irr
Northwest Territories	OEL TWA (ppm)	50 ppm
Northwest Territories	Notations and remarks	Skin & eye irr
Prince Edward Island	OEL TWA (ppm)	50 ppm
Prince Edward Island	Notations and remarks	Skin & eye irr
Saskatchewan	OEL STEL (ppm)	60 ppm
Saskatchewan	OEL TWA (ppm)	50 ppm
1-butanol (71-36-3)		
USA - ACGIH	ACGIH TWA (ppm)	20 ppm
USA - ACGIH	Remark (ACGIH)	Eye & URT irr
USA - ACGIH	Regulatory reference	ACGIH 2018
USA - OSHA	OSHA PEL (TWA) (mg/m ³)	300 mg/m ³
USA - OSHA	OSHA PEL (TWA) (ppm)	100 ppm
USA - OSHA	Regulatory reference (US-OSHA)	OSHA
Alberta	OEL TWA (ppm)	20 ppm
Alberta	Notations and remarks	Eye & URT irr
British Columbia	OEL TWA (ppm)	20 ppm
British Columbia	Notations and remarks	Eye & URT irr
Manitoba	OEL TWA (ppm)	20 ppm
Manitoba	Notations and remarks	Eye & URT irr
New Brunswick	OEL TWA (ppm)	20 ppm
New Brunswick	Notations and remarks	Eye & URT irr
New Foundland & Labrador	OEL TWA (ppm)	20 ppm
New Foundland & Labrador	Notations and remarks	Eye & URT irr
Nova Scotia	OEL TWA (ppm)	20 ppm
Nova Scotia	Notations and remarks	Eye & URT irr
Nunavut	OEL TWA (ppm)	20 ppm
Nunavut	Notations and remarks	Eye & URT irr
Northwest Territories	OEL TWA (ppm)	20 ppm
Northwest Territories	Notations and remarks	Eye & URT irr
Prince Edward Island	OEL TWA (ppm)	20 ppm
Prince Edward Island	Notations and remarks	Eye & URT irr
Saskatchewan	OEL STEL (ppm)	30 ppm
Saskatchewan	OEL TWA (ppm)	20 ppm
1-methoxy-2-propanol, monopropylene glycol methyl ether (107-98-2)		
USA - ACGIH	ACGIH TWA (ppm)	50 ppm

REVvive by RSG Acid Etch Primer - Gray

Safety Data Sheet

according to the Hazardous Products Regulation (February 11, 2015)

1-methoxy-2-propanol, monopropylene glycol methyl ether (107-98-2)		
USA - ACGIH	ACGIH STEL (ppm)	100 ppm
USA - ACGIH	Remark (ACGIH)	Eye irr; CNS impair; A4 (Not classifiable as a Human Carcinogen: Agents which cause concern that they could be carcinogenic for humans but which cannot be assessed conclusively because of a lack of data. In vitro or animal studies do not provide indications of carcinogenicity which are sufficient to classify the agent into one of the other categories)
USA - ACGIH	Regulatory reference	ACGIH 2018
Saskatchewan	OEL STEL (ppm)	150 ppm
Saskatchewan	OEL TWA (ppm)	100 ppm
titanium(IV) oxide (13463-67-7)		
USA - ACGIH	ACGIH TWA (mg/m ³)	10 mg/m ³
USA - ACGIH	Remark (ACGIH)	LRT irr; A3 (Confirmed Animal Carcinogen with Unknown Relevance to Humans: The agent is carcinogenic in experimental animals at a relatively high dose, by route(s) of administration, at site(s), of histologic type(s), or by mechanism(s) that may not be relevant to worker exposure. Available epidemiologic studies do not confirm an increased risk of cancer in exposed humans. Available evidence does not suggest that the agent is likely to cause cancer in humans except under uncommon or unlikely routes or levels of exposure)
USA - ACGIH	Regulatory reference	ACGIH 2018
USA - OSHA	OSHA PEL (TWA) (mg/m ³)	15 mg/m ³
USA - OSHA	Regulatory reference (US-OSHA)	OSHA
Alberta	OEL TWA (mg/m ³)	10 mg/m ³
Alberta	Notations and remarks	LRT irr
British Columbia	OEL TWA (mg/m ³)	10 mg/m ³
British Columbia	Notations and remarks	LRT irr
Manitoba	OEL TWA (mg/m ³)	10 mg/m ³
Manitoba	Notations and remarks	LRT irr
New Brunswick	OEL TWA (mg/m ³)	10 mg/m ³
New Brunswick	Notations and remarks	LRT irr
New Foundland & Labrador	OEL TWA (mg/m ³)	10 mg/m ³
New Foundland & Labrador	Notations and remarks	LRT irr
Nova Scotia	OEL TWA (mg/m ³)	10 mg/m ³
Nova Scotia	Notations and remarks	LRT irr
Nunavut	OEL TWA (mg/m ³)	10 mg/m ³
Nunavut	Notations and remarks	LRT irr
Northwest Territories	OEL TWA (mg/m ³)	10 mg/m ³
Northwest Territories	Notations and remarks	LRT irr
Prince Edward Island	OEL TWA (mg/m ³)	10 mg/m ³
Prince Edward Island	Notations and remarks	LRT irr
Saskatchewan	OEL STEL (mg/m ³)	20 mg/m ³
Saskatchewan	OEL TWA (mg/m ³)	10 mg/m ³
methyl acetate (79-20-9)		
USA - ACGIH	ACGIH TWA (ppm)	200 ppm
USA - ACGIH	ACGIH STEL (ppm)	250 ppm
USA - ACGIH	Remark (ACGIH)	eye & URT irr
USA - ACGIH	Regulatory reference	ACGIH 2018
USA - OSHA	OSHA PEL (TWA) (mg/m ³)	610 mg/m ³
USA - OSHA	OSHA PEL (TWA) (ppm)	200 ppm

REVvive by RSG Acid Etch Primer - Gray

Safety Data Sheet

according to the Hazardous Products Regulation (February 11, 2015)

methyl acetate (79-20-9)		
USA - OSHA	Regulatory reference (US-OSHA)	OSHA
Alberta	OEL STEL (ppm)	250 ppm
Alberta	OEL TWA (ppm)	200 ppm
Alberta	Notations and remarks	eye & URT irr
British Columbia	OEL STEL (ppm)	250 ppm
British Columbia	OEL TWA (ppm)	200 ppm
British Columbia	Notations and remarks	eye & URT irr
Manitoba	OEL STEL (ppm)	250 ppm
Manitoba	OEL TWA (ppm)	200 ppm
Manitoba	Notations and remarks	eye & URT irr
New Brunswick	OEL STEL (ppm)	250 ppm
New Brunswick	OEL TWA (ppm)	200 ppm
New Brunswick	Notations and remarks	eye & URT irr
New Foundland & Labrador	OEL STEL (ppm)	250 ppm
New Foundland & Labrador	OEL TWA (ppm)	200 ppm
New Foundland & Labrador	Notations and remarks	eye & URT irr
Nova Scotia	OEL STEL (ppm)	250 ppm
Nova Scotia	OEL TWA (ppm)	200 ppm
Nova Scotia	Notations and remarks	eye & URT irr
Nunavut	OEL STEL (ppm)	250 ppm
Nunavut	OEL TWA (ppm)	200 ppm
Nunavut	Notations and remarks	eye & URT irr
Northwest Territories	OEL STEL (ppm)	250 ppm
Northwest Territories	OEL TWA (ppm)	200 ppm
Northwest Territories	Notations and remarks	eye & URT irr
Prince Edward Island	OEL STEL (ppm)	250 ppm
Prince Edward Island	OEL TWA (ppm)	200 ppm
Prince Edward Island	Notations and remarks	eye & URT irr
Saskatchewan	OEL STEL (ppm)	250 ppm
Saskatchewan	OEL TWA (ppm)	200 ppm
cyclohexanone (108-94-1)		
USA - ACGIH	ACGIH TWA (ppm)	20 ppm
USA - ACGIH	ACGIH STEL (ppm)	50 ppm
USA - ACGIH	Remark (ACGIH)	Eye & URT irr
USA - ACGIH	Regulatory reference	ACGIH 2018
USA - OSHA	OSHA PEL (TWA) (mg/m ³)	200 mg/m ³
USA - OSHA	OSHA PEL (TWA) (ppm)	50 ppm
USA - OSHA	Regulatory reference (US-OSHA)	OSHA
Saskatchewan	OEL STEL (ppm)	50 ppm
Saskatchewan	OEL TWA (ppm)	20 ppm
Saskatchewan	Notations and remarks	Skin

8.2. Appropriate engineering controls

Appropriate engineering controls : Ensure good ventilation of the work station.
 Environmental exposure controls : Avoid release to the environment.

8.3. Individual protection measures/Personal protective equipment

Personal protective equipment:

Gloves. Protective clothing. Safety glasses.

REVvive by RSG Acid Etch Primer - Gray

Safety Data Sheet

according to the Hazardous Products Regulation (February 11, 2015)

Materials for protective clothing:

Impermeable clothing

Hand protection:

Protective gloves

Eye protection:

Safety glasses

Skin and body protection:

Wear suitable protective clothing

Respiratory protection:

In case of insufficient ventilation, wear suitable respiratory equipment

Personal protective equipment symbol(s):



SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	: Liquid
Appearance	: Aerosol.
Color	: Light gray
Odor	: There may be no odour warning properties, odour is subjective and inadequate to warn of overexposure. Mixture contains one or more component(s) which have the following odour: Irritating/pungent odour Sweet odour Aromatic odour Petroleum-like odour Alcohol odour Pleasant odour Mild odour Fruity odour Odourless Peppermint odour Acetone odour Ether-like odour
Odor threshold	: No data available
pH	: No data available
Relative evaporation rate (butyl acetate=1)	: No data available
Relative evaporation rate (ether=1)	: No data available
Melting point	: Not applicable
Freezing point	: No data available
Boiling point	: No data available
Flash point	: -41 °C
Auto-ignition temperature	: No data available
Decomposition temperature	: No data available
Flammability (solid, gas)	: Extremely flammable aerosol
Vapor pressure	: No data available
Vapor pressure at 50 °C	: No data available
Relative density	: No data available
Specific gravity / density	: 0.83 g/cm ³
Solubility	: insoluble in water. soluble in most organic solvents.
Log Pow	: No data available
Explosive properties	: Pressurized container: may burst if heated.
Explosion limits	: No data available

9.2. Other information

VOC content	: 693 g/l
MIR	: 0.95
Gas group	: Press. Gas (Ref. Liq.)

SECTION 10: Stability and reactivity

10.1. Reactivity

Reactivity	: Extremely flammable aerosol. Pressurized container: may burst if heated.
------------	--

REVvive by RSG Acid Etch Primer - Gray

Safety Data Sheet

according to the Hazardous Products Regulation (February 11, 2015)

Chemical stability	: Stable under normal conditions.
Possibility of hazardous reactions	: No dangerous reactions known under normal conditions of use.
Conditions to avoid	: Avoid contact with hot surfaces. Heat. No flames, no sparks. Eliminate all sources of ignition.
Hazardous decomposition products	: Under normal conditions of storage and use, hazardous decomposition products should not be produced.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity (oral)	: Not classified
Acute toxicity (dermal)	: Not classified
Acute toxicity (inhalation)	: Not classified

ethylbenzene (100-41-4)	
LD50 oral rat	3500 mg/kg (Rat, Male/female, Experimental value, Oral)
LD50 dermal rabbit	15432 mg/kg body weight (24 h, Rabbit, Male, Experimental value, Dermal)
LC50 inhalation rat (mg/l)	17.8 mg/l (4 h, Rat, Male, Experimental value, Inhalation (vapours))
ATE CA (oral)	3500 mg/kg body weight
ATE CA (dermal)	15432 mg/kg body weight
ATE CA (gases)	4500 ppmV/4h
ATE CA (vapours)	17.8 mg/l/4h
ATE CA (dust,mist)	1.5 mg/l/4h
2-methylpropan-1-ol, iso-butanol (78-83-1)	
LD50 oral rat	> 2830 mg/kg body weight (OECD 401: Acute Oral Toxicity, Rat, Male, Experimental value)
LD50 dermal rabbit	> 2000 mg/kg body weight (OECD 402: Acute Dermal Toxicity, 24 h, Rabbit, Male, Experimental value)
LC50 inhalation rat (mg/l)	24.6 mg/l air (Other, 4 h, Rat, Male/female, Experimental value, Inhalation (vapours))
1-butanol (71-36-3)	
LD50 oral rat	2292 mg/kg body weight (Equivalent or similar to OECD 401, Rat, Female, Experimental value, Oral)
LD50 dermal rabbit	3430 mg/kg body weight (Equivalent or similar to OECD 402, 24 h, Rabbit, Male, Experimental value, Dermal)
ATE CA (oral)	500 mg/kg body weight
ATE CA (dermal)	3430 mg/kg body weight
1-methoxy-2-propanol, monopropylene glycol methyl ether (107-98-2)	
LD50 oral rat	4016 mg/kg body weight (EU Method B.1 tris: Acute oral toxic – Acute toxic class method, Rat, Male/female, Experimental value, Oral)
LD50 dermal rat	> 2000 mg/kg body weight (Other, 24 h, Rat, Male/female, Experimental value, Dermal)
ATE CA (oral)	4016 mg/kg body weight
titanium(IV) oxide (13463-67-7)	
LD50 oral rat	> 5000 mg/kg body weight (OECD 425: Acute Oral Toxicity: Up-and-Down Procedure, Rat, Female, Experimental value, Oral, 14 day(s))
LC50 inhalation rat (mg/l)	> 6.82 mg/l (Other, 4 h, Rat, Male, Experimental value, Inhalation (dust), 14 day(s))
methyl acetate (79-20-9)	
LD50 oral rat	6482 mg/kg body weight (Equivalent or similar to OECD 401, Rat, Male, Experimental value, Oral)
LD50 dermal rat	> 2000 mg/kg body weight (OECD 402: Acute Dermal Toxicity, 24 h, Rat, Male/female, Experimental value, Dermal)
ATE CA (oral)	6482 mg/kg body weight
cyclohexanone (108-94-1)	
LD50 oral rat	1890 mg/kg body weight (BASF test, Rat, Experimental value, Oral, 7 day(s))
LC50 inhalation rat (mg/l)	> 6.2 mg/l air (BASF test, 4 h, Rat, Male/female, Experimental value, Inhalation (vapours))
ATE CA (oral)	1890 mg/kg body weight
ATE CA (dermal)	1100 mg/kg body weight
ATE CA (gases)	4500 ppmV/4h
ATE CA (vapours)	11 mg/l/4h
ATE CA (dust,mist)	1.5 mg/l/4h

Skin corrosion/irritation	: Causes skin irritation.
Serious eye damage/irritation	: Causes serious eye damage.
Respiratory or skin sensitization	: Not classified

REVvive by RSG Acid Etch Primer - Gray

Safety Data Sheet

according to the Hazardous Products Regulation (February 11, 2015)

Germ cell mutagenicity : Not classified
Carcinogenicity : Suspected of causing cancer.

Reproductive toxicity : Not classified

Specific target organ toxicity – single exposure : May cause drowsiness or dizziness.

2-methylpropan-1-ol, iso-butanol (78-83-1)	
Specific target organ toxicity – single exposure	May cause respiratory irritation. May cause drowsiness or dizziness.
1-butanol (71-36-3)	
Specific target organ toxicity – single exposure	May cause respiratory irritation. May cause drowsiness or dizziness.
1-methoxy-2-propanol, monopropylene glycol methyl ether (107-98-2)	
Specific target organ toxicity – single exposure	May cause drowsiness or dizziness.
methyl acetate (79-20-9)	
Specific target organ toxicity – single exposure	May cause drowsiness or dizziness.

: Not classified

Specific target organ toxicity – repeated exposure

ethylbenzene (100-41-4)	
Specific target organ toxicity – repeated exposure	May cause damage to organs through prolonged or repeated exposure.

Aspiration hazard : Not classified

REVvive by RSG Acid Etch Primer- Gray	
Vaporizer	Aerosol

Symptoms/effects : May cause drowsiness or dizziness.
Symptoms/effects after skin contact : Irritation.
Symptoms/effects after eye contact : Serious damage to eyes.

SECTION 12: Ecological information

12.1. Toxicity

Ecology - general : Toxic to aquatic life with long lasting effects.
Aquatic acute : Not classified
Aquatic chronic : Toxic to aquatic life with long lasting effects.

ethylbenzene (100-41-4)	
LC50 fish 1	4.2 mg/l (OECD 203: Fish, Acute Toxicity Test, 96 h, Salmo gairdneri, Semi-static system, Fresh water, Experimental value)
EC50 Daphnia 1	1.8 - 2.4 mg/l (US EPA, 48 h, Daphnia magna, Static system, Fresh water, Experimental value)
EC50 72h algae [mg/l] 1	5.4 mg/l (US EPA, Pseudokirchneriella subcapitata, Static system, Fresh water, Experimental value, Cell numbers)
BCF fish 1	1 - 2.4 (Other, 6 week(s), Oncorhynchus kisutch, Flow-through system, Salt water, Experimental value)
Log Pow	3.6 (Experimental value, EU Method A.8: Partition Coefficient, 20 °C)
Log Koc	2.71 (log Koc, PCKOCWIN v1.66, QSAR)

2-methylpropan-1-ol, iso-butanol (78-83-1)	
LC50 fish 1	1430 mg/l (Other, 96 h, Pimephales promelas, Flow-through system, Fresh water, Experimental value)
EC50 Daphnia 1	1100 mg/l (ASTM, 48 h, Daphnia pulex, Static system, Fresh water, Experimental value, Nominal concentration)
ErC50 (algae)	1799 mg/l (OECD 201: Alga, Growth Inhibition Test, 72 h, Pseudokirchneriella subcapitata, Static system, Fresh water, Experimental value, GLP)
Log Pow	1 (Experimental value, OECD 117: Partition Coefficient (n-octanol/water), HPLC method, 25 °C)
Log Koc	0.31 (log Koc, SRC PCKOCWIN v1.66, Calculated value)

REVvive by RSG Acid Etch Primer - Gray

Safety Data Sheet

according to the Hazardous Products Regulation (February 11, 2015)

1-butanol (71-36-3)	
LC50 fish 1	1376 mg/l (OECD 203: Fish, Acute Toxicity Test, 96 h, Pimephales promelas, Static system, Fresh water, Experimental value, GLP)
EC50 Daphnia 1	1328 mg/l (OECD 202: Daphnia sp. Acute Immobilisation Test, 48 h, Daphnia magna, Static system, Fresh water, Experimental value, GLP)
EC50 96h algae [mg/l] (1)	225 mg/l (OECD 201: Alga, Growth Inhibition Test, Pseudokirchneriella subcapitata, Static system, Fresh water, Experimental value, GLP)
BCF other aquatic organisms 1	3.16 (BCFWIN, Calculated value)
Log Pow	1 (Experimental value, OECD 117: Partition Coefficient (n-octanol/water), HPLC method, 25 °C)
Log Koc	0.388 (log Koc, PCKOCWIN v1.66, Calculated value)

1-methoxy-2-propanol, monopropylene glycol methyl ether (107-98-2)	
LC50 fish 1	>= 1000 mg/l (Equivalent or similar to OECD 203, 96 h, Oncorhynchus mykiss, Semi-static system, Fresh water, Experimental value, Nominal concentration)
ErC50 (algae)	> 1000 mg/l (Other, 168 h, Pseudokirchneriella subcapitata, Static system, Fresh water, Experimental value, GLP)
BCF fish 1	1 (Pimephales promelas)
Log Pow	< 1 (Experimental value, Equivalent or similar to OECD 117, 20 °C)

titanium(IV) oxide (13463-67-7)	
LC50 fish 1	> 100 mg/l (Equivalent or similar to OECD 203, 96 h, Oncorhynchus mykiss, Static system, Fresh water, Experimental value, Nominal concentration)
ErC50 (algae)	61 mg/l (EPA 600/9-78-018, 72 h, Pseudokirchneriella subcapitata, Static system, Fresh water, Experimental value, Nominal concentration)

methyl acetate (79-20-9)	
LC50 fish 1	250 - 350 mg/l (OECD 203: Fish, Acute Toxicity Test, 96 h, Brachydanio rerio, Static system, Fresh water, Experimental value, GLP)
EC50 Daphnia 1	1026.7 mg/l (OECD 202: Daphnia sp. Acute Immobilisation Test, 48 h, Daphnia magna, Static system, Fresh water, Experimental value, GLP)
EC50 72h algae [mg/l] 1	> 120 mg/l (OECD 201: Alga, Growth Inhibition Test, Scenedesmus subspicatus, Static system, Fresh water, Experimental value, GLP)
BCF fish 1	< 1 (Pisces, Literature study)
Log Pow	0.37 (Calculated, KOWWIN, 25 °C)
Log Koc	0.18 (log Koc, OECD 121: Estimation of the Adsorption Coefficient (Koc) on Soil and on Sewage Sludge using High Performance Liquid Chromatography (HPLC), Experimental value, GLP)

cyclohexanone (108-94-1)	
LC50 fish 1	527 - 732 mg/l (US EPA, 96 h, Pimephales promelas, Flow-through system, Fresh water, Experimental value)
EC50 Daphnia 1	> 100 mg/l (OECD 202: Daphnia sp. Acute Immobilisation Test, 48 h, Daphnia magna, Static system, Fresh water, Read-across, GLP)
ErC50 (algae)	> 100 mg/l (OECD 201: Alga, Growth Inhibition Test, 72 h, Desmodesmus subspicatus, Static system, Fresh water, Read-across, GLP)
BCF other aquatic organisms 1	2.4 (QSAR)
Log Pow	0.86 (Experimental value, OECD 107: Partition Coefficient (n-octanol/water): Shake Flask Method, 25 °C)
Log Koc	1.18 (log Koc, SRC PCKOCWIN v1.66, Calculated value)

12.2. Persistence and degradability

ethylbenzene (100-41-4)	
Persistence and degradability	Biodegradable in the soil. Readily biodegradable in water.
Biochemical oxygen demand (BOD)	1.44 g O ₂ /g substance (20d.)
Chemical oxygen demand (COD)	2.1 g O ₂ /g substance
ThOD	3.17 g O ₂ /g substance

2-methylpropan-1-ol, iso-butanol (78-83-1)	
Persistence and degradability	Biodegradable in the soil. Readily biodegradable in water.

1-butanol (71-36-3)	
Persistence and degradability	Readily biodegradable in water.
Biochemical oxygen demand (BOD)	1.1 - 1.92 g O ₂ /g substance
Chemical oxygen demand (COD)	2.46 g O ₂ /g substance

REVvive by RSG Acid Etch Primer - Gray

Safety Data Sheet

according to the Hazardous Products Regulation (February 11, 2015)

1-butanol (71-36-3)	
ThOD	2.59 g O ₂ /g substance
BOD (% of ThOD)	0.33 - 0.79
1-methoxy-2-propanol, monopropylene glycol methyl ether (107-98-2)	
Persistence and degradability	Biodegradable in the soil. Readily biodegradable in water.
ThOD	1.95 g O ₂ /g substance
titanium(IV) oxide (13463-67-7)	
Persistence and degradability	Biodegradability: not applicable.
Biochemical oxygen demand (BOD)	Not applicable (inorganic)
Chemical oxygen demand (COD)	Not applicable (inorganic)
ThOD	Not applicable (inorganic)
methyl acetate (79-20-9)	
Persistence and degradability	Readily biodegradable in water. Inherently biodegradable.
cyclohexanone (108-94-1)	
Persistence and degradability	Biodegradable in the soil. Readily biodegradable in water.
Biochemical oxygen demand (BOD)	1.232 g O ₂ /g substance
Chemical oxygen demand (COD)	2.605 g O ₂ /g substance
ThOD	2.605 g O ₂ /g substance
12.3. Bioaccumulative potential	
ethylbenzene (100-41-4)	
Bioaccumulative potential	Low potential for bioaccumulation (BCF < 500).
BCF fish 1	1 - 2.4 (Other, 6 week(s), Oncorhynchus kisutch, Flow-through system, Salt water, Experimental value)
Log Pow	3.6 (Experimental value, EU Method A.8: Partition Coefficient, 20 °C)
Log Koc	2.71 (log Koc, PCKOCWIN v1.66, QSAR)
2-methylpropan-1-ol, iso-butanol (78-83-1)	
Bioaccumulative potential	Low potential for bioaccumulation (Log Kow < 4).
Log Pow	1 (Experimental value, OECD 117: Partition Coefficient (n-octanol/water), HPLC method, 25 °C)
Log Koc	0.31 (log Koc, SRC PCKOCWIN v1.66, Calculated value)
1-butanol (71-36-3)	
Bioaccumulative potential	Low potential for bioaccumulation (Log Kow < 4).
BCF other aquatic organisms 1	3.16 (BCFWIN, Calculated value)
Log Pow	1 (Experimental value, OECD 117: Partition Coefficient (n-octanol/water), HPLC method, 25 °C)
Log Koc	0.388 (log Koc, PCKOCWIN v1.66, Calculated value)
1-methoxy-2-propanol, monopropylene glycol methyl ether (107-98-2)	
Bioaccumulative potential	Not bioaccumulative.
BCF fish 1	1 (Pimephales promelas)
Log Pow	< 1 (Experimental value, Equivalent or similar to OECD 117, 20 °C)
titanium(IV) oxide (13463-67-7)	
Bioaccumulative potential	Not bioaccumulative.
methyl acetate (79-20-9)	
Bioaccumulative potential	Low potential for bioaccumulation (BCF < 500).
BCF fish 1	< 1 (Pisces, Literature study)
Log Pow	0.37 (Calculated, KOWWIN, 25 °C)
Log Koc	0.18 (log Koc, OECD 121: Estimation of the Adsorption Coefficient (Koc) on Soil and on Sewage Sludge using High Performance Liquid Chromatography (HPLC), Experimental value, GLP)
cyclohexanone (108-94-1)	
Bioaccumulative potential	Low potential for bioaccumulation (Log Kow < 4).
BCF other aquatic organisms 1	2.4 (QSAR)
Log Pow	0.86 (Experimental value, OECD 107: Partition Coefficient (n-octanol/water): Shake Flask Method, 25 °C)
Log Koc	1.18 (log Koc, SRC PCKOCWIN v1.66, Calculated value)

REVvive by RSG Acid Etch Primer - Gray

Safety Data Sheet

according to the Hazardous Products Regulation (February 11, 2015)

12.4. Mobility in soil

ethylbenzene (100-41-4)	
Surface tension	0.071 N/m (23 °C, 0.0582 g/l, EU Method A.5: Surface tension)
Ecology - soil	Low potential for adsorption in soil. Toxic to soil organisms.
Log Koc	2.71 (log Koc, PCKOCWIN v1.66, QSAR)
Log Pow	3.6 (Experimental value, EU Method A.8: Partition Coefficient, 20 °C)
2-methylpropan-1-ol, iso-butanol (78-83-1)	
Surface tension	0.0697 N/m (20 °C, 1 g/l, OECD 115: Surface Tension of Aqueous Solutions)
Ecology - soil	Highly mobile in soil.
Log Koc	0.31 (log Koc, SRC PCKOCWIN v1.66, Calculated value)
Log Pow	1 (Experimental value, OECD 117: Partition Coefficient (n-octanol/water), HPLC method, 25 °C)
1-butanol (71-36-3)	
Surface tension	0.07 N/m (20 °C, 1 g/l, OECD 115: Surface Tension of Aqueous Solutions)
Ecology - soil	Highly mobile in soil. May be harmful to plant growth, blooming and fruit formation.
Log Koc	0.388 (log Koc, PCKOCWIN v1.66, Calculated value)
Log Pow	1 (Experimental value, OECD 117: Partition Coefficient (n-octanol/water), HPLC method, 25 °C)
1-methoxy-2-propanol, monopropylene glycol methyl ether (107-98-2)	
Surface tension	0.0707 N/m (20 °C, 1 g/l, OECD 115: Surface Tension of Aqueous Solutions)
Ecology - soil	Low potential for adsorption in soil.
Log Pow	< 1 (Experimental value, Equivalent or similar to OECD 117, 20 °C)
titanium(IV) oxide (13463-67-7)	
Ecology - soil	Low potential for mobility in soil.
methyl acetate (79-20-9)	
Surface tension	0.024 N/m (20 °C)
Ecology - soil	Highly mobile in soil.
Log Koc	0.18 (log Koc, OECD 121: Estimation of the Adsorption Coefficient (Koc) on Soil and on Sewage Sludge using High Performance Liquid Chromatography (HPLC), Experimental value, GLP)
Log Pow	0.37 (Calculated, KOWWIN, 25 °C)
cyclohexanone (108-94-1)	
Surface tension	0.034 N/m (20 °C)
Ecology - soil	Highly mobile in soil.
Log Koc	1.18 (log Koc, SRC PCKOCWIN v1.66, Calculated value)
Log Pow	0.86 (Experimental value, OECD 107: Partition Coefficient (n-octanol/water): Shake Flask Method, 25 °C)

12.5. Other adverse effects

Ozone : Not classified

SECTION 13: Disposal considerations

13.1. Disposal methods

Regional legislation (waste) : Disposal must be done according to official regulations.
Waste treatment methods : Dispose of contents/container in accordance with licensed collector's sorting instructions.

SECTION 14: Transport information

14.1. Basic shipping description

In accordance with TDG

Transportation of Dangerous Goods

UN-No. (TDG) : UN1950
TDG Primary Hazard Classes : 2.1 - Class 2.1 - Flammable Gas.
Transport document description : UN1950 AEROSOLS (flammable), 2.1
Proper Shipping Name (Transportation of Dangerous Goods) : AEROSOLS
flammable

REVvive by RSG Acid Etch Primer - Gray

Safety Data Sheet

according to the Hazardous Products Regulation (February 11, 2015)

Hazard labels (TDG) : 2.1 - Flammable gases



TDG Special Provisions : 80 - Despite section 1.17 of Part 1, Coming into Force, Repeal, Interpretation, General Provisions and Special Cases, a person must not offer for transport or transport these dangerous goods unless they are in a means of containment that is in compliance with section 5.11 of Part 5, Means of Containment, except that the requirement for aerosol containers to be tightly packed in a wood, fibreboard or plastic box does not apply to a user or purchaser who transports no more than six aerosol containers. For a similar rule respecting aerosol containers, see subparagraph 1.15(1)(a)(i) of Part 1, Coming into Force, Repeal, Interpretation, General Provisions and Special Cases. SOR/2012-245

107 - (1)These Regulations, except for Part 1 (Coming into Force, Repeal, Interpretation, General Provisions and Special Cases) and Part 2, (Classification), do not apply to the handling, offering for transport or transporting of UN1950, AEROSOLS, and UN2037, GAS CARTRIDGES, that contain dangerous goods included in Class 2.1 or Class 2.2 and that are transported on a road vehicle, a railway vehicle or a ship on a domestic voyage, if the aerosols or gas cartridges have a capacity less than or equal to 50 mL. (2)Subsection (1) does not apply to self-defence spray. SOR/2014-306

Explosive Limit and Limited Quantity Index : 1 L

Excepted quantities (TDG) : E0

Passenger Carrying Road Vehicle or Passenger : 75 L

Carrying Railway Vehicle Index

Marine pollutant : Yes (IMDG only)



14.2. Transport information/DOT

Department of Transport

DOT NA no. : UN1950

UN-No.(DOT) : 1950

Transport document description : UN1950 Aerosols (flammable, (each not exceeding 1 L capacity)), 2.1

Proper Shipping Name (DOT) : Aerosols
flammable, (each not exceeding 1 L capacity)

Contains Statement Field Selection (DOT) :

Class (DOT) : 2.1 - Class 2.1 - Flammable gas 49 CFR 173.115

Division (DOT) : 2.1

Hazard labels (DOT) : 2.1 - Flammable gas



Dangerous for the environment : Yes

Marine pollutant : Yes



DOT Special Provisions (49 CFR 172.102) : N82 - See 173.306 of this subchapter for classification criteria for flammable aerosols.

DOT Packaging Exceptions (49 CFR 173.xxx) : 306

DOT Packaging Non Bulk (49 CFR 173.xxx) : None

DOT Packaging Bulk (49 CFR 173.xxx) : None

DOT Quantity Limitations Passenger aircraft/rail : 75 kg
(49 CFR 173.27)

DOT Quantity Limitations Cargo aircraft only (49 : 150 kg
CFR 175.75)

REVvive by RSG Acid Etch Primer - Gray

Safety Data Sheet

according to the Hazardous Products Regulation (February 11, 2015)

DOT Vessel Stowage Location	: A - The material may be stowed "on deck" or "under deck" on a cargo vessel and on a passenger vessel.
DOT Vessel Stowage Other	: 25 - Shade from radiant heat, 87 - Stow "separated from" Class 1 (explosives) except Division 14, 126 - Segregation same as for Class 9, miscellaneous hazardous materials
Other information	: No supplementary information available.

14.3. Air and sea transport

IMDG

UN-No. (IMDG)	: 1950
Proper Shipping Name (IMDG)	: AEROSOLS
Transport document description (IMDG)	: UN 1950 AEROSOLS, 2.1, MARINE POLLUTANT/ENVIRONMENTALLY HAZARDOUS
Class (IMDG)	: 2 - Gases

IATA

UN-No. (IATA)	: 1950
Proper Shipping Name (IATA)	: Aerosols, flammable
Transport document description (IATA)	: UN 1950 Aerosols, flammable, 2.1, ENVIRONMENTALLY HAZARDOUS
Class (IATA)	: 2

SECTION 15: Regulatory information

15.1. National regulations

ethylbenzene (100-41-4)

Listed on the Canadian DSL (Domestic Substances List)

2-methylpropan-1-ol, iso-butanol (78-83-1)

Listed on the Canadian DSL (Domestic Substances List)

1-butanol (71-36-3)

Listed on the Canadian DSL (Domestic Substances List)

1-methoxy-2-propanol, monopropylene glycol methyl ether (107-98-2)

Listed on the Canadian DSL (Domestic Substances List)

titanium(IV) oxide (13463-67-7)

Listed on the Canadian DSL (Domestic Substances List)

methyl acetate (79-20-9)

Listed on the Canadian DSL (Domestic Substances List)

cyclohexanone (108-94-1)

Listed on the Canadian DSL (Domestic Substances List)

15.2. International regulations

ethylbenzene (100-41-4)

Listed on the United States TSCA (Toxic Substances Control Act) inventory

2-methylpropan-1-ol, iso-butanol (78-83-1)

Listed on the United States TSCA (Toxic Substances Control Act) inventory

1-butanol (71-36-3)

Listed on the United States TSCA (Toxic Substances Control Act) inventory

1-methoxy-2-propanol, monopropylene glycol methyl ether (107-98-2)

Listed on the United States TSCA (Toxic Substances Control Act) inventory

titanium(IV) oxide (13463-67-7)

Listed on the United States TSCA (Toxic Substances Control Act) inventory

methyl acetate (79-20-9)

Listed on the United States TSCA (Toxic Substances Control Act) inventory

cyclohexanone (108-94-1)

Listed on the United States TSCA (Toxic Substances Control Act) inventory

SECTION 16: Other information

SDS Major/Minor	: None
Date of issue	: 04-17-2018
Revision date	: 08-21-2018
Supersedes	: 06-27-2018

REVvive by RSG Acid Etch Primer - Gray

Safety Data Sheet

according to the Hazardous Products Regulation (February 11, 2015)

Full text of H-phrases:

H222	Extremely flammable aerosol
H225	Highly flammable liquid and vapor
H226	Flammable liquid and vapor
H302	Harmful if swallowed
H304	May be fatal if swallowed and enters airways
H312	Harmful in contact with skin
H315	Causes skin irritation
H318	Causes serious eye damage
H319	Causes serious eye irritation
H332	Harmful if inhaled
H335	May cause respiratory irritation
H336	May cause drowsiness or dizziness
H351	Suspected of causing cancer
H373	May cause damage to organs through prolonged or repeated exposure
H411	Toxic to aquatic life with long lasting effects

SDS Canada

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product