



Safety Data Sheet

acc. to 29 CFR 1910.1200 App D

POR-15 CALIPER PAINT RED

Version number: GHS 1.0

Date of compilation: 2023-12-07

SECTION 1: Identification

1.1 Product identifier

Trade name **POR-15 CALIPER PAINT RED**
Product code(s) 42806

1.2 Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses Paint

1.3 Details of the supplier of the safety data sheet

P.O.R. Products
38 Portman Road
New Rochelle NY 10801
United States

Telephone: +1 914-636-0700
e-mail: support@porproducts.com
Website: www.porproducts.com

e-mail (competent person) support@porproducts.com

1.4 Emergency telephone number

Emergency information service 1-800-255-3924
ChemTel Inc.

SECTION 2: Hazard(s) identification

2.1 Classification of the substance or mixture

Classification acc. to OSHA "Hazard Communication Standard" (29 CFR 1910.1200)

Section	Hazard class	Category	Hazard class and category	Hazard statement
A.1I	acute toxicity (inhal.)	4	Acute Tox. 4	H332
A.4S	skin sensitization	1	Skin Sens. 1	H317
A.5	germ cell mutagenicity	1B	Muta. 1B	H340
A.6	carcinogenicity	1A	Carc. 1A	H350
A.9	specific target organ toxicity - repeated exposure	1	STOT RE 1	H372
A.10	aspiration hazard	1	Asp. Tox. 1	H304
B.6	flammable liquid	1	Flam. Liq. 1	H224

For full text of abbreviations: see SECTION 16.

The most important adverse physicochemical, human health and environmental effects

Delayed or immediate effects can be expected after short or long-term exposure. The product is combustible and can be ignited by potential ignition sources.

2.2 Label elements

POR-15 CALIPER PAINT RED

Version number: GHS 1.0

Date of compilation: 2023-12-07

Labelling acc. to OSHA "Hazard Communication Standard" (29 CFR 1910.1200)

- Signal word danger

- Pictograms

GHS02, GHS07, GHS08



- Hazard statements

H224	Extremely flammable liquid and vapor.
H304	May be fatal if swallowed and enters airways.
H317	May cause an allergic skin reaction.
H332	Harmful if inhaled.
H340	May cause genetic defects.
H350	May cause cancer.
H372	Causes damage to organs through prolonged or repeated exposure.

- Precautionary statements

P201	Obtain special instructions before use.
P210	Keep away from heat/sparks/open flames/hot surfaces. No smoking.
P233	Keep container tightly closed.
P240	Ground/bond container and receiving equipment.
P241	Use explosion-proof electrical/ventilating/lighting equipment.
P242	Use only non-sparking tools.
P243	Take precautionary measures against static discharge.
P260	Do not breathe dust/fume/gas/mist/vapors/spray.
P270	Do not eat, drink or smoke when using this product.
P271	Use only outdoors or in a well-ventilated area.
P272	Contaminated work clothing must not be allowed out of the workplace.
P280	Wear protective gloves/eye protection/face protection.
P301+P310	If swallowed: Immediately call a poison center/doctor.
P302+P352	If on skin: Wash with plenty of water.
P303+P361+P353	If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.
P304+P340	If inhaled: Remove person to fresh air and keep comfortable for breathing.
P312	Call a poison center/doctor if you feel unwell.
P321	Specific treatment (see on this label).
P331	Do NOT induce vomiting.
P363	Wash contaminated clothing before reuse.
P370+P378	In case of fire: Use sand, carbon dioxide or powder extinguisher to extinguish.
P403+P235	Store in a well-ventilated place. Keep cool.
P405	Store locked up.
P501	Dispose of contents/container to industrial combustion plant.

- Hazardous ingredients for labelling

stoddard solvent, 2-butanone oxime, Naphtha (petroleum), hydrotreated heavy, Distillates (petroleum), hydro-treated light



Safety Data Sheet

acc. to 29 CFR 1910.1200 App D

POR-15 CALIPER PAINT RED

Version number: GHS 1.0

Date of compilation: 2023-12-07

2.3 Other hazards

Hazards not otherwise classified

Contains 2-butanone oxime. May produce an allergic reaction.

Very toxic to aquatic life with long lasting effects (GHS category 1: aquatic toxicity - acute and/or chronic).

Results of PBT and vPvB assessment

Does not contain a PBT-/vPvB-substance in a concentration of $\geq 0.1\%$.

Endocrine disrupting properties

Does not contain an endocrine disruptor (EDC) in a concentration of $\geq 0.1\%$.

SECTION 3: Composition/information on ingredients

3.1 Substances

Not relevant (mixture)

3.2 Mixtures

Description of the mixture

Name of substance	Identifier	Wt%	Classification acc. to GHS
alkyd resin	CAS No 63148-69-6	50 - < 75	
stoddard solvent	CAS No 8052-41-3	25 - < 50	Acute Tox. 3 / H331 Muta. 1B / H340 Carc. 1A / H350 STOT RE 1 / H372 Asp. Tox. 1 / H304 Flam. Liq. 3 / H226
2-methoxy-1-methylethyl acetate	CAS No 108-65-6	1 - < 5	Flam. Liq. 3 / H226
Naphtha (petroleum), hydrotreated heavy	CAS No 64742-48-9	1 - < 5	Muta. 1B / H340 Carc. 1A / H350 Asp. Tox. 1 / H304 Flam. Liq. 1 / H224
Diiron trioxide	CAS No 1309-37-1	1 - < 5	
Distillates (petroleum), hydro-treated light	CAS No 64742-47-8	0.1 - < 1	Acute Tox. 3 / H331 Asp. Tox. 1 / H304 Flam. Liq. 3 / H226
Soy Lecithin, Superior # 5, Superior DB	CAS No 8002-43-5	0.1 - < 1	
2-ethylhexanoic acid, zirconium salt	CAS No 22464-99-9	0.1 - < 1	Acute Tox. 4 / H332
Hexanoic acid, 2-ethyl-, cobalt(2+) salt (2:1)	CAS No 136-52-7	0.1 - < 1	

POR-15 CALIPER PAINT RED

Version number: GHS 1.0

Date of compilation: 2023-12-07

Name of substance	Identifier	Wt%	Classification acc. to GHS
2-butanone oxime	CAS No 96-29-7	0.1 - < 1	Acute Tox. 3 / H301 Acute Tox. 4 / H312 Acute Tox. 3 / H331 Skin Irrit. 2 / H315 Eye Dam. 1 / H318 Skin Sens. 1 / H317 Carc. 1B / H350 STOT SE 1 / H370 STOT SE 3 / H336 STOT RE 2 / H373 Flam. Liq. 4 / H227
naphtha (petroleum), hydrodesulphurized heavy	CAS No 64742-82-1	0 - < 0.1	Muta. 1B / H340 Carc. 1A / H350 STOT RE 1 / H372 Asp. Tox. 1 / H304 Flam. Liq. 1 / H224
xylene	CAS No 1330-20-7	0 - < 0.1	Acute Tox. 4 / H312 Acute Tox. 4 / H332 Skin Irrit. 2 / H315 Asp. Tox. 1 / H304 Flam. Liq. 3 / H226
2-(2-butoxyethoxy)ethanol	CAS No 112-34-5	0 - < 0.1	Eye Irrit. 2 / H319
ethyl benzene	CAS No 100-41-4	0 - < 0.1	Acute Tox. 4 / H332 Carc. 2 / H351 STOT RE 2 / H373 Asp. Tox. 1 / H304 Flam. Liq. 3 / H226
naphthalene	CAS No 91-20-3	0 - < 0.1	Acute Tox. 4 / H302 Acute Tox. 1 / H330 Carc. 2 / H351
solvent naphtha (petroleum), medium aliph.	CAS No 64742-88-7	0 - < 0.1	Acute Tox. 3 / H331 STOT RE 1 / H372 Asp. Tox. 1 / H304 Flam. Liq. 3 / H226

For full text of abbreviations: see SECTION 16.

SECTION 4: First-aid measures

4.1 Description of first-aid measures

General notes

Do not leave affected person unattended. Remove victim out of the danger area. Keep affected person warm, still and covered. Take off immediately all contaminated clothing. In all cases of doubt, or when symptoms persist, seek medical advice. In case of unconsciousness place person in the recovery position. Never give anything by mouth.

Following inhalation

If breathing is irregular or stopped, immediately seek medical assistance and start first aid actions. Provide fresh air.

Following skin contact

Wash with plenty of soap and water.

Following eye contact

Remove contact lenses, if present and easy to do. Continue rinsing. Irrigate copiously with clean, fresh water for at least 10 minutes, holding the eyelids apart.

POR-15 CALIPER PAINT RED

Version number: GHS 1.0

Date of compilation: 2023-12-07

Following ingestion

Rinse mouth with water (only if the person is conscious). Do NOT induce vomiting.

4.2 Most important symptoms and effects, both acute and delayed

Symptoms and effects are not known to date.

4.3 Indication of any immediate medical attention and special treatment needed

none

SECTION 5: Fire-fighting measures

5.1 Extinguishing media

Suitable extinguishing media

Water spray, BC-powder, Carbon dioxide (CO₂)

Unsuitable extinguishing media

Water jet

5.2 Special hazards arising from the substance or mixture

In case of insufficient ventilation and/or in use, may form flammable/explosive vapor-air mixture. Solvent vapors are heavier than air and may spread along floors. Places which are not ventilated, e.g. unventilated below ground level areas such as trenches, conduits and shafts, are particularly prone to the presence of flammable substances or mixtures.

Hazardous combustion products

Nitrogen oxides (NO_x), Carbon monoxide (CO), Carbon dioxide (CO₂)

5.3 Advice for firefighters

In case of fire and/or explosion do not breathe fumes. Coordinate firefighting measures to the fire surroundings. Do not allow firefighting water to enter drains or water courses. Collect contaminated firefighting water separately. Fight fire with normal precautions from a reasonable distance.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

For non-emergency personnel

Remove persons to safety.

For emergency responders

Wear breathing apparatus if exposed to vapors/dust/aerosols/gases.

6.2 Environmental precautions

Keep away from drains, surface and ground water. Retain contaminated washing water and dispose of it. If substance has entered a water course or sewer, inform the responsible authority.

6.3 Methods and material for containment and cleaning up

Advice on how to contain a spill

Covering of drains

Advice on how to clean up a spill

Wipe up with absorbent material (e.g. cloth, fleece). Collect spillage: sawdust, kieselgur (diatomite), sand, universal binder

Appropriate containment techniques

Use of adsorbent materials.

POR-15 CALIPER PAINT RED

Version number: GHS 1.0

Date of compilation: 2023-12-07

Other information relating to spills and releases

Place in appropriate containers for disposal. Ventilate affected area.

6.4 Reference to other sections

Hazardous combustion products: see section 5. Personal protective equipment: see section 8. Incompatible materials: see section 10. Disposal considerations: see section 13.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Recommendations

- Measures to prevent fire as well as aerosol and dust generation

Use local and general ventilation. Avoidance of ignition sources. Keep away from sources of ignition - No smoking. Take precautionary measures against static discharge. Use only in well-ventilated areas. Due to danger of explosion, prevent leakage of vapours into cellars, flues and ditches. Ground/bond container and receiving equipment. Use explosion-proof electrical/ventilating/lighting/equipment. Use only non-sparking tools.

- Specific notes/details

Places which are not ventilated, e.g. unventilated below ground level areas such as trenches, conduits and shafts, are particularly prone to the presence of flammable substances or mixtures. Vapors are heavier than air, spread along floors and form explosive mixtures with air. Vapors may form explosive mixtures with air.

Advice on general occupational hygiene

Wash hands after use. Do not eat, drink and smoke in work areas. Remove contaminated clothing and protective equipment before entering eating areas. Never keep food or drink in the vicinity of chemicals. Never place chemicals in containers that are normally used for food or drink. Keep away from food, drink and animal feedingstuffs.

7.2 Conditions for safe storage, including any incompatibilities

Managing of associated risks

- Explosive atmospheres

Keep container tightly closed and in a well-ventilated place. Use local and general ventilation. Keep cool. Protect from sunlight.

- Flammability hazards

Keep away from sources of ignition - No smoking. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Take precautionary measures against static discharge. Protect from sunlight.

- Ventilation requirements

Keep any substance that emits harmful vapors or gases in a place that allows these to be permanently extracted. Use local and general ventilation. Ground/bond container and receiving equipment.

- Packaging compatibilities

Only packagings which are approved (e.g. acc. to the Dangerous Goods Regulations) may be used.

7.3 Specific end use(s)

See section 16 for a general overview.

POR-15 CALIPER PAINT RED

Version number: GHS 1.0

Date of compilation: 2023-12-07

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational exposure limit values (Workplace Exposure Limits)											
Country	Name of agent	CAS No	Identifier	TWA [ppm]	TWA [mg/m ³]	STEL [ppm]	STEL [mg/m ³]	Ceiling-C [ppm]	Ceiling-C [mg/m ³]	Notation	Source
US	ethylbenzene	100-41-4	PEL (CA)	5	22	30	130				Cal/OSHA PEL
US	ethylbenzene	100-41-4	REL	100 (10 h)	435 (10 h)	125	545				NIOSH REL
US	ethylbenzene	100-41-4	TLV®	20							ACGIH® 2023
US	ethylbenzene	100-41-4	PEL	100	435						29 CFR 1910.1000
US	propylene glycol monomethyl ether acetate	108-65-6	PEL (CA)	100	541	150	811				Cal/OSHA PEL
US	diethylene glycol monobutyl ether	112-34-5	TLV®	10						iv	ACGIH® 2023
US	diiron trioxide (iron(III) oxide)	1309-37-1	TLV®		5					r	ACGIH® 2023
US	iron(III) oxide	1309-37-1	PEL (CA)		5					fume	Cal/OSHA PEL
US	iron(III) oxide	1309-37-1	PEL		10					fume	29 CFR 1910.1000
US	iron(III) oxide (diiron trioxide)	1309-37-1	REL		5 (10 h)					df, Fe	NIOSH REL
US	rouge	1309-37-1	REL							appx-D	NIOSH REL
US	rouge	1309-37-1	PEL		15					i, dust	29 CFR 1910.1000
US	rouge	1309-37-1	PEL		5					r, dust	29 CFR 1910.1000
US	xylene, mixture of isomers	1330-20-7	TLV®	20							ACGIH® 2023
US	xylene, mixture of isomers	1330-20-7	PEL	100	435						29 CFR 1910.1000
US	xylene (dimethylbenzene)	1330-20-7	PEL (CA)	100	435	150	655	300			Cal/OSHA PEL



Safety Data Sheet

acc. to 29 CFR 1910.1200 App D

POR-15 CALIPER PAINT RED

Version number: GHS 1.0

Date of compilation: 2023-12-07

Occupational exposure limit values (Workplace Exposure Limits)

Country	Name of agent	CAS No	Identifier	TWA [ppm]	TWA [mg/m ³]	STEL [ppm]	STEL [mg/m ³]	Ceiling-C [ppm]	Ceiling-C [mg/m ³]	Notation	Source
US	petroleum distillates (naphthalene) (rubber solvent)	64742-48-9	PEL	500	2,000						29 CFR 1910.1000
US	stoddard solvent	8052-41-3	PEL (CA)	100	525						Cal/OSHA PEL
US	stoddard solvent	8052-41-3	REL		350 (10 h)				1,800 (15 min)		NIOSH REL
US	stoddard solvent	8052-41-3	TLV®	100							ACGIH® 2023
US	stoddard solvent	8052-41-3	PEL	500	2,900						29 CFR 1910.1000
US	naphthalene	91-20-3	PEL (CA)	0.1	0.5						Cal/OSHA PEL
US	naphthalene	91-20-3	REL	10 (10 h)	50 (10 h)	15	75				NIOSH REL
US	naphthalene	91-20-3	PEL	10	50						29 CFR 1910.1000
US	naphthalene	91-20-3	TLV®	10						H	ACGIH® 2023

Notation

appx-D	see Appendix D - Substances with No Established RELs
Ceiling-C	ceiling value is a limit value above which exposure should not occur
df	as dust and fumes
dust	as dust
Fe	calculated as Fe (iron)
fume	as fume
H	absorbed through the skin
i	inhalable fraction
iv	inhalable fraction and vapor
r	respirable fraction
STEL	short-term exposure limit: a limit value above which exposure should not occur and which is related to a 15-minute period (unless otherwise specified)
TWA	time-weighted average (long-term exposure limit): measured or calculated in relation to a reference period of 8 hours time-weighted average (unless otherwise specified)

Biological limit values

Country	Name of agent	Parameter	Notation	Identifier	Value	Source
US	ethylbenzene	mandelic acid, benzoylformic acid	crea	BEI®	0.15 g/g	ACGIH® 2023
US	xylene, mixture of isomers	methylhippuric acids	crea	BEI®	1.5 g/g	ACGIH® 2023

Notation

crea	creatinine
------	------------



Safety Data Sheet

acc. to 29 CFR 1910.1200 App D

POR-15 CALIPER PAINT RED

Version number: GHS 1.0

Date of compilation: 2023-12-07

Relevant DNELs of components of the mixture						
Name of substance	CAS No	Endpoint	Threshold level	Protection goal, route of exposure	Used in	Exposure time
stoddard solvent	8052-41-3	DNEL	44 mg/m ³	human, inhalatory	worker (industry)	chronic - systemic effects
stoddard solvent	8052-41-3	DNEL	55 mg/m ³	human, inhalatory	worker (industry)	acute - systemic effects
stoddard solvent	8052-41-3	DNEL	44 mg/m ³	human, inhalatory	worker (industry)	chronic - local effects
stoddard solvent	8052-41-3	DNEL	55 mg/m ³	human, inhalatory	worker (industry)	acute - local effects
stoddard solvent	8052-41-3	DNEL	80 mg/kg bw/day	human, dermal	worker (industry)	chronic - systemic effects
stoddard solvent	8052-41-3	DNEL	30 mg/kg bw/day	human, dermal	worker (industry)	acute - systemic effects
2-methoxy-1-methyl-ethyl acetate	108-65-6	DNEL	275 mg/m ³	human, inhalatory	worker (industry)	chronic - systemic effects
2-methoxy-1-methyl-ethyl acetate	108-65-6	DNEL	550 mg/m ³	human, inhalatory	worker (industry)	acute - local effects
2-methoxy-1-methyl-ethyl acetate	108-65-6	DNEL	796 mg/kg bw/day	human, dermal	worker (industry)	chronic - systemic effects
Hexanoic acid, 2-ethyl-, cobalt(2+) salt (2:1)	136-52-7	DNEL	235.1 µg/m ³	human, inhalatory	worker (industry)	chronic - local effects
2-butanone oxime	96-29-7	DNEL	9 mg/m ³	human, inhalatory	worker (industry)	chronic - systemic effects
2-butanone oxime	96-29-7	DNEL	3.33 mg/m ³	human, inhalatory	worker (industry)	chronic - local effects
2-butanone oxime	96-29-7	DNEL	1.3 mg/kg bw/day	human, dermal	worker (industry)	chronic - systemic effects
2-butanone oxime	96-29-7	DNEL	2.5 mg/kg bw/day	human, dermal	worker (industry)	acute - systemic effects
xylene	1330-20-7	DNEL	221 mg/m ³	human, inhalatory	worker (industry)	chronic - systemic effects
xylene	1330-20-7	DNEL	442 mg/m ³	human, inhalatory	worker (industry)	acute - systemic effects
xylene	1330-20-7	DNEL	221 mg/m ³	human, inhalatory	worker (industry)	chronic - local effects
xylene	1330-20-7	DNEL	442 mg/m ³	human, inhalatory	worker (industry)	acute - local effects
xylene	1330-20-7	DNEL	212 mg/kg bw/day	human, dermal	worker (industry)	chronic - systemic effects
2-(2-butoxyethoxy)ethanol	112-34-5	DNEL	67.5 mg/m ³	human, inhalatory	worker (industry)	chronic - systemic effects
2-(2-butoxyethoxy)ethanol	112-34-5	DNEL	67.5 mg/m ³	human, inhalatory	worker (industry)	chronic - local effects
2-(2-butoxyethoxy)ethanol	112-34-5	DNEL	101.2 mg/m ³	human, inhalatory	worker (industry)	acute - local effects



Safety Data Sheet

acc. to 29 CFR 1910.1200 App D

POR-15 CALIPER PAINT RED

Version number: GHS 1.0

Date of compilation: 2023-12-07

Relevant DNELs of components of the mixture						
Name of substance	CAS No	Endpoint	Threshold level	Protection goal, route of exposure	Used in	Exposure time
2-(2-butoxyethoxy)ethanol	112-34-5	DNEL	83 mg/kg bw/day	human, dermal	worker (industry)	chronic - systemic effects
ethyl benzene	100-41-4	DNEL	77 mg/m ³	human, inhalatory	worker (industry)	chronic - systemic effects
ethyl benzene	100-41-4	DNEL	293 mg/m ³	human, inhalatory	worker (industry)	acute - local effects
ethyl benzene	100-41-4	DNEL	180 mg/kg bw/day	human, dermal	worker (industry)	chronic - systemic effects
naphthalene	91-20-3	DNEL	25 mg/m ³	human, inhalatory	worker (industry)	chronic - systemic effects
naphthalene	91-20-3	DNEL	25 mg/m ³	human, inhalatory	worker (industry)	chronic - local effects
naphthalene	91-20-3	DNEL	3.57 mg/kg bw/day	human, dermal	worker (industry)	chronic - systemic effects

Relevant PNECs of components of the mixture						
Name of substance	CAS No	Endpoint	Threshold level	Organism	Environmental compartment	Exposure time
stoddard solvent	8052-41-3	PNEC	0.14 mg/l	aquatic organisms	freshwater	short-term (single instance)
stoddard solvent	8052-41-3	PNEC	0.35 mg/l	aquatic organisms	marine water	short-term (single instance)
stoddard solvent	8052-41-3	PNEC	1.14 mg/kg	aquatic organisms	freshwater sediment	short-term (single instance)
stoddard solvent	8052-41-3	PNEC	0.14 mg/kg	aquatic organisms	marine sediment	short-term (single instance)
2-methoxy-1-methyl-ethyl acetate	108-65-6	PNEC	0.635 mg/l	aquatic organisms	freshwater	short-term (single instance)
2-methoxy-1-methyl-ethyl acetate	108-65-6	PNEC	0.064 mg/l	aquatic organisms	marine water	short-term (single instance)
2-methoxy-1-methyl-ethyl acetate	108-65-6	PNEC	100 mg/l	aquatic organisms	sewage treatment plant (STP)	short-term (single instance)
2-methoxy-1-methyl-ethyl acetate	108-65-6	PNEC	3.29 mg/kg	aquatic organisms	freshwater sediment	short-term (single instance)
2-methoxy-1-methyl-ethyl acetate	108-65-6	PNEC	0.329 mg/kg	aquatic organisms	marine sediment	short-term (single instance)
2-methoxy-1-methyl-ethyl acetate	108-65-6	PNEC	0.29 mg/kg	terrestrial organisms	soil	short-term (single instance)
Hexanoic acid, 2-ethyl-, cobalt(2+) salt (2:1)	136-52-7	PNEC	0.62 µg/l	aquatic organisms	freshwater	short-term (single instance)
Hexanoic acid, 2-ethyl-, cobalt(2+) salt (2:1)	136-52-7	PNEC	2.36 µg/l	aquatic organisms	marine water	short-term (single instance)



Safety Data Sheet

acc. to 29 CFR 1910.1200 App D

POR-15 CALIPER PAINT RED

Version number: GHS 1.0

Date of compilation: 2023-12-07

Relevant PNECs of components of the mixture						
Name of substance	CAS No	Endpoint	Threshold level	Organism	Environmental compartment	Exposure time
Hexanoic acid, 2-ethyl-, cobalt(2+) salt (2:1)	136-52-7	PNEC	0.37 mg/l	aquatic organisms	sewage treatment plant (STP)	short-term (single instance)
Hexanoic acid, 2-ethyl-, cobalt(2+) salt (2:1)	136-52-7	PNEC	53.8 mg/kg	aquatic organisms	freshwater sediment	short-term (single instance)
Hexanoic acid, 2-ethyl-, cobalt(2+) salt (2:1)	136-52-7	PNEC	69.8 mg/kg	aquatic organisms	marine sediment	short-term (single instance)
Hexanoic acid, 2-ethyl-, cobalt(2+) salt (2:1)	136-52-7	PNEC	10.9 mg/kg	terrestrial organisms	soil	short-term (single instance)
2-butanone oxime	96-29-7	PNEC	0.256 mg/l	aquatic organisms	freshwater	short-term (single instance)
2-butanone oxime	96-29-7	PNEC	177 mg/l	aquatic organisms	sewage treatment plant (STP)	short-term (single instance)
xylene	1330-20-7	PNEC	0.327 mg/l	aquatic organisms	freshwater	short-term (single instance)
xylene	1330-20-7	PNEC	0.327 mg/l	aquatic organisms	marine water	short-term (single instance)
xylene	1330-20-7	PNEC	6.58 mg/l	aquatic organisms	sewage treatment plant (STP)	short-term (single instance)
xylene	1330-20-7	PNEC	12.46 mg/kg	aquatic organisms	freshwater sediment	short-term (single instance)
xylene	1330-20-7	PNEC	12.46 mg/kg	aquatic organisms	marine sediment	short-term (single instance)
xylene	1330-20-7	PNEC	2.31 mg/kg	terrestrial organisms	soil	short-term (single instance)
2-(2-butoxyethoxy)ethanol	112-34-5	PNEC	1.1 mg/l	aquatic organisms	freshwater	short-term (single instance)
2-(2-butoxyethoxy)ethanol	112-34-5	PNEC	0.11 mg/l	aquatic organisms	marine water	short-term (single instance)
2-(2-butoxyethoxy)ethanol	112-34-5	PNEC	200 mg/l	aquatic organisms	sewage treatment plant (STP)	short-term (single instance)
2-(2-butoxyethoxy)ethanol	112-34-5	PNEC	4.4 mg/kg	aquatic organisms	freshwater sediment	short-term (single instance)
2-(2-butoxyethoxy)ethanol	112-34-5	PNEC	0.44 mg/kg	aquatic organisms	marine sediment	short-term (single instance)
2-(2-butoxyethoxy)ethanol	112-34-5	PNEC	0.32 mg/kg	terrestrial organisms	soil	short-term (single instance)
ethyl benzene	100-41-4	PNEC	0.1 mg/l	aquatic organisms	freshwater	short-term (single instance)
ethyl benzene	100-41-4	PNEC	0.01 mg/l	aquatic organisms	marine water	short-term (single instance)

POR-15 CALIPER PAINT RED

Version number: GHS 1.0

Date of compilation: 2023-12-07

Relevant PNECs of components of the mixture						
Name of substance	CAS No	Endpoint	Threshold level	Organism	Environmental compartment	Exposure time
ethyl benzene	100-41-4	PNEC	9.6 mg/l	aquatic organisms	sewage treatment plant (STP)	short-term (single instance)
ethyl benzene	100-41-4	PNEC	13.7 mg/kg	aquatic organisms	freshwater sediment	short-term (single instance)
ethyl benzene	100-41-4	PNEC	1.37 mg/kg	aquatic organisms	marine sediment	short-term (single instance)
ethyl benzene	100-41-4	PNEC	2.68 mg/kg	terrestrial organisms	soil	short-term (single instance)

8.2 Exposure controls

Appropriate engineering controls

General ventilation.

Individual protection measures (personal protective equipment)

Eye/face protection

Wear eye/face protection.

Skin protection

- Hand protection

Wear suitable gloves. Chemical protection gloves are suitable, which are tested according to EN 374. Check leak-tightness/impermeability prior to use. In the case of wanting to use the gloves again, clean them before taking off and air them well. For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves.

- Other protection measures

Take recovery periods for skin regeneration. Preventive skin protection (barrier creams/ointments) is recommended. Wash hands thoroughly after handling.

Respiratory protection

In case of inadequate ventilation wear respiratory protection.

Environmental exposure controls

Use appropriate container to avoid environmental contamination. Keep away from drains, surface and ground water.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Appearance

Physical state	liquid
Color	not determined
Particle	not relevant (liquid)
Odor	characteristic

POR-15 CALIPER PAINT RED

Version number: GHS 1.0

Date of compilation: 2023-12-07

Other safety parameters

pH (value)	not determined
Melting point/freezing point	not determined
Initial boiling point and boiling range	≥-20 °C at 101.3 kPa
Flash point	40 °C
Evaporation rate	Not determined
Flammability (solid, gas)	not relevant, (fluid)

Explosive limits

- Lower explosion limit (LEL)	1.4 vol%
- Upper explosion limit (UEL)	7.6 vol%
Vapor pressure	≤240 kPa at 37.8 °C
Density	not determined
Vapor density	this information is not available
Relative density	Information on this property is not available
Solubility(ies)	not determined

Partition coefficient

- n-octanol/water (log KOW)	this information is not available
Auto-ignition temperature	232 °C (auto-ignition temperature (liquids and gases))
Viscosity	not determined
Explosive properties	none
Oxidizing properties	none

9.2 Other information

Solid content	0.3314 %
---------------	----------



Safety Data Sheet

acc. to 29 CFR 1910.1200 App D

POR-15 CALIPER PAINT RED

Version number: GHS 1.0

Date of compilation: 2023-12-07

SECTION 10: Stability and reactivity

10.1 Reactivity

Concerning incompatibility: see below "Conditions to avoid" and "Incompatible materials". The mixture contains reactive substance(s). Risk of ignition.

If heated:

Risk of ignition

10.2 Chemical stability

See below "Conditions to avoid".

10.3 Possibility of hazardous reactions

No known hazardous reactions.

10.4 Conditions to avoid

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

Hints to prevent fire or explosion

Use explosion-proof electrical/ventilating/lighting/equipment. Use only non-sparking tools. Take precautionary measures against static discharge.

10.5 Incompatible materials

Oxidizers

10.6 Hazardous decomposition products

Reasonably anticipated hazardous decomposition products produced as a result of use, storage, spill and heating are not known. Hazardous combustion products: see section 5.

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Test data are not available for the complete mixture.

Classification procedure

The method for classification of the mixture is based on ingredients of the mixture (additivity formula).

Classification acc. to OSHA "Hazard Communication Standard" (29 CFR 1910.1200)

Acute toxicity

Harmful if inhaled.

- Acute toxicity estimate (ATE)

Inhalation: vapor 15.94 mg/l/4h

Acute toxicity estimate (ATE) of components of the mixture

Name of substance	CAS No	Exposure route	ATE
stoddard solvent	8052-41-3	inhalation: vapor	>5.5 mg/l/4h
Distillates (petroleum), hydro-treated light	64742-47-8	inhalation: vapor	>5.28 mg/l/4h
2-ethylhexanoic acid, zirconium salt	22464-99-9	inhalation: dust/mist	>4.3 mg/l/4h



Safety Data Sheet

acc. to 29 CFR 1910.1200 App D

POR-15 CALIPER PAINT RED

Version number: GHS 1.0

Date of compilation: 2023-12-07

Acute toxicity estimate (ATE) of components of the mixture

Name of substance	CAS No	Exposure route	ATE
2-butanone oxime	96-29-7	dermal	>1,000 mg/kg
2-butanone oxime	96-29-7	inhalation: vapor	>4.83 mg/l/4h
xylene	1330-20-7	dermal	1,100 mg/kg
xylene	1330-20-7	inhalation: vapor	11 mg/l/4h
ethyl benzene	100-41-4	inhalation: vapor	11 mg/l/4h
naphthalene	91-20-3	oral	710 mg/kg
naphthalene	91-20-3	inhalation: vapor	>0.4 mg/l/4h
naphthalene	91-20-3	inhalation: dust/mist	0.005 mg/l/4h
solvent naphtha (petroleum), medium aliph.	64742-88-7	inhalation: vapor	>5.28 mg/l/4h

Skin corrosion/irritation

Shall not be classified as corrosive/irritant to skin.

Serious eye damage/eye irritation

Shall not be classified as seriously damaging to the eye or eye irritant.

Respiratory or skin sensitization

May cause an allergic skin reaction.

Germ cell mutagenicity

May cause genetic defects.

Carcinogenicity

May cause cancer.

IARC Monographs on the Evaluation of Carcinogenic Risks to Humans

Name of substance	CAS No	Classification	Number
ethyl benzene	100-41-4	2B	
naphthalene	91-20-3	2B	
xylene	1330-20-7	3	
Diiron trioxide	1309-37-1	3	

Legend

2B Possibly carcinogenic to humans
3 Not classifiable as to carcinogenicity in humans

POR-15 CALIPER PAINT RED

Version number: GHS 1.0

Date of compilation: 2023-12-07

National Toxicology Program (United States): Report on Carcinogens

Name of substance	CAS No	Classification	Number
naphthalene	91-20-3	Reasonably anticipated to be a human carcinogen	11th Report on Carcinogens

Reproductive toxicity

Shall not be classified as a reproductive toxicant.

Specific target organ toxicity - single exposure

Shall not be classified as a specific target organ toxicant (single exposure).

Specific target organ toxicity - repeated exposure

Causes damage to organs through prolonged or repeated exposure.

Aspiration hazard

May be fatal if swallowed and enters airways.

SECTION 12: Ecological information

12.1 Toxicity

Very toxic to aquatic life with long lasting effects.

Aquatic toxicity (acute) of components of the mixture

Name of substance	CAS No	Endpoint	Value	Species	Exposure time
stoddard solvent	8052-41-3	LC50	0.18 mg/l	fish	96 h
stoddard solvent	8052-41-3	LL50	41.4 mg/l	fish	96 h
stoddard solvent	8052-41-3	EL50	2.5 mg/l	algae	96 h
stoddard solvent	8052-41-3	EC50	0.58 mg/l	algae	96 h
2-methoxy-1-methylethyl acetate	108-65-6	LC50	180 mg/l	fish	96 h
2-methoxy-1-methylethyl acetate	108-65-6	EC50	>500 mg/l	aquatic invertebrates	48 h
2-methoxy-1-methylethyl acetate	108-65-6	ErC50	>1,000 mg/l	algae	96 h
Naphtha (petroleum), hydrotreated heavy	64742-48-9	LL50	8.2 mg/l	fish	96 h
Naphtha (petroleum), hydrotreated heavy	64742-48-9	EL50	4.5 mg/l	aquatic invertebrates	48 h
Distillates (petroleum), hydro-treated light	64742-47-8	LL50	5 mg/l	fish	96 h
Distillates (petroleum), hydro-treated light	64742-47-8	EL50	1.4 mg/l	aquatic invertebrates	48 h
2-ethylhexanoic acid, zirconium salt	22464-99-9	LC50	>100 mg/l	fish	96 h



Safety Data Sheet

acc. to 29 CFR 1910.1200 App D

POR-15 CALIPER PAINT RED

Version number: GHS 1.0

Date of compilation: 2023-12-07

Aquatic toxicity (acute) of components of the mixture					
Name of substance	CAS No	Endpoint	Value	Species	Exposure time
2-ethylhexanoic acid, zirconium salt	22464-99-9	LL50	>100 mg/l	fish	96 h
2-ethylhexanoic acid, zirconium salt	22464-99-9	EC50	>0.17 mg/l	aquatic invertebrates	48 h
2-ethylhexanoic acid, zirconium salt	22464-99-9	ErC50	49.3 mg/l	algae	72 h
Hexanoic acid, 2-ethyl-, cobalt(2+) salt (2:1)	136-52-7	LC50	54.1 mg/l	fish	96 h
Hexanoic acid, 2-ethyl-, cobalt(2+) salt (2:1)	136-52-7	EC50	2,618 µg/l	aquatic invertebrates	48 h
Hexanoic acid, 2-ethyl-, cobalt(2+) salt (2:1)	136-52-7	ErC50	71,314 µg/l	algae	96 h
2-butanone oxime	96-29-7	LC50	>100 mg/l	fish	96 h
2-butanone oxime	96-29-7	EC50	201 mg/l	aquatic invertebrates	48 h
2-butanone oxime	96-29-7	ErC50	11.8 mg/l	algae	72 h
naphtha (petroleum), hydrodesulphurized heavy	64742-82-1	LL50	8.2 mg/l	fish	96 h
naphtha (petroleum), hydrodesulphurized heavy	64742-82-1	EL50	4.5 mg/l	aquatic invertebrates	48 h
xylene	1330-20-7	LC50	8.4 mg/l	fish	96 h
xylene	1330-20-7	EC50	4.9 mg/l	algae	72 h
xylene	1330-20-7	ErC50	4.7 mg/l	algae	72 h
2-(2-butoxyethoxy)ethanol	112-34-5	LC50	1,300 mg/l	fish	96 h
2-(2-butoxyethoxy)ethanol	112-34-5	EC50	>100 mg/l	aquatic invertebrates	48 h
2-(2-butoxyethoxy)ethanol	112-34-5	ErC50	>100 mg/l	algae	96 h
ethyl benzene	100-41-4	LC50	7 mg/l	fish	24 h
ethyl benzene	100-41-4	EC50	2.4 mg/l	aquatic invertebrates	48 h
naphthalene	91-20-3	LC50	1.6 mg/l	fish	96 h
naphthalene	91-20-3	EC50	2.16 mg/l	aquatic invertebrates	48 h
solvent naphtha (petroleum), medium aliph.	64742-88-7	LL50	5 mg/l	fish	96 h
solvent naphtha (petroleum), medium aliph.	64742-88-7	EL50	1.4 mg/l	aquatic invertebrates	48 h

POR-15 CALIPER PAINT RED

Version number: GHS 1.0

Date of compilation: 2023-12-07

Aquatic toxicity (chronic) of components of the mixture					
Name of substance	CAS No	Endpoint	Value	Species	Exposure time
stoddard solvent	8052-41-3	EL50	1.19 mg/l	aquatic invertebrates	21 d
stoddard solvent	8052-41-3	EC50	0.33 mg/l	aquatic invertebrates	21 d
2-methoxy-1-methylethyl acetate	108-65-6	LC50	63.5 mg/l	fish	14 d
2-methoxy-1-methylethyl acetate	108-65-6	EC50	>100 mg/l	aquatic invertebrates	21 d
Naphtha (petroleum), hydro-treated heavy	64742-48-9	EL50	10 mg/l	fish	21 d
Naphtha (petroleum), hydro-treated heavy	64742-48-9	EC50	15.41 mg/l	microorganisms	40 h
Distillates (petroleum), hydro-treated light	64742-47-8	EL50	0.89 mg/l	aquatic invertebrates	21 d
2-ethylhexanoic acid, zirconium salt	22464-99-9	EC50	75 mg/l	aquatic invertebrates	21 d
Hexanoic acid, 2-ethyl-, cobalt(2+) salt (2:1)	136-52-7	LC50	41,625 µg/l	fish	28 d
Hexanoic acid, 2-ethyl-, cobalt(2+) salt (2:1)	136-52-7	EC50	82.2 µg/l	aquatic invertebrates	21 d
2-butanone oxime	96-29-7	EC50	≥100 mg/l	aquatic invertebrates	21 d
naphtha (petroleum), hydrodesulphurized heavy	64742-82-1	EL50	10 mg/l	fish	21 d
naphtha (petroleum), hydrodesulphurized heavy	64742-82-1	EC50	15.41 mg/l	microorganisms	40 h
xylene	1330-20-7	EL50	2.9 mg/l	aquatic invertebrates	21 d
xylene	1330-20-7	ErC50	4.36 mg/l	algae	73 h
xylene	1330-20-7	EC50	2.2 mg/l	algae	73 h
ethyl benzene	100-41-4	LC50	3.6 mg/l	aquatic invertebrates	7 d
naphthalene	91-20-3	EC50	2.96 mg/l	algae	4 h
solvent naphtha (petroleum), medium aliph.	64742-88-7	EL50	0.89 mg/l	aquatic invertebrates	21 d

12.2 Persistence and degradability

Data are not available.

12.3 Bioaccumulative potential

Data are not available.

12.4 Mobility in soil

Data are not available.



Safety Data Sheet

acc. to 29 CFR 1910.1200 App D

POR-15 CALIPER PAINT RED

Version number: GHS 1.0

Date of compilation: 2023-12-07

12.5 Results of PBT and vPvB assessment

According to the results of its assessment, this substance is not a PBT or a vPvB. Does not contain a PBT-/vPvB-substance in a concentration of $\geq 0.1\%$.

12.6 Endocrine disrupting properties

Does not contain an endocrine disruptor (EDC) in a concentration of $\geq 0.1\%$.

12.7 Other adverse effects

Data are not available.

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Waste treatment-relevant information

Solvent reclamation/regeneration.

Sewage disposal-relevant information

Do not empty into drains. Avoid release to the environment. Refer to special instructions/safety data sheets.

Waste treatment of containers/packages

Only packagings which are approved (e.g. acc. to DOT) may be used. Completely emptied packages can be recycled. Handle contaminated packages in the same way as the substance itself.

Remarks

Please consider the relevant national or regional provisions. Waste shall be separated into the categories that can be handled separately by the local or national waste management facilities.

SECTION 14: Transport information

14.1 UN number

DOT	UN 1263
IMDG-Code	UN 1263
ICAO-TI	UN 1263

14.2 UN proper shipping name

DOT	Paint
IMDG-Code	PAINT
ICAO-TI	Paint

14.3 Transport hazard class(es)

DOT	3
IMDG-Code	3
ICAO-TI	3

14.4 Packing group

DOT	III
IMDG-Code	III
ICAO-TI	III

POR-15 CALIPER PAINT RED

Version number: GHS 1.0

Date of compilation: 2023-12-07

- 14.5 Environmental hazards** hazardous to the aquatic environment
 Environmentally hazardous substance (aquatic environment) stoddard solvent
- 14.6 Special precautions for user**
 There is no additional information.
- 14.7 Transport in bulk according to IMO instruments**
 The cargo is not intended to be carried in bulk.

Information for each of the UN Model Regulations

Transport of dangerous goods by road or rail (49 CFR US DOT) - Additional information

Particulars in the shipper's declaration UN1263, Paint, (contains: Naphtha (petroleum), hydrotreated heavy, naphtha (petroleum), hydrodesulphurized heavy), 3, III, environmentally hazardous

Reportable quantity (RQ) 1,196,172 lbs (543,062 kg) (xylene) (naphthalene)

Danger label(s) 3, fish and tree



Environmental hazards YES (hazardous to the aquatic environment)

Special provisions (SP) 367, B1, B52, B131, IB3, T2, TP1, TP29

ERG No 128

International Maritime Dangerous Goods Code (IMDG) - Additional information

Marine pollutant YES (hazardous to the aquatic environment)

Danger label(s) 3, fish and tree



Special provisions (SP) 163, 223, 367, 955

Excepted quantities (EQ) E1

Limited quantities (LQ) 5 L

EmS F-E, S-E

Stowage category A

International Civil Aviation Organization (ICAO-IATA/DGR) - Additional information

Environmental hazards YES (hazardous to the aquatic environment)

Danger label(s) 3



Special provisions (SP) A3, A72, A192

Excepted quantities (EQ) E1



Safety Data Sheet

acc. to 29 CFR 1910.1200 App D

POR-15 CALIPER PAINT RED

Version number: GHS 1.0

Date of compilation: 2023-12-07

Limited quantities (LQ)

10 L

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations specific for the product in question

National regulations (United States)

Superfund Amendment and Reauthorization Act (SARA TITLE III)

- The List of Extremely Hazardous Substances and Their Threshold Planning Quantities (EPCRA Section 302, 304)

none of the ingredients are listed

- Specific Toxic Chemical Listings (EPCRA Section 313)

Toxics Release Inventory: Specific Toxic Chemical Listings

Name of substance	CAS No	Remarks	Effective date
ethyl benzene	100-41-4		1986-12-31
naphthalene	91-20-3		1986-12-31
xylene	1330-20-7		1986-12-31

Comprehensive Environmental Response, Compensation, and Liability Act (CERCLA)

- List of Hazardous Substances and Reportable Quantities (CERCLA section 102a) (40 CFR 302.4)

Name of substance	CAS No	Remarks	Statutory code	Final RQ pounds (Kg)
ethyl benzene	100-41-4		1 2 3	1000 (454)
naphthalene	91-20-3		1 2 3 4	100 (45,4)
xylene	1330-20-7		1 3 4	100 (45,4)

Legend

- 1 "1" indicates that the statutory source is section 311(b)(2) of the Clean Water Act
- 2 "2" indicates that the source is section 307(a) of the Clean Water Act
- 3 "3" indicates that the source is section 112 of the Clean Air Act
- 4 "4" indicates that the source is section 3001 of the Resource Conservation and Recovery Act (RCRA)

Clean Air Act

none of the ingredients are listed



Safety Data Sheet

acc. to 29 CFR 1910.1200 App D

POR-15 CALIPER PAINT RED

Version number: GHS 1.0

Date of compilation: 2023-12-07

Right to Know Hazardous Substance List

- Cleaning Product Right to Know Act Substance List (CA-RTK)

Name of substance	CAS No	Functionality	Authoritative Lists
stoddard solvent	8052-41-3		ATSDR Neurotoxicants EC Annex VI CMRs - Cat. 1B
Naphtha (petroleum), hydrotreated heavy	64742-48-9		Canada PBiTs EC Annex VI CMRs - Cat. 1B
2-butanone oxime	96-29-7		EC Annex VI CMRs - Cat. 1B
naphtha (petroleum), hydrodesulphurized heavy	64742-82-1		Canada PBiTs EC Annex VI CMRs - Cat. 1B
xylene	1330-20-7		ATSDR Neurotoxicants CA MCLs CA TACs CDC 4th National Exposure Report IRIS Neurotoxicants OEHHA RELs
2-(2-butoxyethoxy)ethanol			CA TACs
ethyl benzene	100-41-4		ATSDR Neurotoxicants CA MCLs CA TACs CDC 4th National Exposure Report CWA 303(c) IARC Carcinogens - 2B OEHHA RELs Prop 65
naphthalene	91-20-3		ATSDR Neurotoxicants CA NLs CA TACs CDC 4th National Exposure Report CWA 303(c) CWA 303(d) IARC Carcinogens - 2B IRIS Neurotoxicants NTP 13th RoC - reasonable OEHHA RELs Prop 65 U.S. EPA NWMP PBTs

- Toxic or Hazardous Substance List (MA-TURA)

Name of substance	CAS No	DEP CODE	PBT / HHS / LHS	PBT / HHS Threshold	De Minimis Concentration Threshold
ethyl benzene	100-41-4				0.1 %
naphthalene	91-20-3				0.1 %
2-(2-butoxyethoxy)ethanol		1022			1.0 %
xylene	1330-20-7				1.0 %



Safety Data Sheet

acc. to 29 CFR 1910.1200 App D

POR-15 CALIPER PAINT RED

Version number: GHS 1.0

Date of compilation: 2023-12-07

- Hazardous Substances List (MN-ERTK)

Name of substance	CAS No	References	Remarks
Naphtha (petroleum), hydrotreated heavy	64742-48-9	A, O	
stoddard solvent	8052-41-3	A, N, O	
Diiron trioxide	1309-37-1	A, O	fume
Diiron trioxide	1309-37-1	A	

Legend

- A American Conference of Governmental Industrial Hygienists (ACGIH), "Threshold Limit Values for Chemical Substances and Physical Agents and Biological Exposure Indices for 1992-93", available from ACGIH
- fume Small solid particles formed by the condensation of vapors of solid materials.
- N National Institute for Occupational Safety and Health (NIOSH), "Recommendations for Occupational Safety and Health Standards," August 1988, available from NIOSH, Publications Dissemination Office, Division of Standards Development and Technology Transfer
- O Occupational Safety and Health Administration (OSHA), Safety and Health Standards, Code of Federal Regulations, title 29, part 1910, subpart Z, "Toxic and Hazardous Substances, 1990." General information: Minnesota Department of Labor and Industry, Occupational Safety and Health Division

- Hazardous Substance List (NJ-RTK)

Name of substance	CAS No	Remarks	Classifications
ethyl benzene	100-41-4		CA F3
naphtha (petroleum), hydrodesulphurized heavy	8052-41-3		F2
stoddard solvent	8052-41-3		F2
naphthalene	91-20-3		CA F2
2-(2-butoxyethoxy)ethanol			
xylene	1330-20-7		F3
Diiron trioxide	1309-37-1		

Legend

- CA Carcinogenic
- F2 Flammable - Second Degree
- F3 Flammable - Third Degree

- Hazardous Substance List (Chapter 323) (PA-RTK)

Name acc. to inventory	CAS No	Classification
STODDARD SOLVENT	8052-41-3	
IRON OXIDE (FE2O3)	1309-37-1	

POR-15 CALIPER PAINT RED

Version number: GHS 1.0

Date of compilation: 2023-12-07

- Hazardous Substance List (RI-RTK)

Name of substance	CAS No	References
ethyl benzene	100-41-4	T, F
naphtha (petroleum), hydrodesulphurized heavy	8052-41-3	T
stoddard solvent	8052-41-3	T
naphthalene	91-20-3	T, F
xylene	1330-20-7	T, F
xylene	1330-20-7	T, F
xylene	1330-20-7	T, F
Diiron trioxide	1309-37-1	T
Diiron trioxide	1309-37-1	T

Legend

F Flammability (NFPA®)
T Toxicity (ACGIH®)

California Environmental Protection Agency (Cal/EPA): Proposition 65 - Safe Drinking Water and Toxic Enforcement Act of 1987

Proposition 65 List of chemicals			
Name acc. to inventory	CAS No	Remarks	Type of the toxicity
ethylbenzene	100-41-4		cancer
naphthalene	91-20-3		cancer

Industry or sector specific available guidance(s)

NPCA-HMIS® III

Hazardous Materials Identification System. American Coatings Association.

Category	Rating	Description
Chronic	*	chronic (long-term) health effects may result from repeated overexposure
Health	2	temporary or minor injury may occur
Flammability	4	material that rapidly or completely vaporizes at atmospheric pressure and normal ambient temperature or that is readily dispersed in air and burn readily
Physical hazard	0	material that is normally stable, even under fire conditions, and will not react with water, polymerize, decompose, condense, or self-react. Non-explosive
Personal protection	-	

NFPA® 704

National Fire Protection Association: Standard System for the Identification of the Hazards of Materials for Emergency Response (United States).



Safety Data Sheet

acc. to 29 CFR 1910.1200 App D

POR-15 CALIPER PAINT RED

Version number: GHS 1.0

Date of compilation: 2023-12-07

Category	Degree of hazard	Description
Flammability	4	material that rapidly or completely vaporizes at atmospheric pressure and normal ambient temperature or that is readily dispersed in air and burn readily
Health	2	material that, under emergency conditions, can cause temporary incapacitation or residual injury
Instability	0	material that is normally stable, even under fire conditions
Special hazard		

National inventories

Country	Inventory	Status
US	TSCA	all ingredients are listed (ACTIVE)

Legend

TSCA Toxic Substance Control Act

15.2 Chemical Safety Assessment

Chemical safety assessments for substances in this mixture were not carried out.

SECTION 16: Other information, including date of preparation or last revision

Key literature references and sources for data

OSHA Hazard Communication Standard (HCS), 29 CFR 1910.1200.

Transport of dangerous goods by road or rail (49 CFR US DOT). International Maritime Dangerous Goods Code (IMDG). Dangerous Goods Regulations (DGR) for the air transport (IATA).

Classification procedure

Physical and chemical properties: The classification is based on tested mixture.

Health hazards, Environmental hazards: The method for classification of the mixture is based on ingredients of the mixture (additivity formula).

Disclaimer

This information is based upon the present state of our knowledge. This SDS has been compiled and is solely intended for this product.

Safety Data Sheet

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Initial preparation date: 03.23.2018

Page 1 of 10

Cleaner Degreaser

SECTION 1: Identification

Product identifier

Product name: Cleaner Degreaser

Product code: 40101, 40104, 40105, 40116, 40155, 240101, 240104, 240105, 240116, 240155



Recommended use of the product and restriction on use

Relevant identified uses: Cleaner, Degreaser

Uses advised against: Not determined or not applicable.

Reasons why uses advised against: Not determined or not applicable.

Manufacturer or supplier details

Manufacturer:

United States

P.O.R. Products

38 Portman Road

New Rochelle, NY 10801

914-636-0700

Emergency telephone number:

United States

ChemTel Inc.

+1 800 255 3924

+1 813 248 0585

SECTION 2: Hazard(s) identification

GHS classification:

Corrosive to metals, category 1

Skin corrosion, category 1A

Carcinogenicity, category 2

Specific target organ toxicity - single exposure, category 2

Label elements

Hazard pictograms:



Signal word: Danger

Hazard statements:

H290 May be corrosive to metals.

H314 Causes severe skin burns and eye damage.

H351 Suspected of causing cancer.

H371 May cause damage to organs (respiratory system) if inhaled as a mist.

Precautionary statements:

P234 Keep only in original container.

P260 Do not breathe dust/fume/gas/mist/vapors/spray.

P264 Wash hands and skin thoroughly after handling.

P280 Wear protective gloves/protective clothing/eye protection/face protection.

Safety Data Sheet

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Initial preparation date: 03.23.2018

Page 2 of 10

Cleaner Degreaser

P201 Obtain special instructions before use.
P202 Do not handle until all safety precautions have been read and understood.
P270 Do not eat, drink or smoke when using this product.
P390 Absorb spillage to prevent material damage
P310 Immediately call a POISON CENTER or doctor/physician.
P321 Specific treatment (see first aid instructions on this label).
P363 Wash contaminated clothing before reuse
P301+P330+P331 IF SWALLOWED: Rinse mouth. Do NOT induce vomiting.
P303+P361+P353 IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower.
P304+P340 IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.
P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P406 Store in a corrosive resistant container with a resistant inner liner.
P405 Store locked up.
P501 Dispose of contents/container in accordance with applicable regional, national and local laws and regulations.

Hazards not otherwise classified: None

SECTION 3: Composition/information on ingredients

Identification	Name	Weight %
CAS number: 111-76-2	2-Butoxyethanol	1-3
CAS number: 1310-58-3	Potassium hydroxide	2-5
CAS number: 68439-45-2	Alcohols, C6-12, ethoxylated, liquids	1-3

Additional Information: None

SECTION 4: First aid measures

Description of first aid measures

General notes:

Not determined or not applicable.

After inhalation:

Loosen clothing as necessary and position individual in a comfortable position
Maintain an unobstructed airway
Get medical advice/attention if you feel unwell
Take precautions to ensure your own safety
Remove source of exposure or move person to fresh air and keep comfortable for breathing
Immediately call a POISON CONTROL CENTER or seek medical attention
If breathing has stopped, trained personnel should begin rescue breathing
Avoid mouth-to-mouth contact by using a barrier device
If the heart has stopped, immediately start cardiopulmonary resuscitation (CPR)

After skin contact:

Rinse affected area with soap and water
If symptoms develop or persist, seek medical attention
Avoid direct contact and wear chemical protective clothing, if necessary

Safety Data Sheet

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Initial preparation date: 03.23.2018

Page 3 of 10

Cleaner Degreaser

Immediately take off all contaminated clothing
Gently blot or brush away excess product
Rinse skin with lukewarm, gently flowing water until medical aid is available
Immediately call a POISON CONTROL CENTER or seek medical attention
Wash contaminated clothing before re-use or discard

After eye contact:

Rinse/flush exposed eye(s) gently using water for 15-20 minutes
If symptoms develop or persist, seek medical attention
Avoid direct contact and wear chemical protective gloves, if necessary
Rinse eyes cautiously with lukewarm, gently flowing water for several minutes, while holding the eyelids open
Remove contact lenses, if present and easy to do so
Continue rinsing until medical aid is available
Immediately call a POISON CONTROL CENTER or seek medical attention

After swallowing:

Rinse mouth thoroughly
Seek medical attention if irritation, discomfort, or vomiting persists
Immediately call a POISON CONTROL CENTER or seek medical attention
Do not induce vomiting and rinse mouth
If vomiting occurs naturally, lie on your side, in the recovery position
If breathing has stopped, trained personnel should begin rescue breathing
Avoid mouth-to-mouth contact by using a barrier device
If the heart has stopped, immediately start cardiopulmonary resuscitation (CPR)

Most important symptoms and effects, both acute and delayed

Acute symptoms and effects:

Not determined or not applicable.

Delayed symptoms and effects:

Not determined or not applicable.

Immediate medical attention and special treatment

Specific treatment:

Not determined or not applicable.

Notes for the doctor:

Treat symptomatically

SECTION 5: Firefighting measures

Extinguishing media

Suitable extinguishing media:

Use appropriate fire suppression agents for adjacent combustible materials or sources of ignition

Unsuitable extinguishing media:

Not determined or not applicable.

Specific hazards during fire-fighting:

Thermal decomposition can lead to release of irritating gases and vapors
May form corrosive mixtures with water

Special protective equipment for firefighters:

Use typical firefighting equipment, self-contained breathing apparatus, special tightly sealed suit

Special precautions:

Not determined or not applicable.

Safety Data Sheet

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Initial preparation date: 03.23.2018

Page 4 of 10

Cleaner Degreaser

SECTION 6: Accidental release measures

Personal precautions, protective equipment and emergency procedures:

- Ensure adequate ventilation
- Ensure air handling systems are operational
- Wear protective eye wear, gloves and clothing

Environmental precautions:

- Should not be released into the environment
- Prevent from reaching drains, sewer or waterway

Methods and material for containment and cleaning up:

- Wear protective eye wear, gloves and clothing
- Absorb with non-combustible liquid-binding material (sand, diatomaceous earth (clay), acid binders, universal binders)
- Dispose of contents / container in accordance with local regulations

Reference to other sections:

Not determined or not applicable.

SECTION 7: Handling and storage

Precautions for safe handling:

- Use only with adequate ventilation.
- Avoid breathing mist or vapor.
- Do not eat, drink, smoke or use personal products when handling chemical substances.

Conditions for safe storage, including any incompatibilities:

- Keep container tightly sealed.
- Protect from freezing and physical damage.
- Store in a cool, well-ventilated area.
- Store in corrosive resistant container with a resistant inner lining.

SECTION 8: Exposure controls/personal protection

Only those substances with limit values have been included below.

Occupational Exposure limit values:

Country (Legal Basis)	Substance	Identifier	Permissible concentration
ACGIH	Potassium hydroxide	1310-58-3	ACGIH TLV C 2.0 mg/m ³
	2-Butoxyethanol	111-76-2	ACGIH TLV TWA: 20 ppm
NIOSH	Potassium hydroxide	1310-58-3	NIOSH REL C 2.0 mg/m ³
	2-Butoxyethanol	111-76-2	NIOSH REL TWA 5 ppm (24 mg/m ³)
United States (OSHA)	2-Butoxyethanol	111-76-2	OSHA PEL TWA 50 ppm (240 mg/m ³)
Australia	2-Butoxyethanol	111-76-2	TWA: 96.9 mg/m ³ (20 ppm) ; STEL: 242 mg/m ³ (50 ppm)
	Potassium hydroxide	1310-58-3	Peak Limitation: 2 mg/m ³

Biological limit values:

No biological exposure limits noted for the ingredient(s).

Information on monitoring procedures:

Monitoring of the concentration of substances in the breathing zone of workers or in the general workplace may be required to confirm compliance with an OEL and adequacy of exposure controls.

Safety Data Sheet

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Initial preparation date: 03.23.2018

Page 5 of 10

Cleaner Degreaser

Biological monitoring may also be appropriate for some substances.

Appropriate engineering controls:

Emergency eye wash fountains and safety showers should be available in the immediate vicinity of use or handling.

Provide exhaust ventilation or other engineering controls to keep the airborne concentrations of vapor and mists below the applicable workplace exposure limits (Occupational Exposure Limits-OELs) indicated above.

Personal protection equipment

Eye and face protection:

Safety goggles or glasses, or appropriate eye protection.

Skin and body protection:

Select glove material impermeable and resistant to the substance.

Wear appropriate clothing to prevent any possibility of skin contact.

Respiratory protection:

If engineering controls do not maintain airborne concentrations below recommended exposure limits (where applicable) or to an acceptable level (in countries where exposure limits have not been established), an approved respirator must be worn.

General hygienic measures:

Avoid contact with skin, eyes and clothing.

Wash hands before breaks and at the end of work.

Wash contaminated clothing before reuse.

SECTION 9: Physical and chemical properties

Information on basic physical and chemical properties

Appearance	Clear Colorless Liquid
Odor	Very Mild
Odor threshold	Not determined or not available.
pH	9.5 - 13.1
Melting point/freezing point	Melting: Approximately 0°C (32°F); Freezing: Approximately 100°C (212°F)
Initial boiling point/range	Not determined or not available.
Flash point (closed cup)	No Flash Point
Evaporation rate	Not determined or not available.
Flammability (solid, gas)	Not determined or not available.
Upper flammability/explosive limit	Not determined or not available.
Lower flammability/explosive limit	Not determined or not available.
Vapor pressure	23 hPa @ 20°C
Vapor density	Not determined or not available.
Density	1.03 g/mL
Relative density	Not determined or not available.
Solubilities	Miscible in water.
Partition coefficient (n-octanol/water)	Not determined or not available.
Auto/Self-ignition temperature	Not determined or not available.
Decomposition temperature	Not determined or not available.
Dynamic viscosity	1 mm ² /s @ 20°C
Kinematic viscosity	Not determined or not available.
Explosive properties	Not determined or not available.

Safety Data Sheet

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Initial preparation date: 03.23.2018

Page 6 of 10

Cleaner Degreaser

Oxidizing properties	Not determined or not available.
-----------------------------	----------------------------------

Other information

Recommended Storage Temperature	40°F - 90°F
Recommended Shelf Life	Unopened, 3 Years
VOC Content	20.9 g/L; 2.04% w/w

SECTION 10: Stability and reactivity

Reactivity:

Does not react under normal conditions of use and storage.

Chemical stability:

Stable under normal conditions of use and storage.

Possibility of hazardous reactions:

None under normal conditions of use and storage.

Conditions to avoid:

None known.

Incompatible materials:

Strong acids (e.g. hydrochloric acid), strong bases (e.g. sodium hydroxide), strong oxidizing agents (e.g. perchloric acid).

Corrosive to: aluminum alloys, copper alloys (e.g. brass and/or bronze), zinc.

Hazardous decomposition products:

Corrosive chemicals; irritating chemicals; toxic chemicals.

SECTION 11: Toxicological information

Acute toxicity

Assessment: Based on available data, the classification criteria are not met.

Product data: No data available.

Substance data:

Name	Route	Result
Potassium hydroxide	oral	LD50 - Rat - 333 mg/kg
Alcohols, C6-12, ethoxylated, liquids	oral	LD50 > 300 to <= 2,000 mg/kg
2-Butoxyethanol	oral	LD50 - Rat - 470 mg/kg
	dermal	LD50 - Rabbit - 220 mg/kg
	inhalation	LC50 - Rat - 450 ppm - 4H

Skin corrosion/irritation

Assessment: Causes severe skin burns and eye damage

Product data:

No data available.

Substance data:

Name	Result
Potassium hydroxide	Corrosive to the skin.
2-Butoxyethanol	Irritating to the skin.

Serious eye damage/irritation

Assessment: Based on available data, the classification criteria are not met.

Safety Data Sheet

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Initial preparation date: 03.23.2018

Page 7 of 10

Cleaner Degreaser

Product data:

No data available.

Substance data:

Name	Result
Alcohols, C6-12, ethoxylated, liquids	Corrosive effect on the eyes.
2-Butoxyethanol	Irritating effect on the eyes.

Respiratory or skin sensitization

Assessment: Based on available data, the classification criteria are not met.

Product data:

No data available.

Substance data: No data available.

Carcinogenicity

Assessment: Suspected of causing cancer

Product data: No data available.

Substance data: No data available.

International Agency for Research on Cancer (IARC): None of the ingredients are listed.

National Toxicology Program (NTP): None of the ingredients are listed.

Germ cell mutagenicity

Assessment: Based on available data, the classification criteria are not met.

Product data:

No data available.

Substance data: No data available.

Reproductive toxicity

Assessment: Based on available data, the classification criteria are not met.

Product data:

No data available.

Substance data: No data available.

Specific target organ toxicity (single exposure)

Assessment: May cause damage to organs

Product data:

No data available.

Substance data: No data available.

Specific target organ toxicity (repeated exposure)

Assessment: Based on available data, the classification criteria are not met.

Product data:

No data available.

Substance data: No data available.

Aspiration toxicity

Assessment: Based on available data, the classification criteria are not met.

Product data:

No data available.

Substance data: No data available.

Information on likely routes of exposure:

No data available.

Symptoms related to the physical, chemical and toxicological characteristics:

No data available.

Safety Data Sheet

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Initial preparation date: 03.23.2018

Page 8 of 10

Cleaner Degreaser

Other information:

No data available.

SECTION 12: Ecological information

Acute (short-term) toxicity

Assessment: Based on available data, the classification criteria are not met.

Product data: No data available.

Substance data: No data available.

Chronic (long-term) toxicity

Product data: No data available.

Substance data: No data available.

Persistence and degradability

Product data: No data available.

Substance data: No data available.

Bioaccumulative potential

Product data: No data available.

Substance data: No data available.

Mobility in soil

Product data: No data available.

Substance data: No data available.

Other adverse effects: No data available.


SECTION 13: Disposal considerations

Disposal methods:

It is the responsibility of the waste generator to properly characterize all waste materials according to applicable regulatory entities

SECTION 14: Transport information

United States Transportation of dangerous goods (49 CFR DOT)

UN number	1814
UN proper shipping name	POTASSIUM HYDROXIDE, SOLUTION
UN transport hazard class(es)	8 
Packing group	III
Environmental hazards	None
Special precautions for user	None
Passenger air/rail	1L
Cargo aircraft only	30L
Stowage category	A

International Maritime Dangerous Goods (IMDG)

UN number	1814
UN proper shipping name	POTASSIUM HYDROXIDE SOLUTION


Safety Data Sheet

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200


Initial preparation date: 03.23.2018

Page 9 of 10

Cleaner Degreaser

UN transport hazard class(es)	8	
Packing group	III	
Environmental hazards	None	
Special precautions for user	None	
EmS number	F-A, S-B	
Stowage category	A	
Excepted quantities	E1	
Limited quantity	5L	

International Air Transport Association Dangerous Goods Regulations (IATA-DGR)

UN number	1814	
UN proper shipping name	POTASSIUM HYDROXIDE SOLUTION	
UN transport hazard class(es)	8	
Packing group	III	
Environmental hazards	None	
Special precautions for user	None	
ERG code	8L	
Excepted quantities	E1	
Passenger and cargo	5L	
Cargo aircraft only	60L	
Limited quantity	1L	

SECTION 15: Regulatory information

United States regulations

Inventory listing (TSCA):

1310-58-3	Potassium hydroxide	Listed
68439-45-2	Alcohols, C6-12, ethoxylated, liquids	Listed
111-76-2	2-Butoxyethanol	Listed

Significant New Use Rule (TSCA Section 5): Not determined.

Export notification under TSCA Section 12(b): Not determined.

SARA Section 302 extremely hazardous substances: Not determined.

SARA Section 313 toxic chemicals: Not determined.

CERCLA:

1310-58-3	Potassium hydroxide	Listed	1,000 lb
-----------	---------------------	--------	----------

RCRA: Not determined.

Section 112(r) of the Clean Air Act (CAA): Not determined.

Massachusetts Right to Know:

1310-58-3	Potassium hydroxide	Listed
111-76-2	2-Butoxyethanol	Listed

New Jersey Right to Know:

Safety Data Sheet

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Initial preparation date: 03.23.2018

Page 10 of 10

Cleaner Degreaser

1310-58-3	Potassium hydroxide	Listed
111-76-2	2-Butoxyethanol	Listed

New York Right to Know:

1310-58-3	Potassium hydroxide	Listed
111-76-2	2-Butoxyethanol	Listed

Pennsylvania Right to Know:

1310-58-3	Potassium hydroxide	Listed
111-76-2	2-Butoxyethanol	Listed

SECTION 16: Other information

Abbreviations and Acronyms: None

Disclaimer:

This product has been classified in accordance with OSHA HCS 2012 guidelines. The information provided in this SDS is correct, to the best of our knowledge, based on information available. The information given is designed only as a guidance for safe handling, use, storage, transportation and disposal and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials, unless specified in the text. The responsibility to provide a safe workplace remains with the user.

NFPA: 3-0-4

HMIS: 3-0-4

Initial preparation date: 03.23.2018

Additional information:

Version 1.1

End of Safety Data Sheet



Safety Data Sheet

acc. to 29 CFR 1910.1200 App D

POR-15 METAL PREP

Version number: GHS 2.0
Replaces version of: 2022-03-28 (GHS 1)

Revision: 2022-10-24

SECTION 1: Identification

1.1 Product identifier

Trade name **POR-15 METAL PREP**
Product code(s) 40201, 40204, 40216, 40255

1.2 Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses General use
Uses advised against Do not use for squirting or spraying. Do not use for products which come into direct contact with the skin.

1.3 Details of the supplier of the safety data sheet

P.O.R. Products
38 Portman Road
New Rochelle NY 10801
United States

Telephone: +1 914-636-0700
e-mail: support@porproducts.com
Website: www.porproducts.com

e-mail (competent person) support@porproducts.com

1.4 Emergency telephone number

Emergency information service 1-800-255-3924
ChemTel Inc.

SECTION 2: Hazard(s) identification

2.1 Classification of the substance or mixture

Classification acc. to OSHA "Hazard Communication Standard" (29 CFR 1910.1200)

Section	Hazard class	Category	Hazard class and category	Hazard statement
A.2	skin corrosion/irritation	1	Skin Corr. 1	H314
A.3	serious eye damage/eye irritation	1	Eye Dam. 1	H318

For full text of abbreviations: see SECTION 16.

The most important adverse physicochemical, human health and environmental effects

Skin corrosion produces an irreversible damage to the skin; namely, visible necrosis through the epidermis and into the dermis.

2.2 Label elements

Labelling acc. to OSHA "Hazard Communication Standard" (29 CFR 1910.1200)

- Signal word danger

POR-15 METAL PREP

Version number: GHS 2.0
Replaces version of: 2022-03-28 (GHS 1)

Revision: 2022-10-24

- Pictograms

GHS05



- Hazard statements

H314 Causes severe skin burns and eye damage.

- Precautionary statements

P101 If medical advice is needed, have product container or label at hand.
 P102 Keep out of reach of children.
 P103 Read label before use.
 P260 Do not breathe dusts or mists.
 P280 Wear eye protection/face protection.
 P301+P330+P331 If swallowed: Rinse mouth. Do NOT induce vomiting.
 P303+P361+P353 If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.
 P304+P340 If inhaled: Remove person to fresh air and keep comfortable for breathing.
 P305+P351+P338 If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
 P310 Immediately call a poison center/doctor.
 P321 Specific treatment (see on this label).
 P363 Wash contaminated clothing before reuse.
 P405 Store locked up.
 P501 Dispose of contents/container to industrial combustion plant.

- Hazardous ingredients for labelling phosphoric acid ... %

2.3 Other hazards

of no significance

SECTION 3: Composition/information on ingredients

3.1 Substances

Not relevant (mixture)

3.2 Mixtures

Description of the mixture

Name of substance	Identifier	Wt%	Classification acc. to GHS
phosphoric acid ... %	CAS No 7664-38-2	10 - < 25	Skin Corr. 1B / H314 Eye Dam. 1 / H318

For full text of abbreviations: see SECTION 16.

POR-15 METAL PREP

Version number: GHS 2.0
Replaces version of: 2022-03-28 (GHS 1)

Revision: 2022-10-24

SECTION 4: First-aid measures

4.1 Description of first-aid measures

General notes

Do not leave affected person unattended. Remove victim out of the danger area. Keep affected person warm, still and covered. Take off immediately all contaminated clothing. In all cases of doubt, or when symptoms persist, seek medical advice. In case of unconsciousness place person in the recovery position. Never give anything by mouth.

Following inhalation

If breathing is irregular or stopped, immediately seek medical assistance and start first aid actions. In case of respiratory tract irritation, consult a physician. Provide fresh air.

Following skin contact

Wash with plenty of soap and water.

Following eye contact

Remove contact lenses, if present and easy to do. Continue rinsing. Irrigate copiously with clean, fresh water for at least 10 minutes, holding the eyelids apart.

Following ingestion

Rinse mouth with water (only if the person is conscious). Do NOT induce vomiting.

4.2 Most important symptoms and effects, both acute and delayed

Symptoms and effects are not known to date.

4.3 Indication of any immediate medical attention and special treatment needed

none

SECTION 5: Fire-fighting measures

5.1 Extinguishing media

Suitable extinguishing media

Water spray, Alcohol resistant foam, BC-powder, Carbon dioxide (CO₂)

Unsuitable extinguishing media

Water jet

5.2 Special hazards arising from the substance or mixture

Hazardous combustion products

Phosphorus oxides (P_xO_y)

5.3 Advice for firefighters

In case of fire and/or explosion do not breathe fumes. Coordinate firefighting measures to the fire surroundings. Do not allow firefighting water to enter drains or water courses. Collect contaminated firefighting water separately. Fight fire with normal precautions from a reasonable distance.

POR-15 METAL PREP

Version number: GHS 2.0
Replaces version of: 2022-03-28 (GHS 1)

Revision: 2022-10-24

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

For non-emergency personnel

Remove persons to safety.

For emergency responders

Wear breathing apparatus if exposed to vapors/dust/aerosols/gases.

6.2 Environmental precautions

Keep away from drains, surface and ground water. Retain contaminated washing water and dispose of it. If substance has entered a water course or sewer, inform the responsible authority.

6.3 Methods and material for containment and cleaning up

Advice on how to contain a spill

Covering of drains

Advice on how to clean up a spill

Wipe up with absorbent material (e.g. cloth, fleece). Collect spillage: sawdust, kieselgur (diatomite), sand, universal binder

Appropriate containment techniques

Use of adsorbent materials.

Other information relating to spills and releases

Place in appropriate containers for disposal. Ventilate affected area.

6.4 Reference to other sections

Hazardous combustion products: see section 5. Personal protective equipment: see section 8. Incompatible materials: see section 10. Disposal considerations: see section 13.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Recommendations

- Measures to prevent fire as well as aerosol and dust generation

Use local and general ventilation. Use only in well-ventilated areas. Never add water to this product.

- Handling of incompatible substances or mixtures

Do not mix with alkali.

- Keep away from

Caustic solutions

Advice on general occupational hygiene

Wash hands after use. Do not eat, drink and smoke in work areas. Remove contaminated clothing and protective equipment before entering eating areas. Never keep food or drink in the vicinity of chemicals. Never place chemicals in containers that are normally used for food or drink. Keep away from food, drink and animal feedingstuffs.

7.2 Conditions for safe storage, including any incompatibilities

POR-15 METAL PREP

Version number: GHS 2.0
Replaces version of: 2022-03-28 (GHS 1)

Revision: 2022-10-24

Control of the effects

Protect against external exposure, such as frost

- Packaging compatibilities

Only packagings which are approved (e.g. acc. to the Dangerous Goods Regulations) may be used.

7.3 Specific end use(s)

See section 16 for a general overview.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational exposure limit values (Workplace Exposure Limits)

Country	Name of agent	CAS No	Identifier	TWA [ppm]	TWA [mg/m ³]	STEL [ppm]	STEL [mg/m ³]	Ceiling-C [ppm]	Ceiling-C [mg/m ³]	Notation	Source
US	phosphoric acid	7664-38-2	PEL (CA)		1		3				Cal/ OSHA PEL
US	phosphoric acid	7664-38-2	REL		1 (10 h)		3				NIOSH REL
US	phosphoric acid	7664-38-2	TLV®		1		3				ACGIH® 2022
US	phosphoric acid	7664-38-2	PEL		1						29 CFR 1910.1000

Notation

Ceiling-C
STEL

TWA

ceiling value is a limit value above which exposure should not occur
short-term exposure limit: a limit value above which exposure should not occur and which is related to a 15-minute period (unless otherwise specified)
time-weighted average (long-term exposure limit): measured or calculated in relation to a reference period of 8 hours time-weighted average (unless otherwise specified)

8.2 Exposure controls

Appropriate engineering controls

General ventilation.

Individual protection measures (personal protective equipment)

Eye/face protection

Wear eye/face protection.

Skin protection

- Hand protection

Wear suitable gloves. Chemical protection gloves are suitable, which are tested according to EN 374. Check leak-tightness/impermeability prior to use. In the case of wanting to use the gloves again, clean them before taking off and air them well. For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves.



Safety Data Sheet

acc. to 29 CFR 1910.1200 App D

POR-15 METAL PREP

Version number: GHS 2.0
Replaces version of: 2022-03-28 (GHS 1)

Revision: 2022-10-24

- Other protection measures

Take recovery periods for skin regeneration. Preventive skin protection (barrier creams/ointments) is recommended. Wash hands thoroughly after handling.

Respiratory protection

In case of inadequate ventilation wear respiratory protection.

Environmental exposure controls

Use appropriate container to avoid environmental contamination. Keep away from drains, surface and ground water.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Appearance

Physical state	liquid
Color	not determined
Particle	not relevant (liquid)
Odor	characteristic

Other safety parameters

pH (value)	0.5 – 1 (acid)
Melting point/freezing point	not determined
Initial boiling point and boiling range	100 °C
Flash point	not determined
Evaporation rate	Not determined
Flammability (solid, gas)	not relevant, (fluid)
Vapor pressure	not determined
Density	10.22 lb/gal
Vapor density	this information is not available

Solubility(ies)

- Water solubility	miscible in any proportion
--------------------	----------------------------

Partition coefficient

- n-octanol/water (log KOW)	this information is not available
-----------------------------	-----------------------------------



Safety Data Sheet

acc. to 29 CFR 1910.1200 App D

POR-15 METAL PREP

Version number: GHS 2.0
Replaces version of: 2022-03-28 (GHS 1)

Revision: 2022-10-24

Auto-ignition temperature	not determined
Viscosity	not determined
Explosive properties	none
Oxidizing properties	none

9.2 Other information

Solid content	17 %
---------------	------

SECTION 10: Stability and reactivity

10.1 Reactivity

Concerning incompatibility: see below "Conditions to avoid" and "Incompatible materials".

10.2 Chemical stability

See below "Conditions to avoid".

10.3 Possibility of hazardous reactions

No known hazardous reactions.

10.4 Conditions to avoid

There are no specific conditions known which have to be avoided.

10.5 Incompatible materials

There is no additional information.

Release of flammable materials with:

Light metals (due to the release of hydrogen in an acid/alkaline medium)

10.6 Hazardous decomposition products

Reasonably anticipated hazardous decomposition products produced as a result of use, storage, spill and heating are not known. Hazardous combustion products: see section 5.

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Test data are not available for the complete mixture.

Classification procedure

The method for classification of the mixture is based on ingredients of the mixture (additivity formula).

Classification acc. to OSHA "Hazard Communication Standard" (29 CFR 1910.1200)

Acute toxicity

Shall not be classified as acutely toxic.

Skin corrosion/irritation

Causes severe skin burns and eye damage.



Safety Data Sheet

acc. to 29 CFR 1910.1200 App D

POR-15 METAL PREP

Version number: GHS 2.0
Replaces version of: 2022-03-28 (GHS 1)

Revision: 2022-10-24

Serious eye damage/eye irritation

Causes serious eye damage.

Respiratory or skin sensitization

Shall not be classified as a respiratory or skin sensitizer.

Germ cell mutagenicity

Shall not be classified as germ cell mutagenic.

Carcinogenicity

Shall not be classified as carcinogenic.

Reproductive toxicity

Shall not be classified as a reproductive toxicant.

Specific target organ toxicity - single exposure

Shall not be classified as a specific target organ toxicant (single exposure).

Specific target organ toxicity - repeated exposure

Shall not be classified as a specific target organ toxicant (repeated exposure).

Aspiration hazard

Shall not be classified as presenting an aspiration hazard.

SECTION 12: Ecological information

12.1 Toxicity

Shall not be classified as hazardous to the aquatic environment.

12.2 Persistence and degradability

Data are not available.

12.3 Bioaccumulative potential

Data are not available.

12.4 Mobility in soil

Data are not available.

12.5 Results of PBT and vPvB assessment

Data are not available.

12.6 Endocrine disrupting properties

Information on this property is not available.

12.7 Other adverse effects

Data are not available.

POR-15 METAL PREP

Version number: GHS 2.0
Replaces version of: 2022-03-28 (GHS 1)

Revision: 2022-10-24

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Sewage disposal-relevant information

Do not empty into drains. Avoid release to the environment. Refer to special instructions/safety data sheets.

Waste treatment of containers/packages

Only packagings which are approved (e.g. acc. to DOT) may be used. Completely emptied packages can be recycled. Handle contaminated packages in the same way as the substance itself.

Remarks

Please consider the relevant national or regional provisions. Waste shall be separated into the categories that can be handled separately by the local or national waste management facilities.

SECTION 14: Transport information

14.1 UN number

DOT	UN 3264
IMDG-Code	UN 3264
ICAO-TI	UN 3264

14.2 UN proper shipping name

DOT	Corrosive liquid, acidic, inorganic, n.o.s.
IMDG-Code	CORROSIVE LIQUID, ACIDIC, INORGANIC, N.O.S.
ICAO-TI	Corrosive liquid, acidic, inorganic, n.o.s.
Technical name (hazardous ingredients)	phosphoric acid ... %

14.3 Transport hazard class(es)

DOT	8
IMDG-Code	8
ICAO-TI	8

14.4 Packing group

DOT	II
IMDG-Code	II
ICAO-TI	II

14.5 Environmental hazards

	hazardous to the aquatic environment
Environmentally hazardous substance (aquatic environment)	trizinc bis(orthophosphate)

14.6 Special precautions for user

There is no additional information.

14.7 Transport in bulk according to IMO instruments

The cargo is not intended to be carried in bulk.



POR-15 METAL PREP

Version number: GHS 2.0
Replaces version of: 2022-03-28 (GHS 1)



Revision: 2022-10-24

Information for each of the UN Model Regulations


Transport of dangerous goods by road or rail (49 CFR US DOT) - Additional information

Particulars in the shipper's declaration	UN3264, Corrosive liquid, acidic, inorganic, n.o.s., (contains: phosphoric acid ... %), 8, II, environmentally hazardous
Reportable quantity (RQ)	41,667 lbs (18,917 kg) (phosphoric acid ... %)
Danger label(s)	8, fish and tree
 	
Environmental hazards	YES (hazardous to the aquatic environment)
Special provisions (SP)	386, B2, IB2, T11, TP2, TP27
ERG No	154

International Maritime Dangerous Goods Code (IMDG) - Additional information

Marine pollutant	YES (hazardous to the aquatic environment) (trizinc bis(orthophosphate))
Danger label(s)	8, fish and tree
 	
Special provisions (SP)	274
Excepted quantities (EQ)	E2
Limited quantities (LQ)	1 L
EmS	F-A, S-B
Stowage category	B
Segregation group	1 - Acids

International Civil Aviation Organization (ICAO-IATA/DGR) - Additional information

Environmental hazards	YES (hazardous to the aquatic environment)
Danger label(s)	8
	
Special provisions (SP)	A3
Excepted quantities (EQ)	E2
Limited quantities (LQ)	0,5 L



Safety Data Sheet

acc. to 29 CFR 1910.1200 App D

POR-15 METAL PREP

Version number: GHS 2.0
Replaces version of: 2022-03-28 (GHS 1)

Revision: 2022-10-24

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations specific for the product in question

National regulations (United States)

Toxic Substance Control Act (TSCA) all ingredients are listed

Superfund Amendment and Reauthorization Act (SARA TITLE III)

- The List of Extremely Hazardous Substances and Their Threshold Planning Quantities (EPCRA Section 302, 304)

none of the ingredients are listed

- Specific Toxic Chemical Listings (EPCRA Section 313)

none of the ingredients are listed

Comprehensive Environmental Response, Compensation, and Liability Act (CERCLA)

- List of Hazardous Substances and Reportable Quantities (CERCLA section 102a) (40 CFR 302.4)

Name of substance	CAS No	Remarks	Statutory code	Final RQ pounds (Kg)
phosphoric acid ... %	7664-38-2		1	5000 (2270)

Legend

1 "1" indicates that the statutory source is section 311(b)(2) of the Clean Water Act

Clean Air Act

none of the ingredients are listed

Right to Know Hazardous Substance List

- Cleaning Product Right to Know Act Substance List (CA-RTK)

Name of substance	CAS No	Functionality	Authoritative Lists
phosphoric acid ... %	7664-38-2		OEHA RELs

- Toxic or Hazardous Substance List (MA-TURA)

Name of substance	CAS No	DEP CODE	PBT / HHS / LHS	PBT / HHS Threshold	De Minimis Concentration Threshold
phosphoric acid ... %	7664-38-2				1.0 %

- Hazardous Substances List (MN-ERTK)

Name of substance	CAS No	References	Remarks
phosphoric acid ... %	7664-38-2	A, O	

Legend

A American Conference of Governmental Industrial Hygienists (ACGIH), "Threshold Limit Values for Chemical Substances and Physical Agents and Biological Exposure Indices for 1992-93", available from ACGIH
O Occupational Safety and Health Administration (OSHA), Safety and Health Standards, Code of Federal Regulations, title 29, part 1910, subpart Z, "Toxic and Hazardous Substances, 1990." General information: Minnesota Department of Labor and Industry, Occupational Safety and Health Division



Safety Data Sheet

acc. to 29 CFR 1910.1200 App D

POR-15 METAL PREP

Version number: GHS 2.0
Replaces version of: 2022-03-28 (GHS 1)

Revision: 2022-10-24

- Hazardous Substance List (NJ-RTK)

Name of substance	CAS No	Remarks	Classifications
phosphoric acid ... %	7664-38-2		CO

Legend

CO Corrosive

- Hazardous Substance List (Chapter 323) (PA-RTK)

Name acc. to inventory	CAS No	Classification
PHOSPHORIC ACID	7664-38-2	E

Legend

E Environmental hazard

- Hazardous Substance List (RI-RTK)

Name of substance	CAS No	References
phosphoric acid ... %	7664-38-2	T, F

Legend

F Flammability (NFPA®)
T Toxicity (ACGIH®)

California Environmental Protection Agency (Cal/EPA): Proposition 65 - Safe Drinking Water and Toxic Enforcement Act of 1987

none of the ingredients are listed

Industry or sector specific available guidance(s)

NPCA-HMIS® III

Hazardous Materials Identification System. American Coatings Association.

Category	Rating	Description
Chronic	/	none
Health	3	major injury likely unless prompt action is taken and medical treatment is given
Flammability	0	material that will not burn under typical fire conditions
Physical hazard	0	material that is normally stable, even under fire conditions, and will not react with water, polymerize, decompose, condense, or self-react. Non-explosive
Personal protection	-	

NFPA® 704

National Fire Protection Association: Standard System for the Identification of the Hazards of Materials for Emergency Response (United States).



Safety Data Sheet

acc. to 29 CFR 1910.1200 App D

POR-15 METAL PREP

Version number: GHS 2.0
Replaces version of: 2022-03-28 (GHS 1)

Revision: 2022-10-24

Category	Degree of hazard	Description
Flammability	0	material that will not burn under typical fire conditions
Health	3	material that, under emergency conditions, can cause serious or permanent injury
Instability	0	material that is normally stable, even under fire conditions
Special hazard		

National inventories

Country	Inventory	Status
US	TSCA	all ingredients are listed

Legend

TSCA Toxic Substance Control Act

15.2 Chemical Safety Assessment

Chemical safety assessments for substances in this mixture were not carried out.

SECTION 16: Other information, including date of preparation or last revision

Key literature references and sources for data

OSHA Hazard Communication Standard (HCS), 29 CFR 1910.1200.

Transport of dangerous goods by road or rail (49 CFR US DOT). International Maritime Dangerous Goods Code (IMDG). Dangerous Goods Regulations (DGR) for the air transport (IATA).

Classification procedure

Physical and chemical properties: The classification is based on tested mixture.

Health hazards, Environmental hazards: The method for classification of the mixture is based on ingredients of the mixture (additivity formula).

Disclaimer

This information is based upon the present state of our knowledge. This SDS has been compiled and is solely intended for this product.

Safety Data Sheet

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Initial preparation date: 04.06.2018

Page 1 of 15

POR-15 Rust Preventive Coating - Gloss Black

SECTION 1: Identification

Product identifier

Product name: POR-15 Rust Preventive Coating - Gloss Black

Product code: 45001; 45004; 45005; 45008; 45032; 45055; 245001;
245004; 245005; 245008; 245032; 245055



Recommended use of the product and restriction on use

Relevant identified uses: Paints and coatings.

Uses advised against: Not determined or not applicable.

Reasons why uses advised against: Not determined or not applicable.

Manufacturer or supplier details

Manufacturer:

United States

P.O.R. Products

38 Portman Road

New Rochelle, NY 10801

914-636-0700

Emergency telephone number:

United States

ChemTel Inc.

+1 800 255 3924

+1 813 248 0585

SECTION 2: Hazard(s) identification

GHS classification:

Flammable liquids, category 3

Eye irritation, category 2A

Skin irritation, category 2

Skin sensitization, category 1

Respiratory sensitization, category 1

Aspiration hazard, category 1

Acute toxicity (inhalation), category 4

Specific target organ toxicity - single exposure, category 3, respiratory irritation

Specific target organ toxicity - single exposure, category 3, central nervous system

Specific target organ toxicity - repeated exposure, category 1

Carcinogenicity, category 2

Label elements

Hazard pictograms:



Signal word: Danger

Hazard statements:

H226 Flammable liquid and vapor

H319 Causes serious eye irritation

Safety Data Sheet

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Initial preparation date: 04.06.2018

Page 2 of 15

POR-15 Rust Preventive Coating - Gloss Black

H315 Causes skin irritation
H317 May cause an allergic skin reaction
H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled
H304 May be fatal if swallowed and enters airways
H332 Harmful if inhaled
H335 May cause respiratory irritation
H336 May cause drowsiness or dizziness
H372 Causes damage to organs through prolonged or repeated exposure
H351 Suspected of causing cancer
H315+H320 Causes skin and eye irritation.
H302+H332 Harmful if swallowed or if inhaled.
H312+H332 Harmful in contact with skin or if inhaled.
H302+H312+H332 Harmful if swallowed, in contact with skin or if inhaled.

Precautionary statements:

P210 Keep away from heat/sparks/open flames/hot surfaces. No smoking
P233 Keep container tightly closed
P240 Ground/bond container and receiving equipment
P241 Use explosion-proof electrical/ventilating/light/equipment
P242 Use only non-sparking tools
P243 Take precautionary measures against static discharge
P280 Wear protective gloves/protective clothing/eye protection/face protection
P264 Wash skin thoroughly after handling
P272 Contaminated work clothing should not be allowed out of the workplace
P285 In case of inadequate ventilation wear respiratory protection
P271 Use only outdoors or in a well-ventilated area
P260 Do not breathe dust/fume/gas/mist/vapors/spray
P270 Do not eat, drink or smoke when using this product
P201 Obtain special instructions before use
P202 Do not handle until all safety precautions have been read and understood
P261 Avoid breathing dust/fume/gas/mist/vapors/spray.
P284 Wear respiratory protection.
P281 Use personal protective equipment as required.
P303+P361+P353 If on skin (or hair): Immediately remove/take off all contaminated clothing. Rinse skin with water/shower
P370+P378 In case of fire: Use agents recommended in section 5 for extinction
P305+P351+P338 If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses if present and easy to do. Continue rinsing
P321 Specific treatment (see supplemental first aid instructions on this label).
P362 Take off contaminated clothing and wash before reuse
P302+P352 If on skin: Wash with soap and water
P333+P313 If skin irritation or a rash occurs: Get medical advice/attention
P331 Do not induce vomiting
P301+P310 If swallowed: Immediately call a poison center or doctor/physician
P304+P340+P312 If inhaled: Remove victim to fresh air and keep at rest in a position comfortable for breathing. Call a poison center or doctor/physician if you feel unwell
P308+P313 If exposed or concerned: Get medical advice/attention
P337+P313 If eye irritation persists get medical advice/attention
P332+P313 If skin irritation occurs: Get medical advice/attention
P362+P364 Take off contaminated clothing and wash it before reuse.
P363 Wash contaminated clothing before reuse
P304+P340 IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.
P304+P341 IF INHALED: If breathing is difficult, remove victim to fresh air and keep at rest in a position

Safety Data Sheet

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Initial preparation date: 04.06.2018

Page 3 of 15

POR-15 Rust Preventive Coating - Gloss Black

comfortable for breathing.

P342+P311 If experiencing respiratory symptoms: Call a POISON CENTER or doctor/physician.

P312 Call a POISON CENTER or doctor/physician if you feel unwell.

P314 Get medical advice/attention if you feel unwell

P405 Store locked up

P403+P233 Store in a well ventilated place. Keep container tightly closed

P403+P235 Store in a well ventilated place. Keep cool.

P501 Dispose of contents and container as instructed in Section 13

Hazards not otherwise classified: None

SECTION 3: Composition/information on ingredients

Identification	Name	Weight %
CAS number: 95-63-6	1, 2, 4-Trimethylbenzene	<6
CAS number: 64742-48-9	Naphtha (petroleum), hydrotreated heavy	15-20
CAS number: 1333-86-4	Carbon Black	<3
CAS number: 1330-20-7	Xylene	<0.5
CAS number: 52747-01-0	Propanol, ((1-methyl-1,2-ethanediyl)bis(oxy))bis-, polymer with 1,1'-methylenebis(4-isocyanatobenzene)	8-18
CAS number: 64742-95-6	Solvent naphtha (petroleum), light arom.	15-20
CAS number: 9016-87-9	Isocyanic acid, polymethylenepolyphenylene ester	1-5
CAS number: 26447-40-5	Methylenediphenyl diisocyanate	2-7
CAS number: 101-68-8	4,4'-Methylenediphenyl diisocyanate	5-12
CAS number: 98-82-8	Cumene	<0.5
CAS number: 67815-87-6	Isocyanic acid, polymethylenepolyphenylene ester, polymer with 1,2-ethanediamine, 2-methyloxirane and 1,2-propanediol	27-47

Additional Information: None

SECTION 4: First aid measures

Description of first aid measures

General notes:

Get medical attention if you feel unwell

After inhalation:

Loosen clothing as necessary and position individual in a comfortable position

Maintain an unobstructed airway

Get medical advice/attention if you feel unwell

Safety Data Sheet

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Initial preparation date: 04.06.2018

Page 4 of 15

POR-15 Rust Preventive Coating - Gloss Black

Take precautions to ensure your own safety
Remove source of exposure or move person to fresh air
Get medical advice if you feel unwell or concerned

After skin contact:

Rinse affected area with soap and water
If symptoms develop or persist, seek medical attention
Take off all contaminated clothing
Gently blot or brush away excess product
Wash with plenty of lukewarm, gently flowing water
Get medical advice if skin irritation occurs or you feel unwell

After eye contact:

Rinse/flush exposed eye(s) gently using water for 15-20 minutes
If symptoms develop or persist, seek medical attention
Rinse eyes cautiously with lukewarm, gently flowing water for several minutes, while holding the eyelids open
Remove contact lenses, if present and easy to do so
Continue rinsing for 15-20 minutes
Get medical advice if eye irritation persists

After swallowing:

Rinse mouth thoroughly
Seek medical attention if irritation, discomfort, or vomiting persists

Most important symptoms and effects, both acute and delayed

Acute symptoms and effects:

May cause breathing difficulty, asthma attack, nausea, allergic reaction

Delayed symptoms and effects:

Not determined or not applicable.

Immediate medical attention and special treatment

Specific treatment:

Not determined or not applicable.

Notes for the doctor:

Contains isocyanates, consult literature for specific treatment

SECTION 5: Firefighting measures

Extinguishing media

Suitable extinguishing media:

Use Water (fog only), dry chemical, chemical foam, carbon dioxide, or alcohol-resistant foam

Unsuitable extinguishing media:

Do not use a water stream as an extinguisher

Specific hazards during fire-fighting:

Thermal decomposition can lead to release of irritating gases and vapors
Vapors can flow to distant ignition sources and flashback
Liquid is volatile and may generate an explosive atmosphere

Special protective equipment for firefighters:

Use typical firefighting equipment, self-contained breathing apparatus, special tightly sealed suit

Special precautions:

Shut off sources of ignition
Carbon monoxide and carbon dioxide may form upon combustion

Safety Data Sheet

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Initial preparation date: 04.06.2018

Page 5 of 15

POR-15 Rust Preventive Coating - Gloss Black

Heating causes a rise in pressure, risk of bursting and combustion

SECTION 6: Accidental release measures

Personal precautions, protective equipment and emergency procedures:

- Ensure adequate ventilation
- Ensure air handling systems are operational
- Wear protective eye wear, gloves and clothing
- Beware of vapors accumulating to form explosive concentrations
- Vapors can accumulate in low areas

Environmental precautions:

- Should not be released into the environment
- Prevent from reaching drains, sewer or waterway

Methods and material for containment and cleaning up:

- Wear protective eye wear, gloves and clothing
- Use spark-proof tools and explosion-proof equipment
- Absorb with non-combustible liquid-binding material (sand, diatomaceous earth (clay), acid binders, universal binders)
- Dispose of contents / container in accordance with local regulations

Reference to other sections:

Not determined or not applicable.

SECTION 7: Handling and storage

Precautions for safe handling:

- Use only with adequate ventilation.
- Avoid breathing mist or vapor.
- Do not eat, drink, smoke or use personal products when handling chemical substances.
- Take precautionary measures against electrostatic discharges.
- Use only non-sparking tools.

Conditions for safe storage, including any incompatibilities:

- Keep container tightly sealed.
- Protect from freezing and physical damage.
- Store in a cool, well-ventilated area.
- Store away from all ignition sources (open flames, hot surfaces, direct sunlight, spark sources).

SECTION 8: Exposure controls/personal protection

Only those substances with limit values have been included below.

Occupational Exposure limit values:

Country (Legal Basis)	Substance	Identifier	Permissible concentration
ACGIH	4,4'-Methylenediphenyl diisocyanate	101-68-8	ACGIH TLV TWA: 0.0050 ppm
	Xylene	1330-20-7	ACGIH TWA: 100.0 ppm
	Xylene	1330-20-7	ACGIH STEL: 150.0 ppm
	Carbon Black	1333-86-4	TLV-TWA 3.0 mg/m ³
	Cumene	98-82-8	ACGIH TLV TWA: 50 ppm
United States (OSHA)	Carbon Black	1333-86-4	OSHA PEL TWA 3.5 mg/m ³
	4,4'-Methylenediphenyl diisocyanate	101-68-8	OSHA C 0.02 ppm, 0.2 mg/m ³
	Xylene	1330-20-7	STEL: 655 mg/m ³ (150 ppm)

Safety Data Sheet

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Initial preparation date: 04.06.2018

Page 6 of 15

POR-15 Rust Preventive Coating - Gloss Black

Country (Legal Basis)	Substance	Identifier	Permissible concentration
	Xylene	1330-20-7	OSHA TWA: 435.0 mg/m ³ (100.0 ppm)
	Cumene	98-82-8	OSHA PEL TWA 50 ppm, 245.0 mg/m ³
	Naphtha (petroleum), hydrotreated heavy	64742-48-9	OSHA Z-1 TWA 500 ppm (2,000 mg/m ³)
NIOSH	4,4'-Methylenediphenyl diisocyanate	101-68-8	NIOSH REL TWA 0.0050 ppm, 0.05 mg/m ³
	4,4'-Methylenediphenyl diisocyanate	101-68-8	NIOSH REL C 0.2 ppm, 0.2 mg/m ³
	Carbon Black	1333-86-4	NIOSH REL TWA 0.1 mg PAHs/m ³ [Carbon black in presence of polycyclic aromatic hydrocarbons (PAHs)]
	Carbon Black	1333-86-4	NIOSH REL TWA 3.5 mg/m ³ Ca
	Xylene	1330-20-7	REL TWA: 435.0 mg/m ³ (100.0 ppm)
	Xylene	1330-20-7	REL ST: 655 mg/m ³ (150 ppm)
	Cumene	98-82-8	NIOSH REL TWA 50 ppm, 245.0 mg/m ³
	1, 2, 4-Trimethylbenzene	95-63-6	NIOSH REL TWA 25 ppm, 125.0 mg/m ³
Australia	Xylene	1330-20-7	TWA: 350 mg/m ³ (80 ppm) ; STEL: 655 mg/m ³ (150 ppm)
	4,4'-Methylenediphenyl diisocyanate	101-68-8	TWA: 0.02 mg/m ³ ; STEL: 0.07 mg/m ³
	Cumene	98-82-8	TWA: 125 mg/m ³ (25 ppm) ; STEL: 375 mg/m ³ (75 ppm)
	Carbon Black	1333-86-4	TWA: 3 mg/m ³

Biological limit values:

No biological exposure limits noted for the ingredient(s).

Information on monitoring procedures:

Monitoring of the concentration of substances in the breathing zone of workers or in the general workplace may be required to confirm compliance with an OEL and adequacy of exposure controls.

Biological monitoring may also be appropriate for some substances.

Appropriate engineering controls:

Emergency eye wash fountains and safety showers should be available in the immediate vicinity of use or handling.

Provide exhaust ventilation or other engineering controls to keep the airborne concentrations of vapor and mists below the applicable workplace exposure limits (Occupational Exposure Limits-OELs) indicated above.

Use explosion-proof ventilation equipment.

Personal protection equipment

Eye and face protection:

Safety goggles or glasses, or appropriate eye protection.

Skin and body protection:

Select glove material impermeable and resistant to the substance.

Wear appropriate clothing to prevent any possibility of skin contact.

Respiratory protection:

If engineering controls do not maintain airborne concentrations below recommended exposure limits

Safety Data Sheet

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Initial preparation date: 04.06.2018

Page 7 of 15

POR-15 Rust Preventive Coating - Gloss Black

(where applicable) or to an acceptable level (in countries where exposure limits have not been established), an approved respirator must be worn.

General hygienic measures:

- Avoid contact with skin, eyes and clothing.
- Wash hands before breaks and at the end of work.
- Wash contaminated clothing before reuse.

SECTION 9: Physical and chemical properties

Information on basic physical and chemical properties

Appearance	Gloss Black Colored Liquid
Odor	Not determined or not available.
Odor threshold	Not determined or not available.
pH	Not determined or not available.
Melting point/freezing point	Not determined or not available.
Initial boiling point/range	>284°F (>140°C)
Flash point (closed cup)	>106°F (>41°C)
Evaporation rate	Not determined or not available.
Flammability (solid, gas)	Not determined or not available.
Upper flammability/explosive limit	Not determined or not available.
Lower flammability/explosive limit	Not determined or not available.
Vapor pressure	38 mmHg
Vapor density	Not determined or not available.
Density	1.04 g/mL
Relative density	Not determined or not available.
Solubilities	Not miscible.
Partition coefficient (n-octanol/water)	Not determined or not available.
Auto/Self-ignition temperature	Not determined or not available.
Decomposition temperature	Not determined or not available.
Dynamic viscosity	200-500 cPs
Kinematic viscosity	Not determined or not available.
Explosive properties	Not determined or not available.
Oxidizing properties	Not determined or not available.

Other information

VOC Content	295 g/L (US EPA Method 24A)
Recommended Storage Temperature	50°F - 95°F
Recommended Shelf Life	3 Years Un-Opened

SECTION 10: Stability and reactivity

Reactivity:

Does not react under normal conditions of use and storage.

Chemical stability:

Stable under normal conditions of use and storage.

Possibility of hazardous reactions:

Safety Data Sheet

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Initial preparation date: 04.06.2018

Page 8 of 15

POR-15 Rust Preventive Coating - Gloss Black

None under normal conditions of use and storage.

Conditions to avoid:

Keep away from heat, sparks and flames.

Incompatible materials:

None known.

Hazardous decomposition products:

None known.

SECTION 11: Toxicological information

Acute toxicity

Assessment: Harmful if inhaled

Product data: No data available.

Substance data:

Name	Route	Result
Isocyanic acid, polymethylenepolyphenylene ester	inhalation	LC50 - Rat - 490 mg/m ³ /4h
Methylenediphenyl diisocyanate	inhalation	LC50 - Rat - 369 mg/cu m/4 h
4,4'-Methylenediphenyl diisocyanate	inhalation	LC50 - Rat - 369 mg/cu m/4 h
Xylene	dermal	LD50 - Rat - > 1,700 mg/kg
	inhalation	LC50 - Rat - 5,000 ppm/4 h
1, 2, 4-Trimethylbenzene	inhalation	LC50 - Rat - 18,000 mg/m ³

Skin corrosion/irritation

Assessment: Causes skin irritation

Product data:

No data available.

Substance data:

Name	Result
Isocyanic acid, polymethylenepolyphenylene ester, polymer with 1,2-ethanediamine, 2-methyloxirane and 1,2-propanediol	Irritating to the skin.
Isocyanic acid, polymethylenepolyphenylene ester	Moderate skin irritation.
Methylenediphenyl diisocyanate	Irritating to the skin.
4,4'-Methylenediphenyl diisocyanate	Irritating to the skin.
Xylene	Irritating to the skin.
1, 2, 4-Trimethylbenzene	Irritating to the skin.
Naphtha (petroleum), hydrotreated heavy	Irritating to the skin.

Safety Data Sheet

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Initial preparation date: 04.06.2018

Page 9 of 15

POR-15 Rust Preventive Coating - Gloss Black

Serious eye damage/irritation

Assessment: Causes serious eye irritation

Product data:

No data available.

Substance data:

Name	Result
Isocyanic acid, polymethylenepolyphenylene ester, polymer with 1,2-ethanediamine, 2-methyloxirane and 1,2-propanediol	Irritating effect on the eyes.
Isocyanic acid, polymethylenepolyphenylene ester	Irritating effect on the eyes.
Methylenediphenyl diisocyanate	Moderate eye irritation.
4,4'-Methylenediphenyl diisocyanate	Moderate eye irritation.
1, 2, 4-Trimethylbenzene	Irritating effect on the eyes.

Respiratory or skin sensitization

Assessment: May cause an allergic skin reaction May cause allergy or asthma symptoms or breathing difficulties if inhaled

Product data:

No data available.

Substance data:

Name	Result
Isocyanic acid, polymethylenepolyphenylene ester, polymer with 1,2-ethanediamine, 2-methyloxirane and 1,2-propanediol	Sensitization possible through skin and respiratory contact.
Isocyanic acid, polymethylenepolyphenylene ester	May cause sensitization by respiratory contact.
Methylenediphenyl diisocyanate	May cause sensitization by inhalation and skin contact.
4,4'-Methylenediphenyl diisocyanate	May cause sensitization by inhalation and skin contact.
Cumene	No skin irritation No eye irritation
Propanol, ((1-methyl-1,2-ethanediyl)bis(oxy))bis-, polymer with 1,1'-methylenebis(4-isocyanatobenzene)	Sensitization possible through respiratory contact.

Carcinogenicity

Assessment: Suspected of causing cancer

Safety Data Sheet

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Initial preparation date: 04.06.2018

Page 10 of 15

POR-15 Rust Preventive Coating - Gloss Black

Product data: No data available.

Substance data:

Name	Species	Result
Methylenediphenyl diisocyanate	Methylenediphenyl diisocyanate	May cause cancer.
4,4'-Methylenediphenyl diisocyanate		May cause cancer.
Carbon Black	Carbon Black	The IARC carcinogenic classification and California Proposition 65 Warning only apply to airborne, unbound particles of respirable size of Carbon Black.
Solvent naphtha (petroleum), light arom.	Solvent naphtha (petroleum), light arom.	Component may cause cancer.

International Agency for Research on Cancer (IARC):

Name	Classification
Isocyanic acid, polymethylenepolyphenylene ester	Group 3 - Not classifiable as to its carcinogenicity to humans
Carbon Black	Group 2B - Possibly carcinogenic to humans
Xylene	Group 3 - Not classifiable as to its carcinogenicity to humans
Cumene	Group 2B - Possibly carcinogenic to humans

National Toxicology Program (NTP): None of the ingredients are listed.

Germ cell mutagenicity

Assessment: Based on available data, the classification criteria are not met.

Product data:

No data available.

Substance data:

Name	Result
Solvent naphtha (petroleum), light arom.	May cause genetic defects.

Reproductive toxicity

Assessment: Based on available data, the classification criteria are not met.

Product data:

No data available.

Substance data: No data available.

Specific target organ toxicity (single exposure)

Assessment: May cause respiratory irritation May cause drowsiness or dizziness

Product data:

No data available.

Substance data:

Safety Data Sheet

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Initial preparation date: 04.06.2018

Page 11 of 15

POR-15 Rust Preventive Coating - Gloss Black

Name	Result
Isocyanic acid, polymethylenepolyphenylene ester, polymer with 1,2-ethanediamine, 2-methyloxirane and 1,2-propanediol	May cause respiratory tract irritation through single or repeated exposure.
Isocyanic acid, polymethylenepolyphenylene ester	Component affects the respiratory system through single and repeated exposure.
Methylenediphenyl diisocyanate	Component affects the respiratory system through single and repeated exposure.
4,4'-Methylenediphenyl diisocyanate	Component affects the respiratory system through single and repeated exposure.
Cumene	Component affects the respiratory system.
1, 2, 4-Trimethylbenzene	Component affects the respiratory system.
Naphtha (petroleum), hydrotreated heavy	Component affects the central nervous system.

Specific target organ toxicity (repeated exposure)

Assessment: Causes damage to organs through prolonged or repeated exposure

Product data:

No data available.

Substance data: No data available.

Aspiration toxicity

Assessment: May be fatal if swallowed and enters airways

Product data:

No data available.

Substance data:

Name	Result
Solvent naphtha (petroleum), light arom.	May be fatal if swallowed and enters airway.
Naphtha (petroleum), hydrotreated heavy	May be fatal if swallowed and enters airway.

Information on likely routes of exposure:

No data available.

Symptoms related to the physical, chemical and toxicological characteristics:

No data available.

Other information:

No data available.

SECTION 12: Ecological information

Acute (short-term) toxicity

Assessment: Based on available data, the classification criteria are not met.

Product data: No data available.

Substance data:

Name	Result
Cumene	EC50 - Daphnia magna - 1.4 mg/L - 24 h
	LC50 - Pimephales promelas - 6.32 mg/L - 96 h

Safety Data Sheet

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Initial preparation date: 04.06.2018

Page 12 of 15

POR-15 Rust Preventive Coating - Gloss Black

Name	Result
1, 2, 4-Trimethylbenzene	LC50 - Pimephales promelas - 7.72 mg/L - 96 h

Chronic (long-term) toxicity

Product data: No data available.

Substance data: No data available.

Persistence and degradability

Product data: No data available.

Substance data: No data available.

Bioaccumulative potential

Product data: No data available.

Substance data: No data available.

Mobility in soil

Product data: No data available.

Substance data: No data available.

Other adverse effects: No data available.


SECTION 13: Disposal considerations

Disposal methods:


It is the responsibility of the waste generator to properly characterize all waste materials according to applicable regulatory entities

SECTION 14: Transport information

United States Transportation of dangerous goods (49 CFR DOT)

UN number	1263
UN proper shipping name	Paint
UN transport hazard class(es)	3 
Packing group	III
Environmental hazards	None
Special precautions for user	None
Passenger air/rail	60L
Cargo aircraft only	220L
Stowage category	A

International Maritime Dangerous Goods (IMDG)

UN number	1263
UN proper shipping name	Paint
UN transport hazard class(es)	3 
Packing group	III
Environmental hazards	None
Special precautions for user	None
EmS number	F-E, S-E
Stowage category	A

Safety Data Sheet

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200


Initial preparation date: 04.06.2018

Page 13 of 15

POR-15 Rust Preventive Coating - Gloss Black

Excepted quantities	E1
Limited quantity	5L

International Air Transport Association Dangerous Goods Regulations (IATA-DGR)

UN number	1263	
UN proper shipping name	Paint	
UN transport hazard class(es)	3	
Packing group	III	
Environmental hazards	None	
Special precautions for user	None	
ERG code	3L	
Excepted quantities	E1	
Passenger and cargo	60L	
Cargo aircraft only	220L	
Limited quantity	10L	

SECTION 15: Regulatory information

United States regulations

Inventory listing (TSCA):

67815-87-6	Isocyanic acid, polymethylenepolyphenylene ester, polymer with 1,2-ethanediamine, 2-methyloxirane and 1,2-propanediol	Listed
9016-87-9	Isocyanic acid, polymethylenepolyphenylene ester	Listed
26447-40-5	Methylenediphenyl diisocyanate	Listed
101-68-8	4,4'-Methylenediphenyl diisocyanate	Listed
1333-86-4	Carbon Black	Listed
1330-20-7	Xylene	Listed
64742-95-6	Solvent naphtha (petroleum), light arom.	Listed
98-82-8	Cumene	Listed
95-63-6	1, 2, 4-Trimethylbenzene	Listed
52747-01-0	Propanol, ((1-methyl-1,2-ethanediyl)bis(oxy))bis-, polymer with 1,1'-methylenebis(4-isocyanatobenzene)	Listed
64742-48-9	Naphtha (petroleum), hydrotreated heavy	Listed

Significant New Use Rule (TSCA Section 5): Not determined.

Export notification under TSCA Section 12(b): Not determined.

SARA Section 302 extremely hazardous substances: Not determined.

SARA Section 313 toxic chemicals:

9016-87-9	Isocyanic acid, polymethylenepolyphenylene ester	Not Listed
101-68-8	4,4'-Methylenediphenyl diisocyanate	Not Listed
1330-20-7	Xylene	Listed
98-82-8	Cumene	Not Listed

Safety Data Sheet

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Initial preparation date: 04.06.2018

Page 14 of 15

POR-15 Rust Preventive Coating - Gloss Black

95-63-6	1, 2, 4-Trimethylbenzene	Not Listed
---------	--------------------------	------------

CERCLA:

1330-20-7	Xylene	Listed	100 lb
-----------	--------	--------	--------

RCRA:

1330-20-7	Xylene	Listed	U239
-----------	--------	--------	------

Section 112(r) of the Clean Air Act (CAA): Not determined.

Massachusetts Right to Know:

101-68-8	4,4'-Methylenediphenyl diisocyanate	Listed
1333-86-4	Carbon Black	Listed
1330-20-7	Xylene	Listed
64742-95-6	Solvent naphtha (petroleum), light arom.	Not Listed
98-82-8	Cumene	Listed
95-63-6	1, 2, 4-Trimethylbenzene	Listed
64742-48-9	Naphtha (petroleum), hydrotreated heavy	Not Listed

New Jersey Right to Know:

9016-87-9	Isocyanic acid, polymethylenepolyphenylene ester	Listed
101-68-8	4,4'-Methylenediphenyl diisocyanate	Listed
1333-86-4	Carbon Black	Listed
1330-20-7	Xylene	Listed
64742-95-6	Solvent naphtha (petroleum), light arom.	Not Listed
98-82-8	Cumene	Listed
95-63-6	1, 2, 4-Trimethylbenzene	Listed
64742-48-9	Naphtha (petroleum), hydrotreated heavy	Not Listed

New York Right to Know:

101-68-8	4,4'-Methylenediphenyl diisocyanate	Listed
1333-86-4	Carbon Black	Not Listed
1330-20-7	Xylene	Listed
64742-95-6	Solvent naphtha (petroleum), light arom.	Not Listed
98-82-8	Cumene	Listed
95-63-6	1, 2, 4-Trimethylbenzene	Listed
64742-48-9	Naphtha (petroleum), hydrotreated heavy	Not Listed

Pennsylvania Right to Know:

101-68-8	4,4'-Methylenediphenyl diisocyanate	Listed
1333-86-4	Carbon Black	Listed
1330-20-7	Xylene	Listed
98-82-8	Cumene	Listed
95-63-6	1, 2, 4-Trimethylbenzene	Listed

Safety Data Sheet

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Initial preparation date: 04.06.2018

Page 15 of 15

POR-15 Rust Preventive Coating - Gloss Black

California Proposition 65:

⚠️WARNING: This product can expose you to chemicals including Bounded Carbon Black and Cumene which are known to the State of California to cause cancer. For more information go to www.P65Warnings.ca.gov.

SECTION 16: Other information

Abbreviations and Acronyms: None

Disclaimer:

This product has been classified in accordance with OSHA HCS 2012 guidelines. The information provided in this SDS is correct, to the best of our knowledge, based on information available. The information given is designed only as a guidance for safe handling, use, storage, transportation and disposal and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials, unless specified in the text. The responsibility to provide a safe workplace remains with the user.

NFPA: 3-2-0

HMIS: 3-2-0

Initial preparation date: 04.06.2018

End of Safety Data Sheet