

# Safety Data Sheet

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Initial preparation date: 09.25.2017

Page 1 of 13

## TOP COAT SAFETY GREEN AEROSOL

### SECTION 1: Identification

#### Product identifier

**Product name:** TOP COAT SAFETY GREEN AEROSOL

**Product code:** 46518



#### Recommended use of the product and restriction on use

**Relevant identified uses:** Aerosol Spray

**Uses advised against:** Not determined or not applicable.

**Reasons why uses advised against:** Not determined or not applicable.

#### Manufacturer or supplier details

##### Manufacturer:

##### United States

P.O.R. Products

38 Portman Road

New Rochelle, NY 10801

914-636-0700

#### Emergency telephone number:

##### United States

##### ChemTel Inc.

+1 800 255 3924

+1 813 248 0585

### SECTION 2: Hazard(s) identification

#### GHS classification:

Flammable aerosols, category 1

Compressed gases

Aspiration hazard, category 1

Acute toxicity (dermal), category 4

Skin irritation, category 2

Eye irritation, category 2A

Acute toxicity (inhalation), category 4

Specific target organ toxicity - single exposure, category 3, central nervous system

Carcinogenicity, category 2

Specific target organ toxicity - repeated exposure, category 2

#### Label elements

##### Hazard pictograms:



**Signal word:** Danger

#### Hazard statements:

H222 Extremely flammable aerosol

H280 Contains gas under pressure; may explode if heated

H304 May be fatal if swallowed and enters airways

H312 Harmful in contact with skin

# Safety Data Sheet

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Initial preparation date: 09.25.2017

Page 2 of 13

## TOP COAT SAFETY GREEN AEROSOL

H315 Causes skin irritation  
H319 Causes serious eye irritation  
H332 Harmful if inhaled  
H336 May cause drowsiness or dizziness  
H351 Suspected of causing cancer  
H373 May cause damage to organs through prolonged or repeated exposure

### Precautionary statements:

P210 Keep away from heat/sparks/open flames/hot surfaces. No smoking  
P211 Do not spray on an open flame or other ignition source  
P251 Pressurized container. Do not pierce or burn, even after use  
P280 Wear protective gloves/protective clothing/eye protection/face protection  
P264 Wash skin thoroughly after handling  
P271 Use only outdoors or in a well-ventilated area  
P201 Obtain special instructions before use  
P202 Do not handle until all safety precautions have been read and understood  
P260 Do not breathe dust/fume/gas/mist/vapors/spray  
P331 Do not induce vomiting  
P301+P310 If swallowed: Immediately call a poison center or doctor/physician  
P302+P352+P312 If on skin: Wash with soap and water. Call a poison center or doctor/physician if you feel unwell  
P321 Specific treatment (see supplemental first aid instructions on this label).  
P362 Take off contaminated clothing and wash before reuse  
P332+P313 If skin irritation occurs: Get medical advice/attention  
P305+P351+P338 If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses if present and easy to do. Continue rinsing  
P304+P340+P312 If inhaled: Remove victim to fresh air and keep at rest in a position comfortable for breathing. Call a poison center or doctor/physician if you feel unwell  
P308+P313 If exposed or concerned: Get medical advice/attention  
P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F  
P410+P403 Protect from sunlight. Store in a well ventilated place  
P405 Store locked up  
P403+P233 Store in a well ventilated place. Keep container tightly closed  
P501 Dispose of contents and container as instructed in Section 13

**Hazards not otherwise classified:** None

## SECTION 3: Composition/information on ingredients

Identification	Name	Weight %
CAS number: 64742-48-9	Aliphatic Petroleum Naphtha	0.1-1
CAS number: 1330-20-7	Xylene	5-8
CAS number: 100-41-4	Ethyl Benzene	1-3
CAS number: 108-65-6	PM Acetate	1-3
CAS number: 123-86-4	n-Butyl acetate	5-16

# Safety Data Sheet

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Initial preparation date: 09.25.2017

Page 3 of 13

## TOP COAT SAFETY GREEN AEROSOL

CAS number: 13463-67-7	Titanium Dioxide	0.1-5
CAS number: 67-64-1	Acetone	35-40
CAS number: 74-98-6	Propane	15-21
CAS number: 106-97-8	Butane	8-10
CAS number: 763-69-9	Ethyl Ester	1-3

**Additional Information:** None

## SECTION 4: First aid measures

### Description of first aid measures

#### General notes:

Not determined or not applicable.

#### After inhalation:

Loosen clothing as necessary and position individual in a comfortable position

Maintain an unobstructed airway

Get medical advice/attention if you feel unwell

Take precautions to ensure your own safety

Remove source of exposure or move person to fresh air

Get medical advice if you feel unwell or concerned

#### After skin contact:

Rinse affected area with soap and water

If symptoms develop or persist, seek medical attention

Take off all contaminated clothing

Gently blot or brush away excess product

Wash with plenty of lukewarm, gently flowing water

Get medical advice if skin irritation occurs or you feel unwell

#### After eye contact:

Rinse/flush exposed eye(s) gently using water for 15-20 minutes

If symptoms develop or persist, seek medical attention

Rinse eyes cautiously with lukewarm, gently flowing water for several minutes, while holding the eyelids open

Remove contact lenses, if present and easy to do so

Continue rinsing for 15-20 minutes

Get medical advice if eye irritation persists

#### After swallowing:

Rinse mouth thoroughly

Seek medical attention if irritation, discomfort, or vomiting persists

### Most important symptoms and effects, both acute and delayed

#### Acute symptoms and effects:

Not determined or not applicable.

#### Delayed symptoms and effects:

Not determined or not applicable.

# Safety Data Sheet

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Initial preparation date: 09.25.2017

Page 4 of 13

## TOP COAT SAFETY GREEN AEROSOL

### Immediate medical attention and special treatment

#### Specific treatment:

Not determined or not applicable.

#### Notes for the doctor:

Not determined or not applicable.

## SECTION 5: Firefighting measures

### Extinguishing media

#### Suitable extinguishing media:

Use Water (fog only), dry chemical, chemical foam, carbon dioxide, or alcohol-resistant foam

#### Unsuitable extinguishing media:

Not determined or not applicable.

### Specific hazards during fire-fighting:

Thermal decomposition can lead to release of irritating gases and vapors

Contents under pressure

In a fire or if heated, a pressure increase will occur and the container may burst or explode

Vapors can flow to distant ignition sources and flashback

Liquid is volatile and may generate an explosive atmosphere

### Special protective equipment for firefighters:

Use typical firefighting equipment, self-contained breathing apparatus, special tightly sealed suit

### Special precautions:

Shut off sources of ignition

Carbon monoxide and carbon dioxide may form upon combustion

Heating causes a rise in pressure, risk of bursting and combustion

## SECTION 6: Accidental release measures

### Personal precautions, protective equipment and emergency procedures:

Ensure adequate ventilation

Ensure air handling systems are operational

Wear protective eye wear, gloves and clothing

Beware of vapors accumulating to form explosive concentrations

Vapors can accumulate in low areas

### Environmental precautions:

Should not be released into the environment

Prevent from reaching drains, sewer or waterway

### Methods and material for containment and cleaning up:

Wear protective eye wear, gloves and clothing

Use spark-proof tools and equipment

Absorb with non-combustible liquid-binding material (sand, diatomaceous earth (clay), acid binders, universal binders)

Dispose of contents / container in accordance with local regulations

### Reference to other sections:

Not determined or not applicable.

## SECTION 7: Handling and storage

### Precautions for safe handling:

Use only with adequate ventilation.

## Safety Data Sheet

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Initial preparation date: 09.25.2017

Page 5 of 13

### TOP COAT SAFETY GREEN AEROSOL

Avoid breathing mist or vapor.

Do not eat, drink, smoke or use personal products when handling chemical substances.

Do not puncture, crush, or incinerate containers, even when empty.

Protect cylinders from physical damage.

#### **Conditions for safe storage, including any incompatibilities:**

Protect from freezing and physical damage.

Protect from direct sunlight.

Store in a cool, well-ventilated area.

Store cylinders upright.

Store away from all ignition sources (open flames, hot surfaces, direct sunlight, spark sources).

### SECTION 8: Exposure controls/personal protection

Only those substances with limit values have been included below.

#### **Occupational Exposure limit values:**

Country (Legal Basis)	Substance	Identifier	Permissible concentration
ACGIH	Butane	106-97-8	ACGIH STEL 1,000 ppm
	Propane	74-98-6	ACGIH TLV TWA 2,500 ppm
	Xylene	1330-20-7	ACGIH TWA: 100.0 ppm
	Xylene	1330-20-7	ACGIH STEL: 150.0 ppm
	Butane	106-97-8	ACGIH TLV TWA 800 ppm
	Acetone	67-64-1	8-hour Exposure Limit (TLV-TWA): 250 ppm
	Acetone	67-64-1	15-minute STEL: 500 ppm
	n-Butyl acetate	123-86-4	ACGIH TWA: 150 ppm
	n-Butyl acetate	123-86-4	ACGIH STEL: 200 ppm
	Titanium Dioxide	13463-67-7	ACGIH TLV TWA: 10 mg/m <sup>3</sup>
	Ethyl Benzene	100-41-4	ACGIH TWA: 20.0 ppm
	Ethyl Benzene	100-41-4	ACGIH STEL: 125.0 ppm
United States (OSHA)	Propane	74-98-6	OSHA PEL TWA 1,000 ppm (1,800 mg/m <sup>3</sup> )
	Xylene	1330-20-7	STEL: 655 mg/m <sup>3</sup> (150 ppm)
	Acetone	67-64-1	TWA: 750 ppm (1800 mg/m <sup>3</sup> )
	Acetone	67-64-1	STEL: 1000 ppm (2400 mg/m <sup>3</sup> )
	n-Butyl acetate	123-86-4	OSHA PEL TWA 150.0 ppm (710.0 mg/m <sup>3</sup> )
	Xylene	1330-20-7	OSHA TWA: 435.0 mg/m <sup>3</sup> (100.0 ppm)
	Titanium Dioxide	13463-67-7	OSHA PEL TWA 15 mg/m <sup>3</sup> (Total dust)
	Ethyl Benzene	100-41-4	OSHA PEL (STEL): 125.0 ppm
	Ethyl Benzene	100-41-4	OSHA TWA 100 ppm 435 mg/m <sup>3</sup>
NIOSH	Propane	74-98-6	NIOSH REL TWA 1,000 ppm (1,800 mg/m <sup>3</sup> )
	Butane	106-97-8	NIOSH REL TWA 800 ppm (1,900 mg/m <sup>3</sup> )

# Safety Data Sheet

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Initial preparation date: 09.25.2017

Page 6 of 13

## TOP COAT SAFETY GREEN AEROSOL

Country (Legal Basis)	Substance	Identifier	Permissible concentration
	Acetone	67-64-1	REL (for up to a 10-hour workday during a 40-hour workweek): 250 ppm (590 mg/m <sup>3</sup> )
	Acetone	67-64-1	IDLH: 2500 ppm
	n-Butyl acetate	123-86-4	NIOSH TWA 150.0 ppm (710 mg/m <sup>3</sup> )
	n-Butyl acetate	123-86-4	NIOSH ST 200.0 ppm (950.0 mg/m <sup>3</sup> )
	Xylene	1330-20-7	REL TWA: 435.0 mg/m <sup>3</sup> (100.0 ppm)
	Xylene	1330-20-7	REL ST: 655 mg/m <sup>3</sup> (150 ppm)
	Titanium Dioxide	13463-67-7	IDLH: 5,000 mg/m <sup>3</sup>
	Ethyl Benzene	100-41-4	NIOSH TWA 100.0 ppm 435.0 mg/m <sup>3</sup>
	Ethyl Benzene	100-41-4	NIOSH ST 125.0 ppm 545.0 mg/m <sup>3</sup>
WEEL	PM Acetate	108-65-6	WEEL TWA 50.0 ppm

### Biological limit values:

No biological exposure limits noted for the ingredient(s).

### Information on monitoring procedures:

Monitoring of the concentration of substances in the breathing zone of workers or in the general workplace may be required to confirm compliance with an OEL and adequacy of exposure controls.

Biological monitoring may also be appropriate for some substances.

### Appropriate engineering controls:

Emergency eye wash fountains and safety showers should be available in the immediate vicinity of use or handling.

Provide exhaust ventilation or other engineering controls to keep the airborne concentrations of vapor and mists below the applicable workplace exposure limits (Occupational Exposure Limits-OELs) indicated above. Use explosion-proof ventilation equipment.

### Personal protection equipment

#### Eye and face protection:

Safety goggles or glasses, or appropriate eye protection.

#### Skin and body protection:

Select glove material impermeable and resistant to the substance.

Wear appropriate clothing to prevent any possibility of skin contact.

#### Respiratory protection:

If engineering controls do not maintain airborne concentrations below recommended exposure limits (where applicable) or to an acceptable level (in countries where exposure limits have not been established), an approved respirator must be worn.

### General hygienic measures:

Avoid contact with skin, eyes and clothing.

Wash hands before breaks and at the end of work.

Wash contaminated clothing before reuse.

## SECTION 9: Physical and chemical properties

### Information on basic physical and chemical properties

Appearance	Aerosol - Pressurized Liquid
------------	------------------------------

# Safety Data Sheet

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Initial preparation date: 09.25.2017

Page 7 of 13

## TOP COAT SAFETY GREEN AEROSOL

<b>Odor</b>	Solvent Odor
<b>Odor threshold</b>	Not determined or not available.
<b>pH</b>	Not determined or not available.
<b>Melting point/freezing point</b>	Not determined or not available.
<b>Initial boiling point/range</b>	Not determined or not available.
<b>Flash point (closed cup)</b>	Less than -18 degrees C (less than -0.4 degrees F), c.c.
<b>Evaporation rate</b>	Faster than ether
<b>Flammability (solid, gas)</b>	Not determined or not available.
<b>Upper flammability/explosive limit</b>	Not determined or not available.
<b>Lower flammability/explosive limit</b>	Not determined or not available.
<b>Vapor pressure</b>	Not determined or not available.
<b>Vapor density</b>	Not determined or not available.
<b>Density</b>	Not determined or not available.
<b>Relative density</b>	0.776
<b>Solubilities</b>	Negligible.
<b>Partition coefficient (n-octanol/water)</b>	Not determined or not available.
<b>Auto/Self-ignition temperature</b>	Not determined or not available.
<b>Decomposition temperature</b>	Not determined or not available.
<b>Dynamic viscosity</b>	Not determined or not available.
<b>Kinematic viscosity</b>	Not determined or not available.
<b>Explosive properties</b>	Not determined or not available.
<b>Oxidizing properties</b>	Not determined or not available.

### Other information

<b>VOC % by weight</b>	46.64
<b>HAPS PERCENT BY WEIGHT</b>	8.43
<b>MIR NUMBER (EPA AND CA)</b>	1.058

## SECTION 10: Stability and reactivity

### Reactivity:

Does not react under normal conditions of use and storage.

### Chemical stability:

Stable under normal conditions of use and storage.

### Possibility of hazardous reactions:

None under normal conditions of use and storage.

### Conditions to avoid:

Keep away from heat, sparks and flames.

### Incompatible materials:

Strong oxidizing agents.

### Hazardous decomposition products:

CO, CO<sub>2</sub> - by fire.

## SECTION 11: Toxicological information

### Acute toxicity

**Assessment:** Harmful in contact with skin Harmful if inhaled

# Safety Data Sheet

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Initial preparation date: 09.25.2017

Page 8 of 13

## TOP COAT SAFETY GREEN AEROSOL

**Product data:** No data available.

**Substance data:**

Name	Route	Result
Xylene	dermal	LD50 - Rat - > 1,700 mg/kg
	inhalation	LC50 - Rat - 5,000 ppm/4 h
Ethyl Benzene	inhalation	LCLo - Rat - 4,000 ppm/4 h
Ethyl Ester	oral	LD50 Rat male >5,000 mg/kg
	dermal	LD50 Rabbit male 4,080 mg/kg

### Skin corrosion/irritation

**Assessment:** Causes skin irritation

**Product data:**

No data available.

**Substance data:**

Name	Result
Xylene	Irritating to the skin.
Aliphatic Petroleum Naphtha	Irritating to the skin.

### Serious eye damage/irritation

**Assessment:** Causes serious eye irritation

**Product data:**

No data available.

**Substance data:**

Name	Result
Acetone	Causes serious eye irritation.

### Respiratory or skin sensitization

**Assessment:** Based on available data, the classification criteria are not met.

**Product data:**

No data available.

**Substance data:** No data available.

### Carcinogenicity

**Assessment:** Suspected of causing cancer

**Product data:** No data available.

**Substance data:**

Name	Species	Result
Titanium Dioxide	Titanium Dioxide	Airborne, unbound particles of respirable size are known to cause cancer.

### International Agency for Research on Cancer (IARC):

Name	Classification
Xylene	Group 3 - Not classifiable as to its carcinogenicity to humans
Titanium Dioxide	Group 3 - Not classifiable as to its carcinogenicity to humans
Ethyl Benzene	Group 2B - Possibly carcinogenic to humans

**National Toxicology Program (NTP):** None of the ingredients are listed.

### Germ cell mutagenicity

**Assessment:** Based on available data, the classification criteria are not met.

# Safety Data Sheet

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Initial preparation date: 09.25.2017

Page 9 of 13

## TOP COAT SAFETY GREEN AEROSOL

### Product data:

No data available.

**Substance data:** No data available.

### Reproductive toxicity

**Assessment:** Based on available data, the classification criteria are not met.

### Product data:

No data available.

**Substance data:** No data available.

### Specific target organ toxicity (single exposure)

**Assessment:** May cause drowsiness or dizziness

### Product data:

No data available.

### Substance data:

Name	Result
Acetone	Specific Target Organ Toxicity, Single Exposure - May cause drowsiness or dizziness.
n-Butyl acetate	SE May cause drowsiness or dizziness. - Central nervous system
Ethyl Benzene	Repeated exposure damages the hearing organs.
Aliphatic Petroleum Naphtha	Component affects the central nervous system.

### Specific target organ toxicity (repeated exposure)

**Assessment:** May cause damage to organs through prolonged or repeated exposure

### Product data:

No data available.

**Substance data:** No data available.

### Aspiration toxicity

**Assessment:** May be fatal if swallowed and enters airways

### Product data:

No data available.

### Substance data:

Name	Result
Ethyl Benzene	May be fatal if swallowed and enters airway.
Aliphatic Petroleum Naphtha	May be fatal if swallowed and enters airway.

### Information on likely routes of exposure:

No data available.

### Symptoms related to the physical, chemical and toxicological characteristics:

No data available.

### Other information:

No data available.

## SECTION 12: Ecological information

### Acute (short-term) toxicity

**Assessment:** Based on available data, the classification criteria are not met.

**Product data:** No data available.

**Substance data:**

# Safety Data Sheet

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Initial preparation date: 09.25.2017

Page 10 of 13

## TOP COAT SAFETY GREEN AEROSOL

Name	Result
Ethyl Ester	static test LC50 - Pimephales promelas (fathead minnow) - 55.3 mg/l - 96 h
	Immobilization EC50 - Daphnia magna (Water flea) - 785 mg/l - 48 h

### Chronic (long-term) toxicity

**Product data:** No data available.

**Substance data:** No data available.

### Persistence and degradability

**Product data:** No data available.

**Substance data:** No data available.

### Bioaccumulative potential

**Product data:** No data available.

**Substance data:** No data available.

### Mobility in soil

**Product data:** No data available.

**Substance data:** No data available.

**Other adverse effects:** No data available.


## SECTION 13: Disposal considerations

### Disposal methods:


It is the responsibility of the waste generator to properly characterize all waste materials according to applicable regulatory entities

## SECTION 14: Transport information

### United States Transportation of dangerous goods (49 CFR DOT)

UN number	1950
UN proper shipping name	Aerosols, flammable, Limited Quantity
UN transport hazard class(es)	2.1 
Packing group	None
Environmental hazards	None
Special precautions for user	None
Passenger air/rail	75 kg
Cargo aircraft only	150 kg

### International Maritime Dangerous Goods (IMDG)

UN number	1950
UN proper shipping name	Aerosols, flammable, Limited Quantity
UN transport hazard class(es)	2.1 
Packing group	None
Environmental hazards	None
Special precautions for user	None
EmS number	F-D, S-U

# Safety Data Sheet

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200


Initial preparation date: 09.25.2017

Page 11 of 13

## TOP COAT SAFETY GREEN AEROSOL

<b>Stowage category</b>	For AEROSOLS with a maximum capacity of 1 litre: Category A. Segregation as for class 9 but "Separated from" class 1 except division 1.4. For AEROSOLS with a capacity above 1 litre: Category B. Segregation as for the appropriate sub-division of class 2. For WASTE AEROSOLS: Category C. Clear of living quarters. Segregation as for the appropriate sub-division of class 2.
<b>Excepted quantities</b>	E0

### International Air Transport Association Dangerous Goods Regulations (IATA-DGR)

<b>UN number</b>	1950
<b>UN proper shipping name</b>	Aerosols, flammable
<b>UN transport hazard class(es)</b>	2.1 
<b>Packing group</b>	None
<b>Environmental hazards</b>	None
<b>Special precautions for user</b>	None
<b>ERG code</b>	10L
<b>Excepted quantities</b>	E0
<b>Passenger and cargo</b>	75 kg
<b>Cargo aircraft only</b>	150 kg
<b>Limited quantity</b>	30 kg G

## SECTION 15: Regulatory information

### United States regulations

#### Inventory listing (TSCA):

67-64-1	Acetone	Listed
74-98-6	Propane	Listed
123-86-4	n-Butyl acetate	Listed
106-97-8	Butane	Listed
1330-20-7	Xylene	Listed
13463-67-7	Titanium Dioxide	Listed
100-41-4	Ethyl Benzene	Listed
763-69-9	Ethyl Ester	Listed
64742-48-9	Aliphatic Petroleum Naphtha	Listed
108-65-6	PM Acetate	Listed

**Significant New Use Rule (TSCA Section 5):** Not determined.

**Export notification under TSCA Section 12(b):** Not determined.

**SARA Section 302 extremely hazardous substances:** Not determined.

#### SARA Section 313 toxic chemicals:

67-64-1	Acetone	Not Listed
1330-20-7	Xylene	Listed
100-41-4	Ethyl Benzene	Listed

#### CERCLA:

## Safety Data Sheet

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Initial preparation date: 09.25.2017

Page 12 of 13

### TOP COAT SAFETY GREEN AEROSOL

67-64-1	Acetone	Listed	5,000
123-86-4	n-Butyl acetate	Listed	5,000 lb
1330-20-7	Xylene	Listed	100 lb
100-41-4	Ethyl Benzene	Listed	1,000 lb

**RCRA:**

67-64-1	Acetone	Listed	U002
1330-20-7	Xylene	Listed	U239

**Section 112(r) of the Clean Air Act (CAA):**

74-98-6	Propane	Listed
106-97-8	Butane	Listed

**Massachusetts Right to Know:**

67-64-1	Acetone	Listed
74-98-6	Propane	Listed
123-86-4	n-Butyl acetate	Listed
106-97-8	Butane	Listed
1330-20-7	Xylene	Listed
13463-67-7	Titanium Dioxide	Listed
100-41-4	Ethyl Benzene	Listed
763-69-9	Ethyl Ester	Not Listed
64742-48-9	Aliphatic Petroleum Naphtha	Not Listed
108-65-6	PM Acetate	Not Listed

**New Jersey Right to Know:**

67-64-1	Acetone	Listed
74-98-6	Propane	Listed
123-86-4	n-Butyl acetate	Not Listed
106-97-8	Butane	Listed
1330-20-7	Xylene	Listed
13463-67-7	Titanium Dioxide	Listed
100-41-4	Ethyl Benzene	Listed
763-69-9	Ethyl Ester	Not Listed
64742-48-9	Aliphatic Petroleum Naphtha	Not Listed
108-65-6	PM Acetate	Not Listed

**New York Right to Know:**

67-64-1	Acetone	Listed
74-98-6	Propane	Listed
123-86-4	n-Butyl acetate	Listed
106-97-8	Butane	Listed
1330-20-7	Xylene	Listed

# Safety Data Sheet

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Initial preparation date: 09.25.2017

Page 13 of 13

## TOP COAT SAFETY GREEN AEROSOL

13463-67-7	Titanium Dioxide	Listed
100-41-4	Ethyl Benzene	Listed
763-69-9	Ethyl Ester	Not Listed
64742-48-9	Aliphatic Petroleum Naphtha	Not Listed
108-65-6	PM Acetate	Not Listed

### Pennsylvania Right to Know:

67-64-1	Acetone	Listed
74-98-6	Propane	Listed
123-86-4	n-Butyl acetate	Listed
106-97-8	Butane	Listed
1330-20-7	Xylene	Listed
13463-67-7	Titanium Dioxide	Listed
100-41-4	Ethyl Benzene	Listed
763-69-9	Ethyl Ester	Not Listed
64742-48-9	Aliphatic Petroleum Naphtha	Not Listed
108-65-6	PM Acetate	Not Listed

### California Proposition 65:

**⚠️WARNING:** This product can expose you to chemicals including Titanium Dioxide, Ethyl Benzene and Ethyl 3-ethoxypropionate which are known to the State of California to cause cancer. For more information go to [www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov).

## SECTION 16: Other information

**Abbreviations and Acronyms:** None

### Disclaimer:

This product has been classified in accordance with OSHA HCS 2012 guidelines. The information provided in this SDS is correct, to the best of our knowledge, based on information available. The information given is designed only as a guidance for safe handling, use, storage, transportation and disposal and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials, unless specified in the text. The responsibility to provide a safe workplace remains with the user.

**NFPA:** 3-4-3

**HMIS:** 3-4-3

**Initial preparation date:** 09.25.2017

**End of Safety Data Sheet**