

## 1 Identification

- **Product identifier**
- **Trade name:** 39977 Panel Vibration Control Material
- **Article number:** 39977
- **Application of the substance / the mixture** Sealant
- **Details of the supplier of the safety data sheet**
- **Manufacturer/Supplier:**  
SEM Products Inc.  
1685 Overview Drive  
Rock Hill, SC 29730  
803 207 8225
- **Information department:**  
cust\_care@semproducts.com : SEM Products, Inc. 1685 Overview Dr. Rock Hill, SC 29730 : phone 1-800-831-1122, M - TH 7am - 4pm EDT
- **Emergency telephone number:** CHEMTREC 1-800-424-9300

## 2 Hazard(s) identification

- **Classification of the substance or mixture**



GHS08 Health hazard

Resp. Sens. 1 H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled.

Carc. 2 H351 Suspected of causing cancer.

Repr. 2 H361 Suspected of damaging fertility or the unborn child.



GHS05 Corrosion

Skin Corr. 1B H314 Causes severe skin burns and eye damage.

Eye Dam. 1 H318 Causes serious eye damage.



GHS07

Acute Tox. 4 H312 Harmful in contact with skin.

Skin Sens. 1 H317 May cause an allergic skin reaction.

STOT SE 3 H335 May cause respiratory irritation.

- **Label elements**
- **GHS label elements** The product is classified and labeled according to the Globally Harmonized System (GHS).
- **Hazard pictograms**



GHS05



GHS07



GHS08

- **Signal word** Danger

Trade name: 39977 Panel Vibration Control Material

(Contd. of page 1)

· **Hazard-determining components of labeling:**

ALIPHATIC AMINE (PROPRIETARY)

nonylphenol

2-piperazin-1-ylethylamine

CASTOR OIL GLYCIDAL ETHER

· **Hazard statements**

H312 Harmful in contact with skin.

H314 Causes severe skin burns and eye damage.

H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled.

H317 May cause an allergic skin reaction.

H351 Suspected of causing cancer.

H361 Suspected of damaging fertility or the unborn child.

H335 May cause respiratory irritation.

· **Precautionary statements**

P260 Do not breathe dusts or mists.

P284 [In case of inadequate ventilation] wear respiratory protection.

P280 Wear protective gloves / protective clothing.

P280 Wear eye protection / face protection.

P264 Wash thoroughly after handling.

P271 Use only outdoors or in a well-ventilated area.

P272 Contaminated work clothing must not be allowed out of the workplace.

P201 Obtain special instructions before use.

P202 Do not handle until all safety precautions have been read and understood.

P303+P361+P353 If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.

P305+P351+P338 If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P310 Immediately call a POISON CENTER/doctor.

P321 Specific treatment (see on this label).

P342+P311 If experiencing respiratory symptoms: Call a POISON CENTER/doctor.

P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.

P363 Wash contaminated clothing before reuse.

P308+P313 IF exposed or concerned: Get medical advice/attention.

P333+P313 If skin irritation or rash occurs: Get medical advice/attention.

P301+P330+P331 If swallowed: Rinse mouth. Do NOT induce vomiting.

P362+P364 Take off contaminated clothing and wash it before reuse.

P405 Store locked up.

P403+P233 Store in a well-ventilated place. Keep container tightly closed.

P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

· **Classification system:**

· **NFPA ratings (scale 0 - 4)**



Health = 3

Fire = 1

Reactivity = 0

· **HMIS-ratings (scale 0 - 4)**



Health = \*3

Fire = 1

Reactivity = 0

(Contd. on page 3)



Trade name: 39977 Panel Vibration Control Material

(Contd. of page 2)

- **Other hazards**
- **Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.

### 3 Composition/information on ingredients

- **Chemical characterization: Mixtures**
- **Description:**  
Mixture: consisting of the following components.  
Weight percentages

· **Dangerous components:**

	EPOXY RESIN MODIFIER	13 - 30%
	ALIPHATIC AMINE (PROPRIETARY)	13 - 30%
74398-71-3	CASTOR OIL GLYCIDAL ETHER	10 -13%
	Mercaptan Terminated Polymer NJTS 800938 5952	7 - 10%
140-31-8	2-piperazin-1-ylethylamine	7 - 10%
25068-38-6	bisphenolA(chloro)oxirane polymer	7 - 10%
67762-90-7	FUMED SILICA	5 - 7%
25154-52-3	nonylphenol	5 - 7%
	Amine proprietary	
90-72-2	2,4,6-tris(dimethylaminomethyl)phenol	1.5 - 5%
1333-86-4	Carbon black	≤1%

### 4 First-aid measures

- **Description of first aid measures**
- **General information:**  
Immediately remove any clothing soiled by the product.  
Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.
- **After inhalation:**  
Supply fresh air and to be sure call for a doctor.  
In case of unconsciousness place patient stably in side position for transportation.
- **After skin contact:** Immediately wash with water and soap and rinse thoroughly.
- **After eye contact:** Rinse opened eye for several minutes under running water. Then consult a doctor.
- **After swallowing:** Drink copious amounts of water and provide fresh air. Immediately call a doctor.
- **Information for doctor:**
- **Most important symptoms and effects, both acute and delayed** No further relevant information available.
- **Indication of any immediate medical attention and special treatment needed**  
No further relevant information available.

### 5 Fire-fighting measures

- **Extinguishing media**
- **Suitable extinguishing agents:** Use fire fighting measures that suit the environment.

(Contd. on page 4)



Trade name: 39977 Panel Vibration Control Material

(Contd. of page 3)

- **Special hazards arising from the substance or mixture**  
During heating or in case of fire poisonous gases are produced.
- **Advice for firefighters**
- **Protective equipment:** Mouth respiratory protective device.

## 6 Accidental release measures

- **Personal precautions, protective equipment and emergency procedures**  
Mount respiratory protective device.  
Wear protective equipment. Keep unprotected persons away.
- **Environmental precautions:** Do not allow to enter sewers/ surface or ground water.
- **Methods and material for containment and cleaning up:**  
Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).  
Use neutralizing agent.  
Dispose contaminated material as waste according to item 13.  
Ensure adequate ventilation.
- **Reference to other sections**  
See Section 7 for information on safe handling.  
See Section 8 for information on personal protection equipment.  
See Section 13 for disposal information.

## 7 Handling and storage

- **Handling:**
- **Precautions for safe handling**  
No special measures required.  
Ensure good ventilation/exhaustion at the workplace.  
Open and handle receptacle with care.  
Prevent formation of aerosols.
- **Information about protection against explosions and fires:** Keep respiratory protective device available.
- **Conditions for safe storage, including any incompatibilities**
- **Storage:**
- **Requirements to be met by storerooms and receptacles:** No special requirements.
- **Information about storage in one common storage facility:** Not required.
- **Further information about storage conditions:** Keep receptacle tightly sealed.
- **Specific end use(s)** No further relevant information available.

## 8 Exposure controls/personal protection

- **Additional information about design of technical systems:** No further data; see item 7.
- **Control parameters**
- **Components with limit values that require monitoring at the workplace:**  
The product does not contain any relevant quantities of materials with critical values that have to be monitored at the workplace.
- **Additional information:** The lists that were valid during the creation were used as basis.

(Contd. on page 5)

Trade name: 39977 Panel Vibration Control Material

(Contd. of page 4)

· **Exposure controls**

· **Personal protective equipment:**

· **General protective and hygienic measures:**

- Keep away from foodstuffs, beverages and feed.
- Immediately remove all soiled and contaminated clothing.
- Wash hands before breaks and at the end of work.
- Store protective clothing separately.
- Avoid contact with the eyes.
- Avoid contact with the eyes and skin.

· **Breathing equipment:**

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use respiratory protective device that is independent of circulating air.

· **Protection of hands:**

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.  
Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

· **Material of gloves**

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· **Penetration time of glove material**

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· **Eye protection:**



Tightly sealed goggles

**9 Physical and chemical properties**

· **Information on basic physical and chemical properties**

· **General Information**

· **Appearance:**

- Form:** Liquid
- Color:** According to product specification
- **Odor:** Characteristic
- **Odor threshold:** Not determined.

· **pH-value:** Not determined.

· **Change in condition**

- Melting point/Melting range:** Undetermined.
- Boiling point/Boiling range:** 220 °C

(Contd. on page 6)



Trade name: 39977 Panel Vibration Control Material

(Contd. of page 5)

· <b>Flash point:</b>	257 °C
· <b>Flammability (solid, gaseous):</b>	Not applicable.
· <b>Ignition temperature:</b>	315 °C
· <b>Decomposition temperature:</b>	Not determined.
· <b>Auto igniting:</b>	Product is not selfigniting.
· <b>Danger of explosion:</b>	Product does not present an explosion hazard. In use, may form flammable/explosive vapour-air mixture.
· <b>Explosion limits:</b>	
<b>Lower:</b>	Not determined.
<b>Upper:</b>	Not determined.
· <b>Vapor pressure:</b>	Not determined.
· <b>Density at 20 °C:</b>	1.12065 g/cm <sup>3</sup>
· <b>Relative density</b>	Not determined.
· <b>Vapor density</b>	Not determined.
· <b>Evaporation rate</b>	Not determined.
· <b>Solubility in / Miscibility with</b>	
<b>Water:</b>	Not miscible or difficult to mix.
· <b>Partition coefficient (n-octanol/water):</b>	Not determined.
· <b>Viscosity:</b>	
<b>Dynamic:</b>	Not determined.
<b>Kinematic:</b>	Not determined.
· <b>Solvent content:</b>	
<b>Organic solvents:</b>	0.0 %
<b>Solids content:</b>	99.6 %
· <b>Other information</b>	No further relevant information available.

**10 Stability and reactivity**

- **Reactivity** No further relevant information available.
- **Chemical stability**
- **Thermal decomposition / conditions to be avoided:** No decomposition if used according to specifications.
- **Possibility of hazardous reactions** No dangerous reactions known.
- **Conditions to avoid** No further relevant information available.
- **Incompatible materials:** No further relevant information available.
- **Hazardous decomposition products:** No dangerous decomposition products known.

USA

(Contd. on page 7)



Trade name: 39977 Panel Vibration Control Material

(Contd. of page 6)

**11 Toxicological information**

- Information on toxicological effects
- Acute toxicity:

· LD/LC50 values that are relevant for classification:

**140-31-8 2-piperazin-1-ylethylamine**

Oral	LD50	2140 mg/kg (rat)
------	------	------------------

Dermal	LD50	880 mg/kg (rabbit)
--------	------	--------------------

**25154-52-3 nonylphenol**

Oral	LD50	1620 mg/kg (rat)
------	------	------------------

· Primary irritant effect:

· on the skin: Caustic effect on skin and mucous membranes.

· on the eye:

Strong caustic effect.

Strong irritant with the danger of severe eye injury.

· Sensitization:

Sensitization possible through inhalation.

Sensitization possible through skin contact.

· Additional toxicological information:

The product shows the following dangers according to internally approved calculation methods for preparations:

Harmful

Corrosive

Irritant

Swallowing will lead to a strong caustic effect on mouth and throat and to the danger of perforation of esophagus and stomach.

· Carcinogenic categories

· IARC (International Agency for Research on Cancer)

1333-86-4	Carbon black	2B
-----------	--------------	----

106-89-8	1-chloro-2,3-epoxypropane	2A
----------	---------------------------	----

· NTP (National Toxicology Program)

106-89-8	1-chloro-2,3-epoxypropane	R
----------	---------------------------	---

· OSHA-Ca (Occupational Safety & Health Administration)

None of the ingredients is listed.

**12 Ecological information**

· Toxicity

· Aquatic toxicity: No further relevant information available.

· Persistence and degradability No further relevant information available.

· Behavior in environmental systems:

· Bioaccumulative potential No further relevant information available.

· Mobility in soil No further relevant information available.

· Additional ecological information:

· General notes:

Water hazard class 3 (Self-assessment): extremely hazardous for water

Do not allow product to reach ground water, water course or sewage system, even in small quantities.

Must not reach bodies of water or drainage ditch undiluted or unneutralized.

(Contd. on page 8)

Trade name: 39977 Panel Vibration Control Material




(Contd. of page 7)

- Danger to drinking water if even extremely small quantities leak into the ground.
- **Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.
- **Other adverse effects** No further relevant information available.

### 13 Disposal considerations

- **Waste treatment methods**
- **Recommendation:**  
Must not be disposed of together with household garbage. Do not allow product to reach sewage system.
- **Uncleaned packagings:**
- **Recommendation:** Disposal must be made according to official regulations.

### 14 Transport information

· <b>UN-Number</b>	
· <b>DOT, ADR, IMDG, IATA</b>	UN3265
· <b>UN proper shipping name</b>	
· <b>DOT, IATA</b>	Corrosive liquid, acidic, organic, n.o.s. (nonylphenol)
· <b>ADR</b>	3265 Corrosive liquid, acidic, organic, n.o.s. (nonylphenol), ENVIRONMENTALLY HAZARDOUS
· <b>IMDG</b>	CORROSIVE LIQUID, ACIDIC, ORGANIC, N.O.S. (nonylphenol)
· <b>Transport hazard class(es)</b>	
· <b>DOT</b>	
	
· <b>Class</b>	8 Corrosive substances
· <b>Label</b>	8
· <b>ADR, IMDG</b>	
	
· <b>Class</b>	8 Corrosive substances
· <b>Label</b>	8
· <b>IATA</b>	
	
· <b>Class</b>	8 Corrosive substances
· <b>Label</b>	8

(Contd. on page 9)



Trade name: 39977 Panel Vibration Control Material

(Contd. of page 8)

· <b>Packing group</b> · <b>DOT, ADR, IMDG, IATA</b>	<i>III</i>
· <b>Environmental hazards:</b>	<i>Product contains environmentally hazardous substances: nonylphenol</i>
· <b>Marine pollutant:</b>	<i>Yes</i>
· <b>Special marking (ADR):</b>	<i>Symbol (fish and tree)</i>
· <b>Special precautions for user</b> · <b>EMS Number:</b> · <b>Segregation groups</b> · <b>Stowage Category</b> · <b>Stowage Code</b>	<i>Warning: Corrosive substances</i> <i>F-A,S-B</i> <i>Acids</i> <i>A</i> <i>SW2 Clear of living quarters.</i>
· <b>Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code</b>	<i>Not applicable.</i>
· <b>Transport/Additional information:</b> · <b>DOT</b> · <b>Quantity limitations</b> · <b>Remarks</b>	<i>On passenger aircraft/rail: 5 L</i> <i>On cargo aircraft only: 60 L</i> <i>ORM-D CFR49-173,150,156,306</i>
· <b>ADR</b> · <b>Excepted quantities (EQ)</b>	<i>Code: E1</i> <i>Maximum net quantity per inner packaging: 30 ml</i> <i>Maximum net quantity per outer packaging: 1000 ml</i>
· <b>IMDG</b> · <b>Limited quantities (LQ)</b> · <b>Excepted quantities (EQ)</b>	<i>5L</i> <i>Code: E1</i> <i>Maximum net quantity per inner packaging: 30 ml</i> <i>Maximum net quantity per outer packaging: 1000 ml</i>
· <b>UN "Model Regulation":</b>	<i>UN 3265 CORROSIVE LIQUID, ACIDIC, ORGANIC, N.O.S. (NONYLPHENOL), 8, III, ENVIRONMENTALLY HAZARDOUS</i>

**15 Regulatory information**

- Safety, health and environmental regulations/legislation specific for the substance or mixture
- Sara

· <b>Section 355 (extremely hazardous substances):</b>	
106-89-8	1-chloro-2,3-epoxypropane
· <b>Section 313 (Specific toxic chemical listings):</b>	
25154-52-3	nonylphenol
107-21-1	ethanediol
106-89-8	1-chloro-2,3-epoxypropane
· <b>TSCA (Toxic Substances Control Act):</b>	
74398-71-3	CASTOR OIL GLYCIDAL ETHER

(Contd. on page 10)

Trade name: 39977 Panel Vibration Control Material

(Contd. of page 9)

140-31-8	2-piperazin-1-ylethylamine
25068-38-6	bisphenolA(chloro)oxirane polymer
67762-90-7	FUMED SILICA
25154-52-3	nonylphenol
90-72-2	2,4,6-tris(dimethylaminomethyl)phenol
107-21-1	ethanediol
1333-86-4	Carbon black
106-89-8	1-chloro-2,3-epoxypropane

· **Proposition 65**

· **Chemicals known to cause cancer:**

74398-71-3	CASTOR OIL GLYCIDAL ETHER
25068-38-6	bisphenolA(chloro)oxirane polymer
107-21-1	ethanediol
1333-86-4	Carbon black
106-89-8	1-chloro-2,3-epoxypropane

· **Chemicals known to cause reproductive toxicity for females:**

None of the ingredients is listed.

· **Chemicals known to cause reproductive toxicity for males:**

106-89-8	1-chloro-2,3-epoxypropane
----------	---------------------------

· **Chemicals known to cause developmental toxicity:**

107-21-1	ethanediol
----------	------------

· **Carcinogenity categories**

· **EPA (Environmental Protection Agency)**

106-89-8	1-chloro-2,3-epoxypropane	B2
----------	---------------------------	----

· **TLV (Threshold Limit Value established by ACGIH)**

107-21-1	ethanediol	A4
1333-86-4	Carbon black	A4
106-89-8	1-chloro-2,3-epoxypropane	A3

· **NIOSH-Ca (National Institute for Occupational Safety and Health)**

1333-86-4	Carbon black
106-89-8	1-chloro-2,3-epoxypropane

· **GHS label elements** The product is classified and labeled according to the Globally Harmonized System (GHS).

· **Hazard pictograms**



GHS05 GHS07 GHS08

· **Signal word** Danger

· **Hazard-determining components of labeling:**

ALIPHATIC AMINE (PROPRIETARY)

nonylphenol

2-piperazin-1-ylethylamine

(Contd. on page 11)



**Trade name: 39977 Panel Vibration Control Material**

(Contd. of page 10)

**CASTOR OIL GLYCIDAL ETHER**

**· Hazard statements**

- H312 Harmful in contact with skin.
- H314 Causes severe skin burns and eye damage.
- H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled.
- H317 May cause an allergic skin reaction.
- H351 Suspected of causing cancer.
- H361 Suspected of damaging fertility or the unborn child.
- H335 May cause respiratory irritation.

**· Precautionary statements**

- P260 Do not breathe dusts or mists.
- P284 [In case of inadequate ventilation] wear respiratory protection.
- P280 Wear protective gloves / protective clothing.
- P280 Wear eye protection / face protection.
- P264 Wash thoroughly after handling.
- P271 Use only outdoors or in a well-ventilated area.
- P272 Contaminated work clothing must not be allowed out of the workplace.
- P201 Obtain special instructions before use.
- P202 Do not handle until all safety precautions have been read and understood.
- P303+P361+P353 If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.
- P305+P351+P338 If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
- P310 Immediately call a POISON CENTER/doctor.
- P321 Specific treatment (see on this label).
- P342+P311 If experiencing respiratory symptoms: Call a POISON CENTER/doctor.
- P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.
- P363 Wash contaminated clothing before reuse.
- P308+P313 IF exposed or concerned: Get medical advice/attention.
- P333+P313 If skin irritation or rash occurs: Get medical advice/attention.
- P301+P330+P331 If swallowed: Rinse mouth. Do NOT induce vomiting.
- P362+P364 Take off contaminated clothing and wash it before reuse.
- P405 Store locked up.
- P403+P233 Store in a well-ventilated place. Keep container tightly closed.
- P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

**· Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

**16 Other information**

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

**· Department issuing SDS:** Environment protection department.

**· Contact:** Steve Gaver (sgaver@semproducts.com)

**· Date of preparation / last revision** 02/22/2016 / 6

**· Abbreviations and acronyms:**

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)

ICAO: International Civil Aviation Organisation

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation

(Contd. on page 12)



**Trade name: 39977 Panel Vibration Control Material**

(Contd. of page 11)

IATA: International Air Transport Association  
ACGIH: American Conference of Governmental Industrial Hygienists  
EINECS: European Inventory of Existing Commercial Chemical Substances  
ELINCS: European List of Notified Chemical Substances  
CAS: Chemical Abstracts Service (division of the American Chemical Society)  
NFPA: National Fire Protection Association (USA)  
HMIS: Hazardous Materials Identification System (USA)  
LC50: Lethal concentration, 50 percent  
LD50: Lethal dose, 50 percent  
PBT: Persistent, Bioaccumulative and Toxic  
vPvB: very Persistent and very Bioaccumulative  
NIOSH: National Institute for Occupational Safety  
OSHA: Occupational Safety & Health  
TLV: Threshold Limit Value  
PEL: Permissible Exposure Limit  
REL: Recommended Exposure Limit  
Acute Tox. 4: Acute toxicity, Hazard Category 4  
Skin Corr. 1B: Skin corrosion/irritation, Hazard Category 1B  
Eye Dam. 1: Serious eye damage/eye irritation, Hazard Category 1  
Resp. Sens. 1: Sensitisation - Respirat., Hazard Category 1  
Skin Sens. 1: Sensitisation - Skin, Hazard Category 1  
Carc. 2: Carcinogenicity, Hazard Category 2  
Repr. 2: Reproductive toxicity, Hazard Category 2  
STOT SE 3: Specific target organ toxicity - Single exposure, Hazard Category 3

· **\* Data compared to the previous version altered.**

USA