



HI-TECH PRIMERS

A fast drying spray primer that provides maximum rust protection and adhesion for a finishing top coat. Can be used with lacquer, enamel, and acrylic paints. Provides excellent resistance to heat and corrosion. VOC compliant. For best results, sand lightly with fine sandpaper or steel wool prior to applying finish coat.

Suggested Uses:

Wood and metal
Machinery
Engine blocks
Lawn furniture
Vehicle parts

Packaging:

UPC Code	043281000079
Cans per case	6
Shipping weight per case	7 lbs.
Container	16 fluid ounce can
Label weight	12 ounces (340 grams)
Shipping Classification	Consumer Commodity ORM-D, UN 1950
Hazard Class	2.1

Properties:

Coverage	Up to 15 square feet
Cleanup	Paint or lacquer thinner
Flammability	Extremely Flammable
Flash point	-4F
Specific Gravity	0.80
Solids Content	23%
MIR value	0.66, cannot exceed 0.70
HAPs content	11%
Storage Temperature	40-100F
Application Temperature	50-90F
Durability	Good
Abrasion Resistance	Good
Heat Resistance	250F
Resin System	Phenolic
Shelf life	Guaranteed for 2 years
Food contact rating	No

Dry Time*:

To touch	5 minutes
To topcoat	30 minutes

*At 72F, 50% humidity,
1.5 mil thickness

**Curing/Recoat time is extended with
multiple coats and excessively thick coats**

Gloss*: Flat, <15

*as measured on a 60 degree gloss meter

Available Colors:

Part #	Description	UPC Code
16-805	White	043281005548
16-807	Red Iron Oxide	043281000994
16-828	Black	043281001044
16-831	Light Gray	043281001052

12-12-2019