

Safety Data Sheet

Printing date 05/28/2015

Revised On 03/19/2015

1 Identification of the substance and manufacturer

Trade name: SPRUCE GLOSS BLACK LACQUER
Product code: 0000980018
Product category: PC9a Paints and coatings.
Manufacturer/Supplier: Seymour of Sycamore
 917 Crosby Avenue
 Sycamore, IL 60178
 Phone: 815-895-9101 www.seymourpaint.com
Emergency telephone number: CHEMTEL 1-800-255-3924, or 813-248-0585.



2 Hazard(s) identification

Classification of the substance or mixture

Flam. Aerosol 1 H222 Extremely flammable aerosol.
 Press. Gas H280 Contains gas under pressure; may explode if heated.
 Carc. 2 H351 Suspected of causing cancer.
 Repr. 2 H361 Suspected of damaging fertility or the unborn child.
 STOT RE 2 H373 May cause damage to organs through prolonged or repeated exposure.
 Eye Irrit. 2A H319 Causes serious eye irritation.
 STOT SE 3 H336 May cause drowsiness or dizziness.

GHS Hazard pictograms



GHS02 GHS04 GHS07 GHS08

Signal word

Hazard statements

Danger
 Extremely flammable aerosol.
 Contains gas under pressure; may explode if heated.
 Causes serious eye irritation.
 Suspected of causing cancer.
 Suspected of damaging fertility or the unborn child.
 May cause drowsiness or dizziness.

Precautionary statements

May cause damage to organs through prolonged or repeated exposure.
 If medical advice is needed, have product container or label at hand.
 Keep out of reach of children.
 Read label before use.
 Obtain special instructions before use.
 Keep away from heat/sparks/open flames/hot surfaces. - No smoking.
 Do not spray on an open flame or other ignition source.
 Pressurized container: Do not pierce or burn, even after use.
 Wash hands thoroughly after handling.
 Use only outdoors or in a well-ventilated area.
 Wear protective gloves/protective clothing/eye protection/face protection.
 Do not handle until all safety precautions have been read and understood.
 Do not breathe dust/fume/gas/mist/vapors/spray.
 IF INHALED: Remove person to fresh air and keep comfortable for breathing.
 If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
 Call a poison center/doctor if you feel unwell.
 If eye irritation persists: Get medical advice/attention.
 Store locked up.
 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.
 Store in a well-ventilated place. Keep container tightly closed.
 Dispose of contents/container in accordance with local/regional/national/international regulations.

3 Composition/information on ingredients

Chemical characterization: Mixtures

Chemical Description: This product is a mixture of the substances listed below with nonhazardous additions.

Dangerous components:

67-64-1	Acetone	30.72%
74-98-6	propane	13.91%
108-10-1	methyl isobutyl ketone	13.38%
106-97-8	n-butane	8.17%
108-88-3	Toluene	4.09%
64-17-5	ethyl alcohol	3.86%
78-93-3	methyl ethyl ketone	3.81%
111-76-2	Glycol Ether EB	3.33%
108-21-4	isopropyl acetate	3.08%
67-63-0	isopropyl alcohol	2.08%

4 First-aid measures

After inhalation: Supply fresh air; consult doctor in case of complaints.
After skin contact: Remove contaminated clothing. Wash exposed area with soap and water.
After eye contact: Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.
After swallowing: Rinse out mouth and then drink plenty of water.
 Rinse mouth with water. Do not induce vomiting.

(Contd. on page 2)

Safety Data Sheet

Printing date 05/28/2015

Revised On 03/19/2015

Trade name: SPRUCE GLOSS BLACK LACQUER

(Contd. of page 1)

Most important symptoms and effects:

Dizziness

Indication of any immediate medical attention needed:

No further relevant information available.

5 Fire-fighting measures**Extinguishing agents:**CO₂, extinguishing powder or water spray. Fight larger fires with water spray.**Special hazards:**

Can form explosive gas-air mixtures.

Protective equipment for firefighters:

A respiratory protective device may be necessary.

6 Accidental release measures**Personal precautions, protective equipment and emergency procedures:**Wear protective equipment. Keep unprotected persons away.
Use respiratory protective device against the effects of fumes/dust/aerosol.**Methods and material for containment and cleaning up:**

Ensure adequate ventilation.

7 Handling and storage**Precautions for safe handling**

Use only in well ventilated areas.

Storage requirements:

Keep away from sources of heat and direct sunlight. Do not warehouse in subfreezing conditions. Store locked up.

8 Exposure controls/personal protection**Components with limit values that require monitoring at the workplace:****67-64-1 Acetone**

PEL (USA)	Long-term value: 2400 mg/m ³ , 1000 ppm
REL (USA)	Long-term value: 590 mg/m ³ , 250 ppm
TLV (USA)	Short-term value: (1782) NIC-1187 mg/m ³ , (750) NIC-500 ppm
	Long-term value: (1188) NIC-594 mg/m ³ , (500) NIC-250 ppm
	BEI

74-98-6 propane

PEL (USA)	Long-term value: 1800 mg/m ³ , 1000 ppm
REL (USA)	Long-term value: 1800 mg/m ³ , 1000 ppm
TLV (USA)	refer to Appendix F

108-10-1 methyl isobutyl ketone

PEL (USA)	Long-term value: 410 mg/m ³ , 100 ppm
REL (USA)	Short-term value: 300 mg/m ³ , 75 ppm
	Long-term value: 205 mg/m ³ , 50 ppm
TLV (USA)	Short-term value: 307 mg/m ³ , 75 ppm
	Long-term value: 82 mg/m ³ , 20 ppm
	BEI

106-97-8 n-butane

REL (USA)	Long-term value: 1900 mg/m ³ , 800 ppm
TLV (USA)	Short-term value: 2370 mg/m ³ , 1000 ppm

108-88-3 Toluene

PEL (USA)	Long-term value: 200 ppm
	Ceiling limit value: 300; 500* ppm
	*10-min peak per 8-hr shift
REL (USA)	Short-term value: 560 mg/m ³ , 150 ppm
	Long-term value: 375 mg/m ³ , 100 ppm
TLV (USA)	Long-term value: 75 mg/m ³ , 20 ppm
	BEI

64-17-5 ethyl alcohol

PEL (USA)	Long-term value: 1900 mg/m ³ , 1000 ppm
REL (USA)	Long-term value: 1900 mg/m ³ , 1000 ppm
TLV (USA)	Short-term value: 1880 mg/m ³ , 1000 ppm

78-93-3 methyl ethyl ketone

PEL (USA)	Long-term value: 590 mg/m ³ , 200 ppm
REL (USA)	Short-term value: 885 mg/m ³ , 300 ppm
	Long-term value: 590 mg/m ³ , 200 ppm
TLV (USA)	Short-term value: 885 mg/m ³ , 300 ppm
	Long-term value: 590 mg/m ³ , 200 ppm
	BEI

111-76-2 Glycol Ether EB

PEL (USA)	Long-term value: 240 mg/m ³ , 50 ppm
	Skin
REL (USA)	Long-term value: 24 mg/m ³ , 5 ppm
	Skin

(Contd. on page 3)

Safety Data Sheet

Printing date 05/28/2015

Revised On 03/19/2015

Trade name: SPRUCE GLOSS BLACK LACQUER

(Contd. of page 2)

TLV (USA)	Long-term value: 97 mg/m ³ , 20 ppm BEI
108-21-4 isopropyl acetate	
PEL (USA)	Long-term value: 950 mg/m ³ , 250 ppm
TLV (USA)	Short-term value: 836 mg/m ³ , 200 ppm Long-term value: 418 mg/m ³ , 100 ppm
67-63-0 isopropyl alcohol	
PEL (USA)	Long-term value: 980 mg/m ³ , 400 ppm
REL (USA)	Short-term value: 1225 mg/m ³ , 500 ppm Long-term value: 980 mg/m ³ , 400 ppm
TLV (USA)	Short-term value: 984 mg/m ³ , 400 ppm Long-term value: 492 mg/m ³ , 200 ppm BEI
Ingredients with biological limit values:	
67-64-1 Acetone	
BEI (USA)	50 mg/L Medium: urine Time: end of shift Parameter: Acetone (nonspecific)
108-10-1 methyl isobutyl ketone	
BEI (USA)	1 mg/L Medium: urine Time: end of shift Parameter: MIBK
108-88-3 Toluene	
BEI (USA)	0.02 mg/L Medium: blood Time: prior to last shift of workweek Parameter: Toluene
	0.03 mg/L Medium: urine Time: end of shift Parameter: Toluene
	0.3 mg/g creatinine Medium: urine Time: end of shift Parameter: o-Cresol with hydrolysis (background)
78-93-3 methyl ethyl ketone	
BEI (USA)	2 mg/L Medium: urine Time: end of shift Parameter: MEK
111-76-2 Glycol Ether EB	
BEI (USA)	200 mg/g creatinine Medium: urine Time: end of shift Parameter: Butoxyacetic acid with hydrolysis
67-63-0 isopropyl alcohol	
BEI (USA)	40 mg/L Medium: urine Time: end of shift at end of workweek Parameter: Acetone (background, nonspecific)

Hygienic protection:	Keep away from foodstuffs and animal feed. Wash hands after use. Immediately remove all soiled and contaminated clothing. Wash hands after use. Avoid contact with the eyes and skin. Do not eat or drink while working.
Breathing equipment:	A respirator is generally not necessary when using this product outdoors or in large open areas. In cases where short and/or long term overexposure exists, a charcoal filter respirator should be worn. If you suspect overexposure conditions exist, please consult an authority on chemical hygiene.
Hand protection:	Protective gloves. The glove material must be impermeable and resistant to the substance.
Eye protection:	Tightly sealed goggles

9 Physical and chemical properties

Appearance:	Aerosol.
Odor:	Aromatic
Odor threshold:	Not determined.
pH-value:	Not determined.
Melting point/Melting range	Undetermined.
Boiling point:	-44 °C (-47 °F)
Flash point:	-19 °C (-2 °F)
Flammability (solid, gas):	Extremely flammable.
Decomposition temperature:	Not determined.

(Contd. on page 4)

Safety Data Sheet

Printing date 05/28/2015

Revised On 03/19/2015

Trade name: SPRUCE GLOSS BLACK LACQUER

(Contd. of page 3)

Auto igniting:	Product is not self-igniting.
Danger of explosion:	In use, may form flammable/explosive vapour-air mixture.
Lower Explosion Limit:	1.7 Vol %
Upper Explosion Limit:	10.9 Vol %
Vapor pressure:	Not determined.
Relative Density:	Between 0.77 and 0.85 (Water equals 1.00)
Vapour density	Not determined.
Evaporation rate	Not applicable.
Partition coefficient: n-octonal/water:	Not determined.
Solubility:	Not determined.
Viscosity:	Not determined.
VOC content:	611.5 g/l / 5.10 lb/gl
VOC content (less exempt solvents):	57.2 %
MIR Value:	1.34
Solids content:	10.2 %

10 Stability and reactivity

Reactivity:	Stable at normal temperatures.
Conditions to avoid:	Do not allow can to exceed 120 degrees Fahrenheit. Do not warehouse in subfreezing temperatures.
Chemical stability:	Not fully evaluated.
Possibility of hazardous reactions:	No dangerous reactions known.
Incompatible materials:	No further relevant information available.
Hazardous decomposition:	No dangerous decomposition products known.

11 Toxicological information**LD/LC50 values that are relevant for classification:****108-10-1 methyl isobutyl ketone**

Oral	LD50	2100 mg/kg (rat)
Dermal	LD50	16000 mg/kg (rab)
Inhalative	LC50/4 h	8.3-16.6 mg/l (rat)

106-97-8 n-butane

Inhalative	LC50/4 h	658 mg/l (rat)
------------	----------	----------------

64-17-5 ethyl alcohol

Oral	LD50	7060 mg/kg (rat)
Inhalative	LC50/4 h	20000 mg/l (rat)

78-93-3 methyl ethyl ketone

Oral	LD50	3300 mg/kg (rat)
Dermal	LD50	5000 mg/kg (rbt)

111-76-2 Glycol Ether EB

Oral	LD50	1480 mg/kg (rat)
Dermal	LD50	400 mg/kg (rab)

108-21-4 isopropyl acetate

Oral	LD50	9800 mg/kg (rat)
------	------	------------------

67-63-0 isopropyl alcohol

Oral	LD50	4570 mg/kg (rat)
Dermal	LD50	13400 mg/kg (rab)
Inhalative	LC50/4 h	30 mg/l (rat)

Information on toxicological effects:	No data available.
Skin effects:	No irritant effect.
Eye effects:	Irritating effect.
Sensitization:	No sensitizing effects known.

Carcinogenic categories**IARC (International Agency for Research on Cancer)**

108-10-1	methyl isobutyl ketone	2B
108-88-3	Toluene	3
64-17-5	ethyl alcohol	1
111-76-2	Glycol Ether EB	3
67-63-0	isopropyl alcohol	3

NTP (National Toxicology Program)

None of the ingredients is listed.

12 Ecological information

Aquatic toxicity:	Hazardous for water, do not empty into drains.
Persistence and degradability:	The product is degradable after prolonged exposure to natural weathering processes.
Bioaccumulative potential:	No further relevant information available.
Mobility in soil:	No further relevant information available.

(Contd. on page 5)

Safety Data Sheet

Printing date 05/28/2015

Revised On 03/19/2015

Trade name: SPRUCE GLOSS BLACK LACQUER

Other adverse effects: No further relevant information available.

(Contd. of page 4)

13 Disposal considerations

Dispose of in accordance with local, state, and federal regulations. Do not puncture, incinerate, or compact. Partially empty cans must be disposed of responsibly. Do not heat or cut empty containers with electric or gas torches.

Recommendation: Completely empty cans should be recycled.**14 Transport information**

UN-Number	UN1950
DOT	N/A
DOT	UN1950
ADR	Consumer Commodity ORM-D
Transport hazard class(es):	Aerosols, flammable
Class	1950 Aerosols
Marine pollutant:	2.1
Special precautions for user:	No
EMS Number:	Warning: Gases
Quantity limitations	F-D,S-U
	On passenger aircraft/rail: 75 kg
	On cargo aircraft only: 150 kg

ADR	
Excepted quantities (EQ)	Code: E0
	Not permitted as Excepted Quantity

IMDG

Limited quantities (LQ)	1L
Excepted quantities (EQ)	Code: E0
	Not permitted as Excepted Quantity
Packaging Group:	--
UN "Model Regulation":	UN1950, Aerosols, 2.1

15 Regulatory information**SARA Section 355 (extremely hazardous substances):**

None of the ingredients in this product are listed.

SARA Section 313 (Specific toxic chemical listings):

108-10-1	methyl isobutyl ketone
108-88-3	Toluene
78-93-3	methyl ethyl ketone
111-76-2	Glycol Ether EB
67-63-0	isopropyl alcohol

CPSC: This product complies with 16 CFR 1303 and does not contain more than 90 ppm of lead.**California Proposition 65 chemicals known to cause cancer:**

108-10-1	methyl isobutyl ketone
1333-86-4	Carbon black

California Proposition 65 chemicals known to cause developmental toxicity:

108-88-3	Toluene
67-56-1	Methanol

CANADIAN ENVIRONMENTAL PROTECTION ACT:

All hazardous ingredients for this product appear on the Canadian Domestic Substance List.

EPA:

67-64-1	Acetone	I
108-10-1	methyl isobutyl ketone	I
108-88-3	Toluene	II
78-93-3	methyl ethyl ketone	I
111-76-2	Glycol Ether EB	NL

16 Other information

Contact:	Regulatory Affairs
Date of preparation / last revision	05/28/2015 / -