



SPRUCE ENGINE ENAMELS

This is a fast dry spray paint that restores engines to their original factory color. Protects engines, transmissions, and other O.E.M. Equipment. Resists heat to 250°F and does not crack or peel. For maximum protection, rusted metal surfaces should be wire brushed and primed with the Spruce primers. See separate product information sheet for 98-41 and 98-50.

Suggested Uses:

Engine blocks
Valve covers
Water pumps
Cylinder heads
Oil pans
Railings

Packaging:

Cans per case	12
Shipping weight per case	15 lbs.
Container	16 fluid ounce can
Label weight	12 ounces (340 grams)
Shipping Classification	Consumer Commodity ORM-D, UN 1950
Hazard Class	2.1

Properties:

Coverage	Up to 15 square feet
Cleanup	Paint or lacquer thinner
Flammability	Extremely Flammable
Specific Gravity	0.86
Solids Content	15%
MIR value	0.88, cannot exceed 0.95
HAPs content	13%
Storage Temperature	40-100F
Application Temperature	50-90F
Gasoline Resistance	No
Heat Resistance	250F
Resin System	V.T. Alkyd
Shelf life	Guaranteed for 2 years

Dry Time*:

To touch	5 minutes
To recoat	30 minutes

*At 72F, 50% humidity,
1.5 mil thickness

**Curing/Recoat time is extended with
multiple coats and excessively thick coats**

Gloss*: High Gloss, >85

*as measured on a 60 degree gloss meter

Available Colors:

Part #	Description	UPC Code
98-42	Universal Black	043281002660
98-43	Ford Gray	043281002677
98-44	Ford/Chrysler Red	043281002684
98-46	Ford Blue	043281002707
98-48	Chevy Orange	043281002714
98-53	Cadillac Blue	043281002738
98-56	Ford/Mustang Blue	043281002745
98-67	G.M. Blue	043281002776

12-19-2019