

FINISH CUT™

NO SWIRLS COMPOUND



WIZARDS DATA SHEET • COMPLETE PRODUCT INFORMATION

AUTOMOTIVE

32 fl. oz. - 946 ml
Part No. 11040
6/case
Net Wt. 15 lbs.

1 Gallon - 3.785 liters
Part No. 11041
4/case
Net Wt. 36 lbs.

DETAILING • CLEANING • PROTECTION

DESCRIPTION:

WIZARDS® FINISH CUT™ is a medium to fine, No Swirls Compound designed for machine or hand application. It is recommended for removing 1500 grit or finer sand scratches (or similar sized finish imperfections) from new or aged paint finishes – factory, custom - foreign or domestic.


BENEFITS:

FINISH CUT™ is a buffing compound that levels 1500 and finer grit sand scratches from fresh paint and clears, leaving a swirl-free, show gloss finish. Depending on color, type and age of paint, FINISH CUT™ (when used with the blended wool pad #11203) can be used as a one step product to cut and finish with superior results. This is made possible by the use of a series of nonrigid abrasives that provide excellent initial leveling action and slowly become less aggressive while buffing. In addition, the proper choice and use of pads for each job will determine the amount of cut and the degree of desired shine. Using one product with 2 or 3 different pads proves to be faster, less expensive and minimizes dust, dirt and contamination.



FEATURES:

- VOC compliant. FINISH CUT™ contains no wax, silicone or crystalline silica.
- Levels 1500 grit or finer sand scratches.
- No swirls, show gloss buffing on most colors and clear coats, fresh or aged.
- Brightens dull finishes, removes scratches and heavy overspray.
- Water based system for easy cleanup without staining, etching or dusting.



HOW TO USE:

Make sure painted surfaces are clean, cool and dry. Shake product and apply a generous amount to one spot, not ribbons or specks. Place pad directly on top of compound, running buffer speed at 1000-2200 RPM. Move slowly, avoiding fast back and forth motions. Work a 2 to 4 square foot section at a time. Apply adequate pressure to remove scratches and speed up the process.

HINT: For best results use our BLENDED WOOL PAD #11203. Follow with the WHITE FOAM CUTTING PAD #11310 or the GRAY FOAM FINISHING PAD #11312. Remove residue to inspect surface using WIPE DOWN™ Detailer #01220. For maximum protection and high gloss, use SHINE MASTER™ Polish and Breathable™ Sealant #11033 as the final step.